PyPDF2

Mathieu Fenniak

Apr 01, 2024

USER GUIDE

1	Installation	3
2	Migration Guide: 1.x to 2.x	5
3	Imports and Modules	7
4	Naming Adjustments	9
5	Robustness and strict=False	15
6	Exceptions, Warnings, and Log messages	17
7	Metadata	19
8	Extract Text from a PDF	21
9	Extract Images	25
10	Encryption and Decryption of PDFs	27
11	Merging PDF files	29
12	Cropping and Transforming PDFs	33
13	Adding a Stamp/Watermark to a PDF	47
14	Reading PDF Annotations	51
15	Adding PDF Annotations	53
16	Interactions with PDF Forms	59
17	Streaming Data with PyPDF2	61
18	Reduce PDF Size	63
19	PDF Version Support	65
20	The PdfReader Class	67
21	The PdfWriter Class	73
22	The PdfMerger Class	85

23 The PageObject Class	89
24 The Transformation Class	97
25 The DocumentInformation Class	99
26 The XmpInformation Class	101
27 The Destination Class	105
28 The RectangleObject Class	107
29 The Field Class	109
30 The PageRange Class	111
31 The AnnotationBuilder Class	113
32 The Fit Class	115
33 The PaperSize Class	117
34 Developer Intro	119
35 The PDF Format	121
36 CMaps	125
37 The Deprecation Process	127
38 Testing	129
39 CHANGELOG	131
40 Changelog of PyPDF2 1.X	157
41 Project Governance	181
42 History of PyPDF2	185
43 Contributors	187
44 PyPDF2 vs X	189
45 Frequently-Asked Questions	191
46 Indices and tables	193
Index	195

Note: This page is about PyPDF2. PyPDF2 is deprecated, please use pypdf

PyPDF2 is a free and open source pure-python PDF library capable of splitting, merging, cropping, and transforming the pages of PDF files. It can also add custom data, viewing options, and passwords to PDF files. PyPDF2 can retrieve text and metadata from PDFs as well.

You can contribute to PyPDF2 on GitHub.

ONE

INSTALLATION

There are several ways to install PyPDF2. The most common option is to use pip.

1.1 pip

PyPDF2 requires Python 3.6+ to run.

Typically Python comes with pip, a package installer. Using it you can install PyPDF2:

pip install PyPDF2

If you are not a super-user (a system administrator / root), you can also just install PyPDF2 for your current user:

pip install --user PyPDF2

1.1.1 Optional dependencies

PyPDF2 tries to be as self-contained as possible, but for some tasks the amount of work to properly maintain the code would be too high. This is especially the case for cryptography and image formats.

If you simply want to install all optional dependencies, run:

pip install PyPDF2[full]

Alternatively, you can install just some:

If you plan to use PyPDF2 for encrypting or decrypting PDFs that use AES, you will need to install some extra dependencies. Encryption using RC4 is supported using the regular installation.

pip install PyPDF2[crypto]

If you plan to use image extraction, you need Pillow:

pip install PyPDF2[image]

1.2 Python Version Support

Python	3.10	3.9	3.8	3.7	3.6	2.7
PyPDF2>=2.0	YES	YES	YES	YES	YES	
PyPDF2 1.20.0 - 1.28.4	YES	YES	YES	YES	YES	YES
PyPDF2 1.15.0 - 1.20.0						YES

1.3 Anaconda

Anaconda users can install PyPDF2 via conda-forge.

1.4 Development Version

In case you want to use the current version under development:

pip install git+https://github.com/py-pdf/PyPDF2.git

MIGRATION GUIDE: 1.X TO 2.X

PyPDF2<2.0.0 (docs) is very different from PyPDF2>=2.0.0 (docs).

Luckily, most changes are simple naming adjustments. This guide helps you to make the step from PyPDF2 1.x (or even the original PyPpdf) to PyPDF2>=2.0.0.

You can execute your code with the updated version and show deprecation warnings by running python -W all your_code.py.

THREE

IMPORTS AND MODULES

- PyPDF2.utils no longer exists
- PyPDF2.pdf no longer exists. You can import from PyPDF2 directly or from PyPDF2.generic

FOUR

NAMING ADJUSTMENTS

4.1 Classes

The base classes were renamed as they also allow to operate with ByteIO streams instead of files. Also, the strict paramter changed the default value from strict=True to strict=False.

- PdfFileReader PdfReader
- PdfFileWriter PdfWriter
- PdfFileMerger PdfMerger

PdfFileReader and PdfFileMerger no longer have the overwriteWarnings parameter. The new behavior is overwriteWarnings=False.

4.2 Function, Method, and Property Names

In PyPDF2.xmp.XmpInformation:

- rdfRoot rdf_root
- xmp_createDate xmp_create_date
- xmp_creatorTool xmp_creator_tool
- xmp_metadataDate xmp_metadata_date
- xmp_modifyDate xmp_modify_date
- xmpMetadata xmp_metadata
- xmpmm_documentId xmpmm_document_id
- xmpmm_instanceId xmpmm_instance_id

In PyPDF2.generic:

- readObject read_object
- convertToInt convert_to_int
- DocumentInformation.getText DocumentInformation._get_text : This method should typically not be used; please let me know if you need it.
- readHexStringFromStream read_hex_string_from_stream
- initializeFromDictionary initialize_from_dictionary
- createStringObject create_string_object

- TreeObject.hasChildren TreeObject.has_children
- TreeObject.emptyTree TreeObject.empty_tree

In many places:

- getObject get_object
- writeToStream write_to_stream
- readFromStream read_from_stream

PdfReader class:

- reader.getPage(pageNumber) reader.pages[page_number]
- reader.getNumPages() / reader.numPages len(reader.pages)
- getDocumentInfo metadata
- flattenedPages attribute flattened_pages
- resolvedObjects attribute resolved_objects
- xrefIndex attribute xref_index
- getNamedDestinations / namedDestinations attribute named_destinations
- getPageLayout / pageLayout page_layout attribute
- getPageMode / pageMode page_mode attribute
- getIsEncrypted / isEncrypted is_encrypted attribute
- getOutlines get_outlines
- readObjectHeader read_object_header
- cacheGetIndirectObject cache_get_indirect_object
- cacheIndirectObject cache_indirect_object
- getDestinationPageNumber get_destination_page_number
- readNextEndLine read_next_end_line
- _zeroXref _zero_xref
- _authenticateUserPassword _authenticate_user_password
- _pageId2Num attribute _page_id2num
- _buildDestination _build_destination
- _buildOutline _build_outline
- _getPageNumberByIndirect(indirectRef) _get_page_number_by_indirect(indirect_ref)
- _getObjectFromStream _get_object_from_stream
- _decryptObject _decrypt_object
- _flatten(..., indirectRef) _flatten(..., indirect_ref)
- _buildField _build_field
- _checkKids _check_kids
- _writeField _write_field
- _write_field(..., fieldAttributes) _write_field(..., field_attributes)

```
• _read_xref_subsections(..., getEntry, ...) _read_xref_subsections(..., get_entry, ...)
```

PdfWriter class:

- writer.getPage(pageNumber) writer.pages[page_number]
- writer.getNumPages() len(writer.pages)
- addMetadata add_metadata
- addPage add_page
- addBlankPage add_blank_page
- addAttachment(fname, fdata) add_attachment(filename, data)
- insertPage insert_page
- insertBlankPage insert_blank_page
- appendPagesFromReader append_pages_from_reader
- updatePageFormFieldValues update_page_form_field_values
- cloneReaderDocumentRoot clone_reader_document_root
- cloneDocumentFromReader clone_document_from_reader
- getReference get_reference
- getOutlineRoot get_outline_root
- getNamedDestRoot get_named_dest_root
- addBookmarkDestination add_bookmark_destination
- addBookmarkDict add_bookmark_dict
- addBookmark add_bookmark
- addNamedDestinationObject add_named_destination_object
- addNamedDestination add_named_destination
- removeLinks remove_links
- removeImages(ignoreByteStringObject) remove_images(ignore_byte_string_object)
- removeText(ignoreByteStringObject) remove_text(ignore_byte_string_object)
- addURI add_uri
- addLink add_link
- getPage(pageNumber) get_page(page_number)
- getPageLayout / setPageLayout / pageLayout page_layout attribute
- getPageMode / setPageMode / pageMode page_mode attribute
- _addObject _add_object
- _addPage _add_page
- _sweepIndirectReferences _sweep_indirect_references

PdfMerger class

• __init__ parameter: strict=True strict=False (the PdfFileMerger still has the old default)

- addMetadata add_metadata
- addNamedDestination add_named_destination
- setPageLayout set_page_layout
- setPageMode set_page_mode

Page class:

- artBox / bleedBox / cropBox / mediaBox / trimBox artbox / bleedbox / cropbox / mediabox / trimbox
 - getWidth, getHeight width / height
 - getLowerLeft_x/getUpperLeft_x left
 - getUpperRight_x/getLowerRight_x right
 - getLowerLeft_y/getLowerRight_y bottom
 - getUpperRight_y / getUpperLeft_y top
 - getLowerLeft / setLowerLeft lower_left property
 - upperRight upper_right
- mergePage merge_page
- rotateClockwise / rotateCounterClockwise rotate_clockwise
- _mergeResources _merge_resources
- _contentStreamRename _content_stream_rename
- _pushPopGS _push_pop_gs
- _addTransformationMatrix _add_transformation_matrix
- _mergePage _merge_page

XmpInformation class:

- getElement(..., aboutUri, ...) get_element(..., about_uri, ...)
- getNodesInNamespace(..., aboutUri, ...) get_nodes_in_namespace(..., aboutUri, ...)
- _getText _get_text

utils.py:

- matrixMultiply `matrix_multiply
- RC4_encrypt is moved to the security module

4.3 Parameter Names

- PdfWriter.get_page: pageNumber page_number
- PyPDF2.filters (all classes): decodeParms decode_parms
- PyPDF2.filters (all classes): decodeStreamData decode_stream_data
- pagenum page_number
- PdfMerger.merge: position page_number
- PdfWriter.add_outline_item_destination: dest page_destination

- PdfWriter.add_named_destination_object: dest page_destination
- PdfWriter.encrypt: user_pwd user_password
- PdfWriter.encrypt: owner_pwd owner_password

4.4 Deprecations

A few classes / functions were deprecated without replacement:

- PyPDF2.utils.ConvertFunctionsToVirtualList
- PyPDF2.utils.formatWarning
- PyPDF2.isInt(obj): Use instance(obj, int) instead
- PyPDF2.u_(s): Use s directly
- PyPDF2.chr_(c): Use chr(c) instead
- PyPDF2.barray(b): Use bytearray(b) instead
- PyPDF2.isBytes(b): Use instance(b, type(bytes())) instead
- PyPDF2.xrange_fn: Use range instead
- PyPDF2.string_type: Use strinstead
- PyPDF2.isString(s): Use instance(s, str) instead
- PyPDF2._basestring: Use str instead
- b_(...) was removed. You should typically be able use the bytes object directly, otherwise you can copy this

ROBUSTNESS AND STRICT=FALSE

PDF is specified in various versions. The specification of PDF 1.7 has 978 pages. This length makes it hard to get everything right. As a consequence, a lot of PDF files are not strictly following the specification.

If a PDF file does not follow the specification, it is not always possible to be certain what the intended effect would be. Think of the following broken Python code as an example:

```
# Broken
function (foo, bar):
# Potentially intended:
def function(foo, bar):
....
# Also possible:
function = (foo, bar)
```

Writing a parser you can go two paths: Either you try to be forgiving and try to figure out what the user intended, or you are strict and just tell the user that they should fix their stuff.

PyPDF2 gives you the option to be strict or not.

PyPDF2 has three core objects and all of them have a strict parameter:

- PdfReader
- PdfWriter
- PdfMerger

Choosing strict=True means that PyPDF2 will raise an exception if a PDF does not follow the specification.

Choosing strict=False means that PyPDF2 will try to be forgiving and do something reasonable, but it will log a warning message. It is a best-effort approach.

EXCEPTIONS, WARNINGS, AND LOG MESSAGES

PyPDF2 makes use of 3 mechanisms to show that something went wrong:

- Log messages are informative messages that can be used for post-mortem analysis. Most of the time, users can ignore them. They come in different *levels*, such as info / warning / error indicating the severity. Examples are non-standard compliant PDF files which PyPDF2 can deal with.
- Warnings are avoidable issues, such as using deprecated classes / functions / parameters. Another example is missing capabilities of PyPDF2. In those cases, PyPDF2 users should adjust their code. Warnings are issued by the warnings module those are different from the log-level "warning".
- Exceptions are error-cases that PyPDF2 users should explicitly handle. In the strict=True mode, most log messages with the warning level will become exceptions. This can be useful in applications where you can force to user to fix the broken PDF.

6.1 Exceptions

Exeptions need to be catched if you want to handle them. For example, you could want to read the text from a PDF as a part of a search function.

Most PDF files don't follow the specifications. In this case PyPDF2 needs to guess which kinds of mistakes were potentially done when the PDF file was created. See the robustness page for the related issues.

As a users, you likely don't care about it. If it's readable in any way, you want the text. You might use pdfminer.six as a fallback and do this:

```
from PyPDF2 import PdfReader
from pdfminer.high_level import extract_text as fallback_text_extraction
text = ""
try:
    reader = PdfReader("example.pdf")
    for page in reader.pages:
        text += page.extract_text()
except Exception as exc:
    text = fallback_text_extraction("example.pdf")
```

You could also capture PyPDF2.errors.PyPdfError if you prefer something more specific.

6.2 Warnings

The warnings module allows you to ignore warnings:

import warnings

```
warnings.filterwarnings("ignore")
```

In many cases, you actually want to start Python with the -W flag so that you see all warnings. This is especially true for Continuous Integration (CI).

6.3 Log messages

Log messages can be noisy in some cases. PyPDF2 hopefully is having a reasonable level of log messages, but you can reduce which types of messages you want to see:

```
import logging
logger = logging.getLogger("PyPDF2")
```

logger.setLevel(logging.ERROR)

The logging module defines six log levels:

- CRITICAL
- ERROR
- WARNING
- INFO
- DEBUG
- NOTSET

SEVEN

METADATA

7.1 Reading metadata

```
from PyPDF2 import PdfReader
reader = PdfReader("example.pdf")
meta = reader.metadata
print(len(reader.pages))
# All of the following could be None!
print(meta.author)
print(meta.creator)
print(meta.producer)
print(meta.subject)
print(meta.title)
```

7.2 Writing metadata

(continues on next page)

(continued from previous page)

```
with open("meta-pdf.pdf", "wb") as f:
    writer.write(f)
```

EIGHT

EXTRACT TEXT FROM A PDF

You can extract text from a PDF like this:

```
from PyPDF2 import PdfReader
reader = PdfReader("example.pdf")
page = reader.pages[0]
print(page.extract_text())
```

you can also choose to limit the text orientation you want to extract, e.g:

```
# extract only text oriented up
print(page.extract_text(0))
# extract text oriented up and turned left
print(page.extract_text((0, 90)))
```

Refer to extract_text for more details.

8.1 Using a visitor

You can use visitor-functions to control which part of a page you want to process and extract. The visitor-functions you provide will get called for each operator or for each text fragment.

The function provided in argument visitor_text of function extract_text has five arguments: current transformation matrix, text matrix, font-dictionary and font-size. In most cases the x and y coordinates of the current position are in index 4 and 5 of the current transformation matrix.

The font-dictionary may be None in case of unknown fonts. If not None it may e.g. contain key "/BaseFont" with value "/Arial,Bold".

Caveat: In complicated documents the calculated positions might be wrong.

The function provided in argument visitor_operand_before has four arguments: operand, operand-arguments, current transformation matrix and text matrix.

8.1.1 Example 1: Ignore header and footer

The following example reads the text of page 4 of this PDF document, but ignores header (y < 720) and footer (y > 50).

```
from PyPDF2 import PdfReader

reader = PdfReader("GeoBase_NHNC1_Data_Model_UML_EN.pdf")
page = reader.pages[3]

parts = []

def visitor_body(text, cm, tm, fontDict, fontSize):
    y = tm[5]
    if y > 50 and y < 720:
        parts.append(text)

page.extract_text(visitor_text=visitor_body)
text_body = "".join(parts)
print(text_body)</pre>
```

8.1.2 Example 2: Extract rectangles and texts into a SVG-file

The following example converts page 3 of this PDF document into a SVG file.

Such a SVG export may help to understand whats going on in a page.

```
from PyPDF2 import PdfReader
import svgwrite
reader = PdfReader("GeoBase_NHNC1_Data_Model_UML_EN.pdf")
page = reader.pages[2]
dwg = svgwrite.Drawing("GeoBase_test.svg", profile="tiny")
def visitor_svg_rect(op, args, cm, tm):
   if op == b"re":
        (x, y, w, h) = (args[i].as_numeric() for i in range(4))
        dwg.add(dwg.rect((x, y), (w, h), stroke="red", fill_opacity=0.05))
def visitor_svg_text(text, cm, tm, fontDict, fontSize):
    (x, y) = (tm[4], tm[5])
   dwg.add(dwg.text(text, insert=(x, y), fill="blue"))
page.extract_text(
   visitor_operand_before=visitor_svg_rect, visitor_text=visitor_svg_text
)
dwg.save()
```

The SVG generated here is bottom-up because the coordinate systems of PDF and SVG differ.

Unfortunately in complicated PDF documents the coordinates given to the visitor-functions may be wrong.

8.2 Why Text Extraction is hard

Extracting text from a PDF can be pretty tricky. In several cases there is no clear answer what the expected result should look like:

- 1. **Paragraphs**: Should the text of a paragraph have line breaks at the same places where the original PDF had them or should it rather be one block of text?
- 2. Page numbers: Should they be included in the extract?
- 3. Headers and Footers: Similar to page numbers should they be extracted?
- 4. Outlines: Should outlines be extracted at all?
- 5. Formatting: If text is **bold** or *italic*, should it be included in the output?
- 6. **Tables**: Should the text extraction skip tables? Should it extract just the text? Should the borders be shown in some Markdown-like way or should the structure be present e.g. as an HTML table? How would you deal with merged cells?
- 7. Captions: Should image and table captions be included?
- 8. Ligatures: The Unicode symbol U+FB00 is a single symbol ff for two lowercase letters 'f'. Should that be parsed as the Unicode symbol 'ff' or as two ASCII symbols 'ff'?
- 9. SVG images: Should the text parts be extracted?
- 10. Mathematical Formulas: Should they be extracted? Formulas have indices, and nested fractions.
- 11. Whitespace characters: How many new lines should be extracted for 3cm of vertical whitespace? How many spaces should be extracted if there is 3cm of horizontal whitespace? When would you extract tabs and when spaces?
- 12. Footnotes: When the text of multiple pages is extracted, where should footnotes be shown?
- 13. Hyperlinks and Metadata: Should it be extracted at all? Where should it be placed in which format?
- 14. **Linearization**: Assume you have a floating figure in between a paragraph. Do you first finish the paragraph or do you put the figure text in between?

Then there are issues where most people would agree on the correct output, but the way PDF stores information just makes it hard to achieve that:

- 1. **Tables**: Typically, tables are just absolutely positioned text. In the worst case, ever single letter could be absolutely positioned. That makes it hard to tell where columns / rows are.
- 2. **Images**: Sometimes PDFs do not contain the text as it's displayed, but instead an image. You notice that when you cannot copy the text. Then there are PDF files that contain an image and a text layer in the background. That typically happens when a document was scanned. Although the scanning software (OCR) is pretty good today, it still fails once in a while. PyPDF2 is no OCR software; it will not be able to detect those failures. PyPDF2 will also never be able to extract text from images.

And finally there are issues that PyPDF2 will deal with. If you find such a text extraction bug, please share the PDF with us so we can work on it!

8.3 OCR vs Text Extraction

Optical Character Recognition (OCR) is the process of extracting text from images. Software which does this is called *OCR software*. The tesseract OCR engine is the most commonly known Open Source OCR software.

PyPDF2 is not OCR software.

8.3.1 Digitally-born vs Scanned PDF files

PDF documents can contain images and text. PDF files don't store text in a semantically meaningful way, but in a way that makes it easy to show the text on screen or print it. For this reason text extraction from PDFs is hard.

If you scan a document, the resulting PDF typically shows the image of the scan. Scanners then also run OCR software and put the recognized text in the background of the image. This result of the scanners OCR software can be extracted by PyPDF2. However, in such cases it's recommended to directly use OCR software as errors can accumulate: The OCR software is not perfect in recognizing the text. Then it stores the text in a format that is not meant for text extraction and PyPDF2 might make mistakes parsing that.

Hence I would distinguish three types of PDF documents:

- **Digitally-born PDF files**: The file was created digitally on the computer. It can contain images, texts, links, outline items (a.k.a., bookmarks), JavaScript, ... If you Zoom in a lot, the text still looks sharp.
- Scanned PDF files: Any number of pages was scanned. The images were then stored in a PDF file. Hence the file is just a container for those images. You cannot copy the text, you don't have links, outline items, JavaScript.
- **OCRed PDF files**: The scanner ran OCR software and put the recognized text in the background of the image. Hence you can copy the text, but it still looks like a scan. If you zoom in enough, you can recognize pixels.

8.3.2 Can we just always use OCR?

You might now wonder if it makes sense to just always use OCR software. If the PDF file is digitally-born, you can just render it to an image.

I would recommend not to do that.

Text extraction software like PyPDF2 can use more information from the PDF than just the image. It can know about fonts, encodings, typical character distances and similar topics.

That means PyPDF2 has a clear advantage when it comes to characters which are easy to confuse such as o00ö. **PyPDF2 will never confuse characters**. It just reads what is in the file.

PyPDF2 also has an edge when it comes to characters which are rare, e.g. . OCR software will not be able to recognize smileys correctly.

8.4 Attempts to prevent text extraction

If people who share PDF documents want to prevent text extraction, there are multiple ways to do so:

- 1. Store the contents of the PDF as an image
- 2. Use a scrambled font

However, text extraction cannot be completely prevented if people should still be able to read the document. In the worst case people can make a screenshot, print it, scan it, and run OCR over it.

NINE

EXTRACT IMAGES

Please note: In order to use the following code you need to install optional dependencies, see installation guide.

Every page of a PDF document can contain an arbitrary amount of images. The names of the files may not be unique.

```
from PyPDF2 import PdfReader
reader = PdfReader("example.pdf")
page = reader.pages[0]
count = 0
for image_file_object in page.images:
    with open(str(count) + image_file_object.name, "wb") as fp:
        fp.write(image_file_object.data)
        count += 1
```

ENCRYPTION AND DECRYPTION OF PDFS

Please see the note in the installation guide for installing the extra dependencies if interacting with PDFs that use AES.

10.1 Encrypt

Add a password to a PDF (encrypt it):

```
from PyPDF2 import PdfReader, PdfWriter
reader = PdfReader("example.pdf")
writer = PdfWriter()
# Add all pages to the writer
for page in reader.pages:
    writer.add_page(page)
# Add a password to the new PDF
writer.encrypt("my-secret-password")
# Save the new PDF to a file
with open("encrypted-pdf.pdf", "wb") as f:
    writer.write(f)
```

10.2 Decrypt

Remove the password from a PDF (decrypt it):

```
from PyPDF2 import PdfReader, PdfWriter
reader = PdfReader("encrypted-pdf.pdf")
writer = PdfWriter()
if reader.is_encrypted:
    reader.decrypt("my-secret-password")
# Add all pages to the writer
for page in reader.pages:
```

(continues on next page)

(continued from previous page)

writer.add_page(page)

```
# Save the new PDF to a file
with open("decrypted-pdf.pdf", "wb") as f:
    writer.write(f)
```

ELEVEN

MERGING PDF FILES

11.1 Basic Example

```
from PyPDF2 import PdfWriter
merger = PdfWriter()
for pdf in ["file1.pdf", "file2.pdf", "file3.pdf"]:
    merger.append(pdf)
merger.write("merged-pdf.pdf")
merger.close()
```

For more details, see an excellent answer on StackOverflow by Paul Rooney.

11.2 Showing more merging options

```
from PyPDF2 import PdfWriter
merger = PdfWriter()
input1 = open("document1.pdf", "rb")
input2 = open("document2.pdf", "rb")
input3 = open("document3.pdf", "rb")
# add the first 3 pages of input1 document to output
merger.append(fileobj=input1, pages=(0, 3))
# insert the first page of input2 into the output beginning after the second page
merger.merge(position=2, fileobj=input2, pages=(0, 1))
# append entire input3 document to the end of the output document
merger.append(input3)
# Write to an output PDF document
output = open("document-output.pdf", "wb")
merger.write(output)
```

(continues on next page)

(continued from previous page)

```
# Close File Descriptors
merger.close()
output.close()
```

11.3 append

append has been slighlty extended in PdfWriter.

see pdfWriter.append for more details

parameters:

fileobj: PdfReader or filename to merge *outline_item*: string of a outline/bookmark pointing to the beginning of the inserted file. if None, or omitted, no bookmark will be added. *pages*: pages to merge ; you can also provide a list of pages to merge None(default) means that the full document will be merged. *import_outline*: import/ignore the pertinent outlines from the source (default True) *excluded_fields*: list of keys to be ignored for the imported objects; if "/Annots" is part of the list, the annotation will be ignored if "/B" is part of the list, the articles will be ignored

examples:

writer.append("source.pdf",(0,10)) # append the first 10 pages of source.pdf

writer.append(reader,"page 1 and 10",[0,9]) #append first and 10th page from reader and create an outline)

During the merging, the relevant named destination will also imported.

If you want to insert pages in the middle of the destination, use merge (which provides (insert) position)

You can now insert the same page multiple times. You can also insert the same page many time at once with a list:

eg: writer.append(reader,[0,1,0,2,0]) will insert the pages (1), (2), with page (0) before, in the middle and after

11.4 add_page / insert_page

It is recommended to use append or merge instead

11.5 reset_translation

During the cloning, if an object has been already cloned, it will not be cloned again, a pointer this previously cloned object is returned. because of that, if you add/merge a page that has been already added, the same object will be added the second time. If later you modify any of these two page, both pages can be modified independently.

To reset, call writer.reset_translation(reader)

11.6 Advanced cloning

In order to prevent side effect between pages/objects objects and all objects linked are linked during merging.

This process will be automatically applied if you use PdfWriter.append/merge/add_page/insert_page. If you want to clone an object before attaching it "manually", use clone function of any PdfObject: eg:

cloned_object = object.clone(writer)

if you try clone an object already belonging to writer, it will return the same object

cloned_object == object.clone(writer) # -> returns True

the same, if you try to clone twice an object it will return the previously cloned object

object.clone(writer) == object.clone(writer) # -> returns True

Also, note that if you clone an object, you will clone all the objects below including the objects pointed by IndirectObject. because of that if you clone a page that includes some articles ("/B"), not only the first article, but also all the chained articles, and the pages where those articles can be read will be copied. It means that you may copy lots of objects, that will be saved in the output pdf.

In order to prevent, that you can provide the list of defined the fields in the dictionaries to be ignored:

eg: new_page = writer.add_page(reader.pages[0],excluded_fields=["/B"])
TWELVE

CROPPING AND TRANSFORMING PDFS

```
from PyPDF2 import PdfWriter, PdfReader
reader = PdfReader("example.pdf")
writer = PdfWriter()
# add page 1 from reader to output document, unchanged:
writer.add_page(reader.pages[0])
# add page 2 from reader, but rotated clockwise 90 degrees:
writer.add_page(reader.pages[1].rotate(90))
# add page 3 from reader, but crop it to half size:
page3 = reader.pages[2]
page3.mediabox.upper_right = (
   page3_mediabox_right / 2,
   page3.mediabox.top / 2,
writer.add_page(page3)
# add some Javascript to launch the print window on opening this PDF.
# the password dialog may prevent the print dialog from being shown,
# comment the the encription lines, if that's the case, to try this out:
writer.add_js("this.print({bUI:true,bSilent:false,bShrinkToFit:true});")
# write to document-output.pdf
with open("PyPDF2-output.pdf", "wb") as fp:
   writer.write(fp)
```

12.1 Page rotation

The most typical rotation is a clockwise rotation of the page by multiples of 90 degrees. That is done when the orientation of the page is wrong. You can do that with the rotate method of the PageObject class:

```
from PyPDF2 import PdfWriter, PdfReader
reader = PdfReader("input.pdf")
writer = PdfWriter()
```

```
writer.add_page(reader.pages[0])
writer.pages[0].rotate(90)
with open("output.pdf", "wb") as fp:
    writer.write(fp)
```

The rotate method is typically preferred over the page.add_transformation(Transformation().rotate()) method, because rotate will ensure that the page is still in the mediabox / cropbox. The transformation object operates on the coordinates of the pages contents and does not change the mediabox or cropbox.

12.2 Plain Merge



is the result of

```
from PyPDF2 import PdfReader, PdfWriter, Transformation
# Get the data
reader_base = PdfReader("labeled-edges-center-image.pdf")
page_base = reader_base.pages[0]
reader = PdfReader("box.pdf")
page_box = reader.pages[0]
page_base.merge_page(page_box)
# Write the result back
writer = PdfWriter()
writer.add_page(page_base)
with open("merged-foo.pdf", "wb") as fp:
    writer.write(fp)
```

12.3 Merge with Rotation



```
from PyPDF2 import PdfReader, PdfWriter, Transformation
# Get the data
reader_base = PdfReader("labeled-edges-center-image.pdf")
page_base = reader_base.pages[0]
reader = PdfReader("box.pdf")
page_box = reader.pages[0]
# Apply the transformation
transformation = Transformation().rotate(45)
page_box.add_transformation().rotate(45)
page_base.merge_page(page_box)
# Write the result back
writer = PdfWriter()
writer.add_page(page_base)
with open("merged-foo.pdf", "wb") as fp:
```

writer.write(fp)

If you add the expand parameter:

```
transformation = Transformation().rotate(45)
page_box.add_transformation(transformation)
page_base.merge_page(page_box)
```

you get:



Alternatively, you can move the merged image a bit to the right by using

op = Transformation().rotate(45).translate(tx=50)



12.4 Scaling

PyPDF2 offers two ways to scale: The page itself and the contents on a page. Typically, you want to combine both.



12.4.1 Scaling a Page (the Canvas)

```
from PyPDF2 import PdfReader, PdfWriter

# Read the input
reader = PdfReader("resources/side-by-side-subfig.pdf")
page = reader.pages[0]

# Scale
page.scale_by(0.5)

# Write the result to a file
writer = PdfWriter()
writer.add_page(page)
writer.write("out.pdf")
```

If you wish to have more control, you can adjust the various page boxes directly:

```
from PyPDF2.generic import RectangleObject
mb = page.mediabox
page.mediabox = RectangleObject((mb.left, mb.bottom, mb.right, mb.top))
page.cropbox = RectangleObject((mb.left, mb.bottom, mb.right, mb.top))
page.trimbox = RectangleObject((mb.left, mb.bottom, mb.right, mb.top))
page.bleedbox = RectangleObject((mb.left, mb.bottom, mb.right, mb.top))
page.artbox = RectangleObject((mb.left, mb.bottom, mb.right, mb.top))
```

12.4.2 Scaling the content

The content is scaled towords the origin of the coordinate system. Typically, that is the lower-left corner.

```
from PyPDF2 import PdfReader, PdfWriter, Transformation
# Read the input
reader = PdfReader("resources/side-by-side-subfig.pdf")
page = reader.pages[0]
# Scale
op = Transformation().scale(sx=0.7, sy=0.7)
page.add_transformation(op)
# Write the result to a file
writer = PdfWriter()
writer.add_page(page)
writer.write("out-pg-transform.pdf")
```

THIRTEEN

ADDING A STAMP/WATERMARK TO A PDF

Adding stamps or watermarks are two common ways to manipulate PDF files. A stamp is adding something on top of the document, a watermark is in the background of the document.

In both cases you might want to ensure that the mediabox/cropbox of the original content stays the same.

13.1 Stamp (Overlay)

```
from pathlib import Path
from typing import Union, Literal, List
from PyPDF2 import PdfWriter, PdfReader
def stamp(
   content_pdf: Path,
   stamp_pdf: Path,
   pdf_result: Path,
   page_indices: Union[Literal["ALL"], List[int]] = "ALL",
):
   reader = PdfReader(stamp_pdf)
   image_page = reader.pages[0]
   writer = PdfWriter()
   reader = PdfReader(content_pdf)
   if page_indices == "ALL":
       page_indices = list(range(0, len(reader.pages)))
    for index in page_indices:
        content_page = reader.pages[index]
        mediabox = content_page.mediabox
        content_page.merge_page(image_page)
        content_page.mediabox = mediabox
        writer.add_page(content_page)
   with open(pdf_result, "wb") as fp:
       writer.write(fp)
```

The Crazy Ones

October 14, 1998

- Heres to the crazy ones. The misfits. The rebels. The troublemakers. The round pegs in the square holes.
- The ones who see things differently. Theyre not fond of rules. And they have no respect for the status quo. You can quote them, disagree with them, glorify or vilify them.

About the only thing you cant do is ignore them y neal. They explore. They things. They invent. They imaging create. They inspire. They in the human race forward. Maybe they have to b αZV. How else can you are at an empty canvas a. work and hear a sit in sile itten? g thats never leen t a red **p** let and se ab tory on wheels? We m tools for these of people. Wł some s m as the crazy ones, we comus. Because the zy enough to the they can change the world, seople w a_1

13.2 Watermark (Underlay)

are the o

```
from pathlib import Path
from typing import Union, Literal, List
from PyPDF2 import PdfWriter, PdfReader

def watermark(
    content_pdf: Path,
    stamp_pdf: Path,
    pdf_result: Path,
    page_indices: Union[Literal["ALL"], List[int]] = "ALL",
):
    reader = PdfReader(content_pdf)
```

```
if page_indices == "ALL":
    page_indices = list(range(0, len(reader.pages)))
writer = PdfWriter()
for index in page_indices:
    content_page = reader.pages[index]
    mediabox = content_page.mediabox
    # You need to load it again, as the last time it was overwritten
    reader_stamp = PdfReader(stamp_pdf)
    image_page = reader_stamp.pages[0]
    image_page.merge_page(content_page)
    image_page.mediabox = mediabox
    writer.add_page(image_page)
with open(pdf_result, "wb") as fp:
    writer.write(fp)
```

The Crazy Ones October 14, 1998

Heres to the crazy ones. The misfits. The rebels. The troublemakers. The round pegs in the square holes.

- The ones who see things differently. Theyre not fond of rules. And they have no respect for the status quo. You can quote them, disagree with them, glorify or vilify them.
- About the only thing you cant do is ignore them. Because they change things. They invent. They imagine. They heal. They explore. They create. They inspire. They push the human race forward.

Maybe they have to be crazy.

How else can you stare at an empty canvas and see a work of art? Or sit in silence and hear a song thats never been written? Or gaze at a red planet and see a laboratory on wheels?

We make tools for these kinds of people.

While some see them as the crazy ones, we see genius. Because the people who are crazy enough to think they can change the world, are the ones who do.

FOURTEEN

READING PDF ANNOTATIONS

PDF 1.7 defines 25 different annotation types:

- Text
- Link
- FreeText
- Line, Square, Circle, Polygon, PolyLine, Highlight, Underline, Squiggly, StrikeOut
- Stamp, Caret, Ink
- Popup
- FileAttachment
- Sound, Movie
- Widget, Screen
- PrinterMark
- TrapNet
- Watermark
- 3D

In general, annotations can be read like this:

```
from PyPDF2 import PdfReader
reader = PdfReader("commented.pdf")
for page in reader.pages:
    if "/Annots" in page:
        for annot in page["/Annots"]:
            obj = annot.get_object()
            annotation = {"subtype": obj["/Subtype"], "location": obj["/Rect"]}
        print(annotation)
```

Reading the most common ones is described here.

14.1 Text

```
from PyPDF2 import PdfReader
reader = PdfReader("example.pdf")
for page in reader.pages:
    if "/Annots" in page:
        for annot in page["/Annots"]:
            subtype = annot.get_object()["/Subtype"]
            if subtype == "/Text":
                print(annot.get_object()["/Contents"])
```

14.2 Highlights

```
from PyPDF2 import PdfReader
reader = PdfReader("commented.pdf")
for page in reader.pages:
    if "/Annots" in page:
        for annot in page["/Annots"]:
            subtype = annot.get_object()["/Subtype"]
            if subtype == "/Highlight":
                coords = annot.get_object()["/QuadPoints"]
                x1, y1, x2, y2, x3, y3, x4, y4 = coords
```

14.3 Attachments

```
from PyPDF2 import PdfReader
reader = PdfReader("example.pdf")
attachments = {}
for page in reader.pages:
    if "/Annots" in page:
        for annotation in page["/Annots"]:
            subtype = annot.get_object()["/Subtype"]
            if subtype == "/FileAttachment":
                fileobj = annotobj["/FS"]
                attachments[fileobj["/F"]] = fileobj["/EF"]["/F"].get_data()
```

FIFTEEN

ADDING PDF ANNOTATIONS

15.1 Attachments

from PyPDF2 import PdfWriter
writer = PdfWriter()
writer.add_blank_page(width=200, height=200)
data = b"any bytes - typically read from a file"
writer.add_attachment("smile.png", data)

```
with open("output.pdf", "wb") as output_stream:
    writer.write(output_stream)
```

15.2 Free Text

If you want to add text in a box like this

The Crazy Ones October 14, 1998

Heres to the crazy ones. The misfits. The rebels. The troublemakers. The round pegs in the square holes.

Hello World This is the second line!	erently. Theyre not fond of rules. And he status quo. You can quote them, y or vilify them.	
	nt do is ignore them. Because they change , imagine. They heal. They explore. They y push the human race forward.	

How else can you stare at an empty canvas and see a work of art? Or sit in silence and hear a song thats never been written? Or gaze at a red planet and see a laboratory on wheels?

We make tools for these kinds of people.

While some see them as the crazy ones, we see genius. Because the people who are crazy enough to think they can change the world, are the ones who do.

you can use the *AnnotationBuilder*:

```
from PyPDF2 import PdfReader, PdfWriter
from PyPDF2.generic import AnnotationBuilder
# Fill the writer with the pages you want
pdf_path = os.path.join(RESOURCE_ROOT, "crazyones.pdf")
reader = PdfReader(pdf_path)
page = reader.pages[0]
writer = PdfWriter()
writer.add_page(page)
# Create the annotation and add it
annotation = AnnotationBuilder.free_text(
   "Hello World\nThis is the second line!",
   rect=(50, 550, 200, 650),
    font="Arial",
   bold=True,
   italic=True,
    font_size="20pt",
    font_color="00ff00",
```

```
border_color="0000ff",
    background_color="cdcdcd",
)
writer.add_annotation(page_number=0, annotation=annotation)
# Write the annotated file to disk
with open("annotated-pdf.pdf", "wb") as fp:
    writer.write(fp)
```

15.3 Text

A text annotation looks like this:

Contents **1** Foo $\mathbf{2}$ 2 Bar $\mathbf{2}$ 3 Baz $\mathbf{2}$ **4** Foo $\mathbf{2}$ 5 Bar 3 6 Baz 3 7 Foo 3 8 Bar 4 9 Baz 4

15.4 Line

If you want to add a line like this:

The Crazy Ones October 14, 1998

- Heres to the crazy ones. The misfits. The rebels. The troublemakers. The round pegs in the square holes.
- The ones who see things differently. Theyre not fond of rules. And they have no respect for the status quo. You can quote them, disagree with them, glorify or vilify them.
- About the only thing you cant do is ignore them. Because they change things. They invent. They imagine. They heal. They explore. They create. They inspire. They push the human race forward.

Maybe they have to be crazy.

How else can you stare at an empty canvas and see a work of art? Or sit in silence and hear a song thats never been written? Or gaze at a red planet and see a laboratory on wheels?

We make tools for these kinds of people.

While some see them as the crazy ones, we see genius. Because the people who are crazy enough to think they can change the world, are the ones who do.

you can use the *AnnotationBuilder*:

```
pdf_path = os.path.join(RESOURCE_ROOT, "crazyones.pdf")
reader = PdfReader(pdf_path)
page = reader.pages[0]
writer = PdfWriter()
writer.add_page(page)
# Add the line
annotation = AnnotationBuilder.line(
    text="Hello World\nLine2",
    rect=(50, 550, 200, 650),
    p1=(50, 550),
    p2=(200, 650),
)
writer.add_annotation(page_number=0, annotation=annotation)
# Write the annotated file to disk
with open("annotated-pdf.pdf", "wb") as fp:
```

writer.write(fp)

15.5 Rectangle

If you want to add a rectangle like this:

The Crazy Ones October 14, 1998

> Heres to the crazy ones. The misfits. The rebels. The troublemakers. The round pegs in the square holes.

The ones who see things differently. Theyre not fond of rules. And they have no respect for the status quo. You can quote them, disagree with them, glorify or vilify them.

About the only thing you cant do is ignore them. Because they change things. They invent. They imagine. They heal. They explore. They create. They inspire. They push the human race forward.

Maybe they have to be crazy

How else can you stare at an empty canvas and see a work of art? Or sit in silence and hear a song thats never been written? Or gaze at a red planet and see a laboratory on wheels?

We make tools for these kinds of people.

you can use the AnnotationBuilder:

```
pdf_path = os.path.join(RESOURCE_ROOT, "crazyones.pdf")
reader = PdfReader(pdf_path)
page = reader.pages[0]
writer = PdfWriter()
writer.add_page(page)
# Add the line
annotation = AnnotationBuilder.rectangle(
    rect=(50, 550, 200, 650),
)
writer.add_annotation(page_number=0, annotation=annotation)
# Write the annotated file to disk
with open("annotated-pdf.pdf", "wb") as fp:
    writer.write(fp)
```

If you want the rectangle to be filled, use the interiour_color="ff0000" parameter.

This method uses the "square" annotation type of the PDF format.

15.6 Link

If you want to add a link, you can use the AnnotationBuilder:

```
pdf_path = os.path.join(RESOURCE_ROOT, "crazyones.pdf")
reader = PdfReader(pdf_path)
page = reader.pages[0]
writer = PdfWriter()
writer.add_page(page)
# Add the line
annotation = AnnotationBuilder.link(
   rect=(50, 550, 200, 650),
   url="https://martin-thoma.com/",
)
writer.add_annotation(page_number=0, annotation=annotation)
# Write the annotated file to disk
with open("annotated-pdf.pdf", "wb") as fp:
   writer.write(fp)
```

You can also add internal links:

```
pdf_path = os.path.join(RESOURCE_ROOT, "crazyones.pdf")
reader = PdfReader(pdf_path)
page = reader.pages[0]
writer = PdfWriter()
writer.add_page(page)
# Add the line
annotation = AnnotationBuilder.link(
    rect=(50, 550, 200, 650), target_page_index=3, fit="/FitH", fit_args=(123,)
)
writer.add_annotation(page_number=0, annotation=annotation)
# Write the annotated file to disk
with open("annotated-pdf.pdf", "wb") as fp:
    writer.write(fp)
```

SIXTEEN

INTERACTIONS WITH PDF FORMS

16.1 Reading form fields

```
from PyPDF2 import PdfReader
reader = PdfReader("form.pdf")
fields = reader.get_form_text_fields()
fields == {"key": "value", "key2": "value2"}
```

16.2 Filling out forms

```
from PyPDF2 import PdfReader, PdfWriter

reader = PdfReader("form.pdf")
writer = PdfWriter()

page = reader.pages[0]
writer.add_page(page)
writer.update_page_form_field_values(
    writer.pages[0], {"fieldname": "some filled in text"}
)

# write "output" to PyPDF2-output.pdf
with open("filled-out.pdf", "wb") as output_stream:
    writer.write(output_stream)
```

SEVENTEEN

STREAMING DATA WITH PYPDF2

In some cases you might want to avoid saving things explicitly as a file to disk, e.g. when you want to store the PDF in a database or AWS S3.

PyPDF2 supports streaming data to a file-like object and here is how.

```
from io import BytesI0
# Prepare example
with open("example.pdf", "rb") as fh:
    bytes_stream = BytesIO(fh.read())
# Read from bytes_stream
reader = PdfReader(bytes_stream)
# Write to bytes_stream
writer = PdfWriter()
with BytesIO() as bytes_stream:
    writer.write(bytes_stream)
```

17.1 Writing a PDF directly to AWS S3

Suppose you want to manipulate a PDF and write it directly to AWS S3 without having to write the document to a file first. We have the original PDF in raw_bytes_data as bytes and want to set my-secret-password:

```
from io import BytesIO
import boto3
from PyPDF2 import PdfReader, PdfWriter

reader = PdfReader(BytesIO(raw_bytes_data))
writer = PdfWriter()

# Add all pages to the writer
for page in reader.pages:
    writer.add_page(page)
# Add a password to the new PDF
writer.encrypt("my-secret-password")
```

```
# Save the new PDF to a file
with BytesIO() as bytes_stream:
    writer.write(bytes_stream)
    bytes_stream.seek(0)
    s3 = boto3.client("s3")
    s3.write_get_object_response(
        Body=bytes_stream, RequestRoute=request_route, RequestToken=request_token
    )
```

17.2 Reading PDFs directly from cloud services

One option is to first download the file and then pass the local file path to PdfReader. Another option is to get a byte stream.

For AWS S3 it works like this:

```
from io import BytesI0
import boto3
from PyPDF2 import PdfReader
s3 = boto3.client("s3")
obj = s3.get_object(Body=csv_buffer.getvalue(), Bucket="my-bucket", Key="my/doc.pdf")
reader = PdfReader(BytesI0(obj["Body"].read()))
```

It works similarly for Google Cloud Storage (example)

EIGHTEEN

REDUCE PDF SIZE

There are multiple ways to reduce the size of a given PDF file. The easiest one is to remove content (e.g. images) or pages.

18.1 Removing duplication

Some PDF documents contain the same object multiple times. For example, if an image appears three times in a PDF it could be embedded three times. Or it can be embedded once and referenced twice.

This can be done by reading and writing the file:

```
from PyPDF2 import PdfReader, PdfWriter
reader = PdfReader("big-old-file.pdf")
writer = PdfWriter()
for page in reader.pages:
    writer.add_page(page)
writer.add_metadata(reader.metadata)
with open("smaller-new-file.pdf", "wb") as fp:
    writer.write(fp)
```

It depends on the PDF how well this works, but we have seen an 86% file reduction (from 5.7 MB to 0.8 MB) within a real PDF.

18.2 Remove images

```
from PyPDF2 import PdfReader, PdfWriter
reader = PdfReader("example.pdf")
writer = PdfWriter()
for page in reader.pages:
    writer.add_page(page)
writer.remove_images()
```

```
with open("out.pdf", "wb") as f:
    writer.write(f)
```

18.3 Lossless Compression

PyPDF2 supports the FlateDecode filter which uses the zlib/deflate compression method. It is a lossless compression, meaning the resulting PDF looks exactly the same.

Deflate compression can be applied to a page via page.compress_content_streams:

```
from PyPDF2 import PdfReader, PdfWriter

reader = PdfReader("example.pdf")
writer = PdfWriter()

for page in reader.pages:
    page.compress_content_streams() # This is CPU intensive!
    writer.add_page(page)

with open("out.pdf", "wb") as f:
    writer.write(f)
```

Using this method, we have seen a reduction by 70% (from 11.8 MB to 3.5 MB) with a real PDF.

NINETEEN

PDF VERSION SUPPORT

PDF comes in the following versions:

- 1993: 1.0
- 1994: 1.1
- 1996: 1.2
- 1999: 1.3
- 2001: 1.4
- 2003: 1.5
- 2004: 1.6
- 2006 2012: 1.7, ISO 32000-1:2008
- 2017: 2.0

The general format didn't change, but new features got added. It can be that PyPDF2 can do the operations you want on PDF 2.0 files without fully supporting all features of PDF 2.0.

19.1 PDF Feature Support by PyPDF2

Feature	PDF-Version	PyPDF2 Support
Transparent Graphics	1.4	?
CMaps	1.4	
Object Streams	1.5	?
Cross-reference Streams	1.5	?
Optional Content Groups (OCGs) - Layers	1.5	?
Content Stream Compression	1.5	?
AES Encryption	1.6	

See History of PDF for more features.

Some PDF features are not supported by PyPDF2, but other libraries can be used for them:

- pyHanko: Cryptographically sign a PDF (#302)
- camelot-py: Table Extraction (#231)

Note: This page is about PyPDF2. PyPDF2 is deprecated, please use pypdf

TWENTY

THE PDFREADER CLASS

class PyPDF2.**PdfReader**(*stream: Union[str, IO, Path], strict: bool = False, password: Union[None, str, bytes] = None*)

Bases: object

Initialize a PdfReader object.

This operation can take some time, as the PDF stream's cross-reference tables are read into memory.

Parameters

- **stream** A File object or an object that supports the standard read and seek methods similar to a File object. Could also be a string representing a path to a PDF file.
- **strict** (*bool*) Determines whether user should be warned of all problems and also causes some correctable problems to be fatal. Defaults to False.
- **password** (*None/str/bytes*) Decrypt PDF file at initialization. If the password is None, the file will not be decrypted. Defaults to None

cacheGetIndirectObject(generation: int, idnum: int) \rightarrow Optional[PdfObject]

Deprecated since version 1.28.0: Use cache_get_indirect_object() instead.

cacheIndirectObject(generation: int, idnum: int, obj: Optional[PdfObject]) \rightarrow Optional[PdfObject]) Deprecated since version 1.28.0: Use cache_indirect_object() instead.

 $cache_get_indirect_object(generation: int, idnum: int) \rightarrow Optional[PdfObject]$

cache_indirect_object(generation: int, idnum: int, obj: $Optional[PdfObject]) \rightarrow Optional[PdfObject]$

decode_permissions(*permissions_code: int*) \rightarrow Dict[str, bool]

decrypt(*password: Union*[*str, bytes*]) → PasswordType

When using an encrypted / secured PDF file with the PDF Standard encryption handler, this function will allow the file to be decrypted. It checks the given password against the document's user password and owner password, and then stores the resulting decryption key if either password is correct.

It does not matter which password was matched. Both passwords provide the correct decryption key that will allow the document to be used with this library.

Parameters

password (*str*) – The password to match.

Returns

PasswordType.

```
property documentInfo: Optional[DocumentInformation]
     Deprecated since version 1.28.0.
     Use the attribute metadata instead.
getDestinationPageNumber(destination: Destination) \rightarrow int
     Deprecated since version 1.28.0: Use get_destination_page_number() instead.
getDocumentInfo() → Optional[DocumentInformation]
     Deprecated since version 1.28.0: Use the attribute metadata instead.
getFields(tree: Optional[TreeObject] = None, retval: Optional[Dict[Any, Any]] = None, fileobj:
            Optional[Any] = None) \rightarrow Optional[Dict[str, Any]]
     Deprecated since version 1.28.0: Use get_fields() instead.
getFormTextFields() \rightarrow Dict[str, Any]
     Deprecated since version 1.28.0: Use get_form_text_fields() instead.
getIsEncrypted() \rightarrow bool
     Deprecated since version 1.28.0: Use is_encrypted instead.
getNamedDestinations(tree: Optional[TreeObject] = None, retval: Optional[Any] = None) \rightarrow Dict[str,
                          Any]
     Deprecated since version 1.28.0: Use named_destinations instead.
getNumPages() \rightarrow int
     Deprecated since version 1.28.0: Use len(reader.pages) instead.
get0bject(indirectReference: IndirectObject) → Optional[PdfObject]
     Deprecated since version 1.28.0: Use get_object() instead.
getOutlines(node: Optional[DictionaryObject] = None, outline: Optional[Any] = None) \rightarrow
               List[Union[Destination, List[Union[Destination, List[Destination]]]]]
     Deprecated since version 1.28.0: Use outline instead.
getPage(pageNumber: int) \rightarrow PageObject
     Deprecated since version 1.28.0: Use reader.pages[page_number] instead.
getPageLayout() \rightarrow Optional[str]
     Deprecated since version 1.28.0: Use page_layout instead.
getPageMode() \rightarrow Optional[Literal['/UseNone', '/UseOutlines', '/UseThumbs', '/FullScreen', '/UseOC',
               '/UseAttachments']]
     Deprecated since version 1.28.0: Use page_mode instead.
getPageNumber(page: PageObject) \rightarrow int
     Deprecated since version 1.28.0: Use get_page_number() instead.
getXmpMetadata() \rightarrow Optional[XmpInformation]
     Deprecated since version 1.28.0: Use the attribute xmp_metadata instead.
get_destination_page_number(destination: Destination) \rightarrow int
     Retrieve page number of a given Destination object.
         Parameters
              destination (Destination) – The destination to get page number.
         Returns
              the page number or -1 if page not found
```
get_fields(*tree: Optional*[*TreeObject*] = *None, retval: Optional*[*Dict*[*Any, Any*]] = *None, fileobj: Optional*[*Any*] = *None*) \rightarrow Optional[Dict[str, Any]]

Extract field data if this PDF contains interactive form fields.

The tree and retval parameters are for recursive use.

Parameters

fileobj – A file object (usually a text file) to write a report to on all interactive form fields found.

Returns

A dictionary where each key is a field name, and each value is a *Field* object. By default, the mapping name is used for keys. None if form data could not be located.

get_form_text_fields() → Dict[str, Any]

Retrieve form fields from the document with textual data.

The key is the name of the form field, the value is the content of the field.

If the document contains multiple form fields with the same name, the second and following will get the suffix $2, 3, \ldots$

get_object(*indirect_reference: Union*[*int, IndirectObject*]) \rightarrow Optional[PdfObject]

get_page_number(page: PageObject) \rightarrow int

Retrieve page number of a given PageObject

Parameters

page (PageObject) – The page to get page number. Should be an instance of PageObject

Returns

the page number or -1 if page not found

property isEncrypted: bool

Deprecated since version 1.28.0.

Use is_encrypted instead.

property is_encrypted: bool

Read-only boolean property showing whether this PDF file is encrypted. Note that this property, if true, will remain true even after the *decrypt()* method is called.

property metadata: Optional[DocumentInformation]

Retrieve the PDF file's document information dictionary, if it exists. Note that some PDF files use metadata streams instead of docinfo dictionaries, and these metadata streams will not be accessed by this function.

Returns

the document information of this PDF file

property namedDestinations: Dict[str, Any]

Deprecated since version 1.28.0.

Use named_destinations instead.

property named_destinations: Dict[str, Any]

A read-only dictionary which maps names to *Destinations*

property numPages: int

Deprecated since version 1.28.0.

Use len(reader.pages) instead.

property outline: List[Union[Destination, List[Union[Destination, List[Destination]]]]]

Read-only property for the outline (i.e., a collection of 'outline items' which are also known as 'bookmarks') present in the document.

Returns

a nested list of *Destinations*.

property outlines: List[Union[Destination, List[Union[Destination,

List[Destination]]]]]

Deprecated since version 2.9.0.

Use outline instead.

property pageLayout: Optional[str]

Deprecated since version 1.28.0.

Use *page_layout* instead.

property pageMode: Optional[Literal['/UseNone', '/UseOutlines', '/UseThumbs', '/FullScreen', '/UseOC', '/UseAttachments']]

Deprecated since version 1.28.0.

Use page_mode instead.

property page_layout: Optional[str]

Get the page layout.

Returns

Page layout currently being used.

/NoLayout	Layout explicitly not specified	
/SinglePage	Show one page at a time	
/OneColumn	Show one column at a time	
/TwoColumnLeft	Show pages in two columns, odd-numbered pages on the left	
/TwoColumn-	Show pages in two columns, odd-numbered pages on the right	
Right		
/TwoPageLeft	Show two pages at a time, odd-numbered pages on the left	
/TwoPageRight	Show two pages at a time, odd-numbered pages on the right	

Table 1: Valid layout values

property page_mode: Optional[Literal['/UseNone', '/UseOutlines', '/UseThumbs', '/FullScreen', '/UseOC', '/UseAttachments']]

Get the page mode.

Returns

Page mode currently being used.

Table 2: valid mode values	Table 2:	Valid mode	values
----------------------------	----------	------------	--------

/UseNone	Do not show outline or thumbnails panels	
/UseOutlines	Show outline (aka bookmarks) panel	
/UseThumbs	Show page thumbnails panel	
/FullScreen	Fullscreen view	
/UseOC	Show Optional Content Group (OCG) panel	
/UseAttachments	Show attachments panel	

property pages: List[PageObject]

Read-only property that emulates a list of Page objects.

property pdf_header: str

read(*stream: IO*) \rightarrow None

readNextEndLine(*stream: IO*, *limit_offset: int* = 0) \rightarrow bytes Deprecated since version 1.28.0.

readObjectHeader(*stream: IO*) \rightarrow Tuple[int, int]

Deprecated since version 1.28.0: Use *read_object_header()* instead.

read_next_end_line(*stream: IO, limit_offset: int* = 0) \rightarrow bytes Deprecated since version 2.1.0.

read_object_header(*stream: IO*) → Tuple[int, int]

property threads: Optional[ArrayObject]

Read-only property for the list of threads see §8.3.2 from PDF 1.7 spec

Returns

an Array of Dictionnaries with "/F" and "/I" properties or None if no articles.

property xfa: Optional[Dict[str, Any]]

property xmpMetadata: Optional[XmpInformation]

Deprecated since version 1.28.0.

Use the attribute *xmp_metadata* instead.

property xmp_metadata: Optional[XmpInformation]

XMP (Extensible Metadata Platform) data

Returns

a *XmpInformation* instance that can be used to access XMP metadata from the document. or **None** if no metadata was found on the document root.

Note: This page is about PyPDF2. PyPDF2 is deprecated, please use pypdf

CHAPTER

TWENTYONE

THE PDFWRITER CLASS

class PyPDF2.**PdfWriter**(*fileobj: Union*[*str*, *IO*] = ") Bases: object This class supports writing PDF files out, given pages produced by another class (typically *PdfReader*). addAttachment(fname: str, fdata: Union[str, bytes]) \rightarrow None Deprecated since version 1.28.0: Use add_attachment() instead. addBlankPage(width: $Optional[float] = None, height: Optional[float] = None) \rightarrow PageObject$ Deprecated since version 1.28.0: Use add_blank_page() instead. addBookmark(title: str, pagenum: int, parent: Union[None, TreeObject, IndirectObject] = None, color: *Optional*[*Tuple*[*float*, *float*]] = *None*, *bold*: *bool* = *False*, *italic*: *bool* = *False*, *fit*: Literal['/Fit', '/XYZ', '/FitH', '/FitV', '/FitR', '/FitB', '/FitBH', '/FitBV'] = '/Fit', *args: *Union*[*NumberObject*, *NullObject*, *float*]) → IndirectObject Deprecated since version 1.28.0: Use add_outline_item() instead. addBookmarkDestination(dest: PageObject, parent: Optional[TreeObject] = None) \rightarrow IndirectObject Deprecated since version 1.28.0: Use add_outline_item_destination() instead. addBookmarkDict(outline_item: Union[OutlineItem, Destination], parent: Optional[TreeObject] = None) \rightarrow IndirectObject Deprecated since version 1.28.0: Use add_outline_item_dict() instead. addJS(*javascript: str*) \rightarrow None Deprecated since version 1.28.0: Use *add_js()* instead. **addLink**(*pagenum: int, page_destination: int, rect:* RectangleObject, *border: Optional*[*ArrayObject*] = *None*, fit: Literal['/Fit', '/XYZ', '/FitH', '/FitV', '/FitR', '/FitB', '/FitBH', '/FitBV'] = '/Fit', *args: *Union*[*NumberObject, NullObject, float*]) \rightarrow None Deprecated since version 1.28.0: Use add_link() instead. addMetadata(*infos:* Dict[str, Any]) \rightarrow None Deprecated since version 1.28.0: Use add_metadata() instead. **addNamedDestination**(*title: str, pagenum: int*) \rightarrow IndirectObject Deprecated since version 1.28.0: Use add_named_destination() instead. $addNamedDestinationObject(\mathit{dest:}\ Destination) \rightarrow IndirectObject$ Deprecated since version 1.28.0: Use add_named_destination_object() instead. addPage(page: PageObject, excluded_keys: Iterable[str] = ()) \rightarrow PageObject Deprecated since version 1.28.0: Use add_page() instead.

- addURI (*pagenum: int, uri: str, rect:* RectangleObject, *border: Optional*[ArrayObject] = None) \rightarrow None Deprecated since version 1.28.0: Use add_uri() instead.
- add_annotation($page_number$: int, annotation: Dict[str, Any]) \rightarrow None
- add_attachment(filename: str, data: Union[str, bytes]) \rightarrow None

Embed a file inside the PDF.

Parameters

- **filename** (*str*) The filename to display.
- data (*str*) The data in the file.

Reference: https://www.adobe.com/content/dam/Adobe/en/devnet/acrobat/pdfs/PDF32000_2008.pdf Section 7.11.3

add_blank_page(width: Optional[float] = None, height: Optional[float] = None) $\rightarrow PageObject$

Append a blank page to this PDF file and returns it. If no page size is specified, use the size of the last page.

Parameters

- width (*float*) The width of the new page expressed in default user space units.
- height (float) The height of the new page expressed in default user space units.

Returns

the newly appended page

Raises

PageSizeNotDefinedError – if width and height are not defined and previous page does not exist.

add_bookmark(title: str, pagenum: int, parent: Union[None, TreeObject, IndirectObject] = None, color: Optional[Tuple[float, float, float]] = None, bold: bool = False, italic: bool = False, fit: Literal['/Fit', '/XYZ', '/FitH', '/FitR', '/FitB', '/FitBH', '/FitBV'] = '/Fit', *args: Union[NumberObject, NullObject, float]) → IndirectObject

Deprecated since version 2.9.0: Use add_outline_item() instead.

add_bookmark_destination(dest: Union[PageObject, TreeObject], parent: Union[None, TreeObject, IndirectObject] = None) \rightarrow IndirectObject

Deprecated since version 2.9.0: Use add_outline_item_destination() instead.

add_bookmark_dict(*outline_item: Union[OutlineItem*, Destination], *parent: Optional[TreeObject]* = None) → IndirectObject

Deprecated since version 2.9.0: Use add_outline_item_dict() instead.

add_filtered_articles(fltr: Union[Pattern, str], pages: Dict[int, PageObject], reader: PdfReader) \rightarrow None

Add articles matching the defined criteria

add_js(*javascript: str*) \rightarrow None

Add Javascript which will launch upon opening this PDF.

Parameters javascript (*str*) – Your Javascript.

```
>>> output.add_js("this.print({bUI:true,bSilent:false,bShrinkToFit:true});")
# Example: This will launch the print window when the PDF is opened.
```

add_link(pagenum: int, page_destination: int, rect: RectangleObject, border: Optional[ArrayObject] =
 None, fit: Literal['/Fit', '/XYZ', '/FitH', '/FitV', '/FitR', '/FitB', '/FitBH', '/FitBV'] = '/Fit', *args:
 Union[NumberObject, NullObject, float]) → None

add_metadata(*infos:* Dict[str, Any]) \rightarrow None

Add custom metadata to the output.

Parameters

infos (dict) – a Python dictionary where each key is a field and each value is your new metadata.

- add_named_destination(*title: str, page_number: Optional[int] = None, pagenum: Optional[int] = None*) → IndirectObject
- add_named_destination_array(title: TextStringObject, destination: Union[IndirectObject, ArrayObject]) \rightarrow None

add_named_destination_object(page_destination: Optional[PdfObject] = None, dest: $Optional[PdfObject] = None) \rightarrow IndirectObject$

add_outline() \rightarrow None

Add an outline item (commonly referred to as a "Bookmark") to this PDF file.

Parameters

- **title** (*str*) Title to use for this outline item.
- page_number (int) Page number this outline item will point to.
- parent A reference to a parent outline item to create nested outline items.
- **parent** A reference to a parent outline item to create nested outline items.
- **color** (*tuple*) Color of the outline item's font as a red, green, blue tuple from 0.0 to 1.0 or as a Hex String (#RRGGBB)
- **bold** (*bool*) Outline item font is bold
- italic (bool) Outline item font is italic
- **fit** (Fit) The fit of the destination page.

add_outline_item_destination(page_destination: Union[None, PageObject, TreeObject] = None,

parent: Union[None, TreeObject, IndirectObject] = None, before: Union[None, TreeObject, IndirectObject] = None, dest: Union[None, PageObject, TreeObject] = None) \rightarrow IndirectObject add_outline_item_dict(outline_item: Union[OutlineItem, Destination], parent: Union[None, TreeObject, IndirectObject] = None, before: Union[None, TreeObject, IndirectObject] = None) → IndirectObject

add_page(page: PageObject, excluded_keys: Iterable[str] = ()) → PageObject

Add a page to this PDF file. Recommended for advanced usage including the adequate excluded_keys

The page is usually acquired from a *PdfReader* instance.

Parameters

page (PageObject) – The page to add to the document. Should be an instance of *PageObject*

add_uri(page_number: int, uri: str, rect: RectangleObject, border: Optional[ArrayObject] = None, pagenum: Optional[int] = None) \rightarrow None

Add an URI from a rectangular area to the specified page. This uses the basic structure of add_link()

Parameters

- page_number (*int*) index of the page on which to place the URI action.
- **uri** (*str*) URI of resource to link to.
- rect (Tuple[int, int, int, int]) RectangleObject or array of four integers specifying the clickable rectangular area [xLL, yLL, xUR, yUR], or string in the form "[xLL yLL xUR yUR]".
- **border** (*ArrayObject*) if provided, an array describing border-drawing properties. See the PDF spec for details. No border will be drawn if this argument is omitted.

append(*fileobj:* Union[str, IO, PdfReader, Path], outline_item: Union[str, None, PageRange, Tuple[int, int], $Tuple[int, int, int], List[int]] = None, pages: Union[None, PageRange, Tuple[int, int], Tuple[int, int, int], List[int]] = None, import_outline: bool = True, excluded_fields: Optional[Union[List[str], Tuple[str, ...]]] = None) \rightarrow None$

Identical to the *merge()* method, but assumes you want to concatenate all pages onto the end of the file instead of specifying a position.

Parameters

- **fileobj** A File Object or an object that supports the standard read and seek methods similar to a File Object. Could also be a string representing a path to a PDF file.
- **outline_item** (*str*) Optionally, you may specify a string to build an outline (aka 'book-mark') to identify the beginning of the included file.
- **pages** can be a *PageRange* or a (start, stop[, step]) tuple or a list of pages to be processed to merge only the specified range of pages from the source document into the output document.
- **import_outline** (*bool*) You may prevent the source document's outline (collection of outline items, previously referred to as 'bookmarks') from being imported by specifying this as False.
- **excluded_fields** (*List*) provide the list of fields/keys to be ignored if "/Annots" is part of the list, the annotation will be ignored if "/B" is part of the list, the articles will be ignored

appendPagesFromReader(reader: PdfReader, after_page_append: Optional[Callable[[PageObject], None]] = None) \rightarrow None

Deprecated since version 1.28.0: Use append_pages_from_reader() instead.

append_pages_from_reader(reader: PdfReader, after_page_append: Optional[Callable[[PageObject], None]] = None) \rightarrow None

Copy pages from reader to writer. Includes an optional callback parameter which is invoked after pages are appended to the writer.

Parameters

- **reader** (PdfReader) a PdfReader object from which to copy page annotations to this writer object. The writer's annots will then be updated
- **after_page_append** (*Callable[[PageObject]*, *None]*) Callback function that is invoked after each page is appended to the writer. Signature includes a reference to the appended page (delegates to append_pages_from_reader). The single parameter of the callback is a reference to the page just appended to the document.

clean_page(*page: Union*[PageObject, *IndirectObject*]) → *PageObject*])

Perform some clean up in the page. Currently: convert NameObject nameddestination to TextStringObject (required for names/dests list)

cloneDocumentFromReader(*reader*: PdfReader, *after_page_append*: Optional[Callable[[PageObject], None]] = None) \rightarrow None

Deprecated since version 1.28.0: Use clone_document_from_reader() instead.

$\texttt{cloneReaderDocumentRoot}(\mathit{reader}: \mathsf{PdfReader}) \rightarrow \mathsf{None}$

Deprecated since version 1.28.0: Use clone_reader_document_root() instead.

clone_document_from_reader(*reader*: PdfReader, *after_page_append*: Optional[Callable[[PageObject], None]] = None) \rightarrow None

Create a copy (clone) of a document from a PDF file reader

Parameters

- reader PDF file reader instance from which the clone should be created.
- **after_page_append** (*Callable[[PageObject]*, *None]*) Callback function that is invoked after each page is appended to the writer. Signature includes a reference to the appended page (delegates to append_pages_from_reader). The single parameter of the callback is a reference to the page just appended to the document.

clone_reader_document_root(reader: PdfReader) \rightarrow None

Copy the reader document root to the writer.

Parameters

reader – PdfReader from the document root should be copied.

$\texttt{close()} \rightarrow \text{None}$

To match the functions from Merger

 $\begin{aligned} \texttt{encrypt}(user_password: Optional[str] = None, owner_password: Optional[str] = None, use_128bit: bool = \\ True, permissions_flag: UserAccessPermissions = UserAccessPermissions.PRINT | MODIFY | \\ EXTRACT | ADD_OR_MODIFY | R7 | R8 | FILL_FORM_FIELDS | \\ EXTRACT_TEXT_AND_GRAPHICS | ASSEMBLE_DOC | PRINT_TO_REPRESENTATION | R13 | \\ R14 | R15 | R16 | R17 | R18 | R19 | R20 | R21 | R22 | R23 | R24 | R25 | R26 | R27 | R28 | R29 | R30 | \\ R31, user_pwd: Optional[str] = None, owner_pwd: Optional[str] = None) \rightarrow None \end{aligned}$

Encrypt this PDF file with the PDF Standard encryption handler.

Parameters

• **user_password** (*str*) – The "user password", which allows for opening and reading the PDF file with the restrictions provided.

- owner_password (str) The "owner password", which allows for opening the PDF files without any restrictions. By default, the owner password is the same as the user password.
- **use_128bit** (*bool*) flag as to whether to use 128bit encryption. When false, 40bit encryption will be used. By default, this flag is on.
- **permissions_flag** (*unsigned int*) permissions as described in TABLE 3.20 of the PDF 1.7 specification. A bit value of 1 means the permission is grantend. Hence an integer value of -1 will set all flags. Bit position 3 is for printing, 4 is for modifying content, 5 and 6 control annotations, 9 for form fields, 10 for extraction of text and graphics.

find_bookmark(*outline_item: Dict[str, Any], root: Optional[List[Union[Destination, List[Union[Destination, List[Destination]]]]] = None*) \rightarrow Optional[List[int]]

Deprecated since version 2.9.0: Use find_outline_item() instead.

find_outline_item(*outline_item*: *Dict[str, Any], root: Optional[List[Union[Destination, List[Union[Destination, List[Destination]]]]] = None*) \rightarrow Optional[List[int]]

 $\texttt{getNamedDestRoot}() \rightarrow ArrayObject$

Deprecated since version 1.28.0: Use get_named_dest_root() instead.

$\texttt{getNumPages()} \rightarrow \texttt{int}$

Deprecated since version 1.28.0: Use len(writer.pages) instead.

getObject(*ido: Union*[*int, IndirectObject*]) → PdfObject

Deprecated since version 1.28.0: Use get_object() instead.

getOutlineRoot() \rightarrow TreeObject

Deprecated since version 1.28.0: Use get_outline_root() instead.

getPage(pageNumber: int) \rightarrow PageObject

Deprecated since version 1.28.0: Use writer.pages[page_number] instead.

getPageLayout () → Optional[Literal['/NoLayout', '/SinglePage', '/OneColumn', '/TwoColumnLeft', '/TwoColumnRight', '/TwoPageLeft', '/TwoPageRight']]

Deprecated since version 1.28.0: Use page_layout instead.

 $\label{eq:getPageMode()} \begin{array}{l} \rightarrow \mbox{ Optional[Literal['/UseNone', '/UseOutlines', '/UseThumbs', '/FullScreen', '/UseOC', '/UseAttachments']] \end{array}$

Deprecated since version 1.28.0: Use *page_mode* instead.

- getReference(*obj: PdfObject*) \rightarrow IndirectObject Deprecated since version 1.28.0: Use get_reference() instead.
- $\texttt{get_named_dest_root()} \rightarrow \textit{ArrayObject}$

get_outline_root() → TreeObject

get_page(page_number: Optional[int] = None, pageNumber: Optional[int] = None) \rightarrow PageObject Retrieve a page by number from this PDF file.

Parameters

page_number (*int*) – The page number to retrieve (pages begin at zero)

Returns

the page at the index given by *page_number*

get_reference(obj: PdfObject) \rightarrow IndirectObject

 $\texttt{get_threads_root()} \rightarrow \textit{ArrayObject}$

the list of threads see §8.3.2 from PDF 1.7 spec

return

an Array (possibly empty) of Dictionaries with "/F" and "/I" properties

insertBlankPage(*width: Optional*[Decimal] = None, height: Optional[Decimal] = None, index: int = 0) \rightarrow PageObject

Deprecated since version 1.28.0: Use *insertBlankPage()* instead.

insertPage(*page*: PageObject, *index*: *int* = 0, *excluded_keys*: *Iterable*[*str*] = ()) \rightarrow *PageObject*

Deprecated since version 1.28.0: Use *insert_page()* instead.

insert_blank_page(width: Optional[Decimal] = None, height: Optional[Decimal] = None, index: int = 0) \rightarrow PageObject

Insert a blank page to this PDF file and returns it. If no page size is specified, use the size of the last page.

Parameters

- width (float) The width of the new page expressed in default user space units.
- height (float) The height of the new page expressed in default user space units.
- **index** (*int*) Position to add the page.

Returns

the newly appended page

Raises

PageSizeNotDefinedError – if width and height are not defined and previous page does not exist.

insert_page(*page:* PageObject, *index: int* = 0, *excluded_keys: Iterable*[*str*] = ()) \rightarrow *PageObject* Insert a page in this PDF file. The page is usually acquired from a *PdfReader* instance.

Parameters

- page (PageObject) The page to add to the document.
- **index** (*int*) Position at which the page will be inserted.
- **merge**(*position: Optional[int]*, *fileobj: Union[Path, str, IO,* PdfReader], *outline_item: Optional[str]* = None, pages: Optional[Union[str, PageRange, Tuple[int, int], Tuple[int, int, int], List[int]]] = None, import_outline: bool = True, excluded_fields: Optional[Union[List[str], Tuple[str, ...]]] = ()) \rightarrow None

Merge the pages from the given file into the output file at the specified page number.

Parameters

- **position** (*int*) The *page number* to insert this file. File will be inserted after the given number.
- **fileobj** A File Object or an object that supports the standard read and seek methods similar to a File Object. Could also be a string representing a path to a PDF file.
- **outline_item** (*str*) Optionally, you may specify a string to build an outline (aka 'book-mark') to identify the beginning of the included file.
- **pages** can be a *PageRange* or a (start, stop[, step]) tuple or a list of pages to be processed to merge only the specified range of pages from the source document into the output document.

- **import_outline** (*bool*) You may prevent the source document's outline (collection of outline items, previously referred to as 'bookmarks') from being imported by specifying this as False.
- **excluded_fields** (*List*) provide the list of fields/keys to be ignored if "/Annots" is part of the list, the annotation will be ignored if "/B" is part of the list, the articles will be ignored

property open_destination: Union[None, Destination, TextStringObject, ByteStringObject]

Property to access the opening destination ("/OpenAction" entry in the PDF catalog). it returns *None* if the entry does not exist is not set.

:param destination:. the property can be set to a Destination, a Page or an string(NamedDest) or

None (to remove "/OpenAction")

(value stored in "/OpenAction" entry in the Pdf Catalog)

```
property pageLayout: Optional[Literal['/NoLayout', '/SinglePage', '/OneColumn',
'/TwoColumnLeft', '/TwoColumnRight', '/TwoPageLeft', '/TwoPageRight']]
```

Deprecated since version 1.28.0.

Use page_layout instead.

```
property pageMode: Optional[Literal['/UseNone', '/UseOutlines', '/UseThumbs',
'/FullScreen', '/UseOC', '/UseAttachments']]
```

Deprecated since version 1.28.0.

Use page_mode instead.

```
property page_layout: Optional[Literal['/NoLayout', '/SinglePage', '/OneColumn',
'/TwoColumnLeft', '/TwoColumnRight', '/TwoPageLeft', '/TwoPageRight']]
```

Page layout property.

/NoLayout	Layout explicitly not specified
/SinglePage	Show one page at a time
/OneColumn	Show one column at a time
/TwoColumnLeft	Show pages in two columns, odd-numbered pages on the left
/TwoColumn-	Show pages in two columns, odd-numbered pages on the right
Right	
/TwoPageLeft	Show two pages at a time, odd-numbered pages on the left
/TwoPageRight	Show two pages at a time, odd-numbered pages on the right

Table 1: Valid layout values

property page_mode: Optional[Literal['/UseNone', '/UseOutlines', '/UseThumbs', '/FullScreen', '/UseOC', '/UseAttachments']]

Page mode property.

Table 2:	Valid mode	values
----------	------------	--------

/UseNone	Do not show outline or thumbnails panels
/UseOutlines	Show outline (aka bookmarks) panel
/UseThumbs	Show page thumbnails panel
/FullScreen	Fullscreen view
/UseOC	Show Optional Content Group (OCG) panel
/UseAttachments	Show attachments panel

property pages: List[PageObject]

Property that emulates a list of PageObject.

property pdf_header: bytes

Header of the PDF document that is written.

This should be something like b'%PDF-1.5'. It is recommended to set the lowest version that supports all features which are used within the PDF file.

removeImages(*ignoreByteStringObject: bool* = *False*) \rightarrow None

Deprecated since version 1.28.0: Use *remove_images()* instead.

 $removeLinks() \rightarrow None$

Deprecated since version 1.28.0: Use *remove_links()* instead.

removeText(*ignoreByteStringObject:* bool = False) \rightarrow None

Deprecated since version 1.28.0: Use *remove_text()* instead.

remove_images(*ignore_byte_string_object: bool* = *False*) \rightarrow None Remove images from this output.

Parameters

ignore_byte_string_object (*bool*) – optional parameter to ignore ByteString Objects.

$\textbf{remove_links()} \rightarrow None$

Remove links and annotations from this output.

remove_text(*ignore_byte_string_object: bool = False*) \rightarrow None

Remove text from this output.

Parameters

ignore_byte_string_object (bool) - optional parameter to ignore ByteString Objects.

reset_translation(*reader: Union*[*None*, PdfReader, *IndirectObject*] = *None*) \rightarrow None

reset the translation table between reader and the writer object. late cloning will create new independent objects

Parameters

reader – PdfReader or IndirectObject refering a PdfReader object. if set to None or omitted, all tables will be reset.

setPageLayout (*layout: Literal['/NoLayout', '/SinglePage', '/OneColumn', '/TwoColumnLeft', '/TwoColumnRight', '/TwoPageLeft', '/TwoPageRight']*) → None

Deprecated since version 1.28.0: Use page_layout instead.

 $setPageMode(mode: Literal['/UseNone', '/UseOutlines', '/UseThumbs', '/FullScreen', '/UseOC', '/UseAttachments']) \rightarrow None$

Deprecated since version 1.28.0: Use page_mode instead.

$\texttt{set_need_appearances_writer()} \rightarrow None$

set_page_layout(*layout*: *Literal['/NoLayout', '/SinglePage', '/OneColumn', '/TwoColumnLeft', '/TwoColumnRight', '/TwoPageLeft', '/TwoPageRight']*) → None

Set the page layout.

Parameters layout (*str*) – The page layout to be used

/NoLayout	Layout explicitly not specified
/SinglePage	Show one page at a time
/OneColumn	Show one column at a time
/TwoColumnLeft	Show pages in two columns, odd-numbered pages on the left
/TwoColumn-	Show pages in two columns, odd-numbered pages on the right
Right	
/TwoPageLeft	Show two pages at a time, odd-numbered pages on the left
/TwoPageRight	Show two pages at a time, odd-numbered pages on the right

Table 3: Valid layout arguments

set_page_mode(mode: Literal['/UseNone', '/UseOutlines', '/UseThumbs', '/FullScreen', '/UseOC', '/UseAttachments']) \rightarrow None

Deprecated since version 1.28.0: Use page_mode instead.

property threads: ArrayObject

Read-only property for the list of threads see §8.3.2 from PDF 1.7 spec

Returns

an Array (possibly empty) of Dictionaries with "/F" and "/I" properties

 $\label{eq:pageFormFieldValues(page: ~PyPDF2_page.PageObject, fields: ~typing.Dict[str, ~typing.Any], \\ flags: ~PyPDF2.constants.FieldFlag = FieldFlag.None) \rightarrow \mbox{None}$

Deprecated since version 1.28.0: Use update_page_form_field_values() instead.

update_page_form_field_values(page: ~PyPDF2._page.PageObject, fields: ~typing.Dict[str, ~typing.Any], flags: ~PyPDF2.constants.FieldFlag = FieldFlag.None) → None

Update the form field values for a given page from a fields dictionary.

Copy field texts and values from fields to page. If the field links to a parent object, add the information to the parent.

Parameters

- **page** (PageObject) Page reference from PDF writer where the annotations and field data will be updated.
- fields (dict) a Python dictionary of field names (/T) and text values (/V)
- **flags** (*int*) An integer (0 to 7). The first bit sets ReadOnly, the second bit sets Required, the third bit sets NoExport. See PDF Reference Table 8.70 for details.

write(stream: Union[Path, str, IO]) \rightarrow Tuple[bool, IO]

Write the collection of pages added to this object out as a PDF file.

Parameters

stream – An object to write the file to. The object can support the write method and the tell method, similar to a file object, or be a file path, just like the fileobj, just named it stream to keep existing workflow.

write_stream(stream: IO) \rightarrow None

CHAPTER TWENTYTWO

THE PDFMERGER CLASS

class PyPDF2.**PdfMerger**(*strict: bool = False, fileobj: Union*[*Path, str, IO*] = ")

Bases: object

Initialize a PdfMerger object.

PdfMerger merges multiple PDFs into a single PDF. It can concatenate, slice, insert, or any combination of the above.

See the functions merge() (or append()) and write() for usage information.

Parameters

- **strict** (*bool*) Determines whether user should be warned of all problems and also causes some correctable problems to be fatal. Defaults to False.
- fileobj Output file. Can be a filename or any kind of file-like object.

addBookmark(title: str, pagenum: int, parent: Union[None, TreeObject, IndirectObject] = None, color: Optional[Tuple[float, float, float]] = None, bold: bool = False, italic: bool = False, fit: Literal['/Fit', '/XYZ', '/FitH', '/FitV', '/FitR', '/FitB', '/FitBV'] = '/Fit', *args: Union[NumberObject, NullObject, float]) → IndirectObject

Deprecated since version 1.28.0: Use add_outline_item() instead.

addMetadata(*infos:* Dict[str, Any]) \rightarrow None

Deprecated since version 1.28.0: Use add_metadata() instead.

addNamedDestination(*title: str*, *pagenum: int*) \rightarrow None

Deprecated since version 1.28.0: Use add_named_destination() instead.

Deprecated since version 2.9.0: Use add_outline_item() instead.

add_metadata(*infos:* Dict[str, Any]) \rightarrow None

Add custom metadata to the output.

Parameters

infos (dict) – a Python dictionary where each key is a field and each value is your new metadata. Example: {u'/Title': u'My title'}

add_named_destination(*title: str, page_number: Optional[int] = None, pagenum: Optional[int] = None*) \rightarrow None

Add a destination to the output.

Parameters

• **title** (*str*) – Title to use

• page_number (int) – Page number this destination points at.

~typing.Optional[~typing.luple[ftoat, ftoat, ftoat]] = None, bold: bool = False, italic: bool = False, fit: ~PyPDF2.generic._fit.Fit = <PyPDF2.generic._fit.Fit object>, pagenum: ~typing.Optional[int] = None) → IndirectObject

Add an outline item (commonly referred to as a "Bookmark") to this PDF file.

Parameters

- **title** (*str*) Title to use for this outline item.
- page_number (*int*) Page number this outline item will point to.
- **parent** A reference to a parent outline item to create nested outline items.
- color (tuple) Color of the outline item's font as a red, green, blue tuple from 0.0 to 1.0
- **bold** (*bool*) Outline item font is bold
- **italic** (*bool*) Outline item font is italic
- **fit** (Fit) The fit of the destination page.
- **append**(*fileobj:* Union[str, IO, PdfReader, Path], outline_item: Optional[str] = None, pages: Union[None, PageRange, Tuple[int, int], Tuple[int, int], List[int]] = None, import_outline: bool = True) \rightarrow None

Identical to the *merge()* method, but assumes you want to concatenate all pages onto the end of the file instead of specifying a position.

Parameters

- **fileobj** A File Object or an object that supports the standard read and seek methods similar to a File Object. Could also be a string representing a path to a PDF file.
- **outline_item** (*str*) Optionally, you may specify an outline item (previously referred to as a 'bookmark') to be applied at the beginning of the included file by supplying the text of the outline item.
- **pages** can be a *PageRange* or a (start, stop[, step]) tuple to merge only the specified range of pages from the source document into the output document. Can also be a list of pages to append.
- **import_outline** (*bool*) You may prevent the source document's outline (collection of outline items, previously referred to as 'bookmarks') from being imported by specifying this as False.

$close() \rightarrow None$

Shut all file descriptors (input and output) and clear all memory usage.

find_bookmark(*outline_item: Dict[str, Any], root: Optional[List[Union[Destination, List[Union[Destination, List[Destination, List[Destination]]]]] = None*) → Optional[List[int]]

Deprecated since version 2.9.0: Use find_outline_item() instead.

find_outline_item (outline_item: Dict[str, Any], root: Optional[List[Union[Destination, List[Union[Destination, List[Destination]]]]]] = None) → Optional[List[int]] **merge**(*page_number: Optional[int]* = *None, fileobj: Union[Path, str, IO,* PdfReader] = *None, outline_item: Optional[str]* = *None, pages: Optional[Union[str,* PageRange, Tuple[int, int], Tuple[int, int, int], List[int]]] = None, import_outline: bool = True, position: Optional[int] = None) \rightarrow None

Merge the pages from the given file into the output file at the specified page number.

Parameters

- **page_number** (*int*) The *page number* to insert this file. File will be inserted after the given number.
- **fileobj** A File Object or an object that supports the standard read and seek methods similar to a File Object. Could also be a string representing a path to a PDF file.
- **outline_item** (*str*) Optionally, you may specify an outline item (previously referred to as a 'bookmark') to be applied at the beginning of the included file by supplying the text of the outline item.
- **pages** can be a *PageRange* or a (start, stop[, step]) tuple to merge only the specified range of pages from the source document into the output document. Can also be a list of pages to merge.
- **import_outline** (*bool*) You may prevent the source document's outline (collection of outline items, previously referred to as 'bookmarks') from being imported by specifying this as False.

Deprecated since version 1.28.0: Use set_page_layout() instead.

setPageMode(mode: Literal['/UseNone', '/UseOutlines', '/UseThumbs', '/FullScreen', '/UseOC', '/UseAttachments']) \rightarrow None

Deprecated since version 1.28.0: Use set_page_mode() instead.

Set the page layout.

Parameters

layout (*str*) – The page layout to be used

Table 1:	Valid	layout	arguments
----------	-------	--------	-----------

/NoLayout	Layout explicitly not specified
/SinglePage	Show one page at a time
/OneColumn	Show one column at a time
/TwoColumnLeft	Show pages in two columns, odd-numbered pages on the left
/TwoColumn-	Show pages in two columns, odd-numbered pages on the right
Right	
/TwoPageLeft	Show two pages at a time, odd-numbered pages on the left
/TwoPageRight	Show two pages at a time, odd-numbered pages on the right

set_page_mode(mode: Literal['/UseNone', '/UseOutlines', '/UseThumbs', '/FullScreen', '/UseOC', '/UseAttachments']) \rightarrow None

Set the page mode.

Parameters

mode (str) – The page mode to use.

/UseNone	Do not show outline or thumbnails panels	
/UseOutlines	Show outline (aka bookmarks) panel	
/UseThumbs	Show page thumbnails panel	
/FullScreen	Fullscreen view	
/UseOC	Show Optional Content Group (OCG) panel	
/UseAttachments	Show attachments panel	

Table 2: Valid mode arguments

write(*fileobj: Union*[*Path, str, IO*]) \rightarrow None

Write all data that has been merged to the given output file.

Parameters

fileobj – Output file. Can be a filename or any kind of file-like object.

Note: This page is about PyPDF2. PyPDF2 is deprecated, please use pypdf

CHAPTER

TWENTYTHREE

THE PAGEOBJECT CLASS

Bases: DictionaryObject

PageObject represents a single page within a PDF file.

Typically this object will be created by accessing the get_page() method of the *PdfReader* class, but it is also possible to create an empty page with the *create_blank_page()* static method.

Parameters

- **pdf** PDF file the page belongs to.
- indirect_reference Stores the original indirect reference to this object in its source PDF

addTransformation(*ctm: Tuple[float, float, float, float, float, float, float]*) \rightarrow None

Deprecated since version 1.28.0: Use add_transformation() instead.

add_transformation(ctm: Union[Transformation, Tuple[float, float, float, float, float, float]], expand: bool $= False) \rightarrow None$

Apply a transformation matrix to the page.

Parameters

ctm – A 6-element tuple containing the operands of the transformation matrix. Alternatively, a *Transformation* object can be passed.

See Cropping and Transforming PDFs.

property annotations: Optional[ArrayObject]

property artBox: RectangleObject

Deprecated since version 1.28.0.

Use artbox instead.

property artbox

A *RectangleObject*, expressed in default user space units, defining the extent of the page's meaningful content as intended by the page's creator.

property bleedBox: RectangleObject

Deprecated since version 1.28.0.

Use *bleedbox* instead.

property bleedbox

A *RectangleObject*, expressed in default user space units, defining the region to which the contents of the page should be clipped when output in a production environment.

$compressContentStreams() \rightarrow None$

Deprecated since version 1.28.0: Use compress_content_streams() instead.

$\texttt{compress_content_streams()} \rightarrow None$

Compress the size of this page by joining all content streams and applying a FlateDecode filter.

However, it is possible that this function will perform no action if content stream compression becomes "automatic".

static createBlankPage(pdf: Optional[Any] = None, width: Optional[Union[float, Decimal]] = None, height: Optional[Union[float, Decimal]] = None) \rightarrow PageObject

Deprecated since version 1.28.0: Use create_blank_page() instead.

static create_blank_page(pdf: Optional[Any] = None, width: Optional[Union[float, Decimal]] = None, height: Optional[Union[float, Decimal]] = None) \rightarrow PageObject

Return a new blank page.

If width or height is None, try to get the page size from the last page of *pdf*.

Parameters

- **pdf** PDF file the page belongs to
- width The width of the new page expressed in default user space units.
- height The height of the new page expressed in default user space units.

Returns

The new blank page

Raises

PageSizeNotDefinedError – if pdf is None or contains no page

property cropBox: RectangleObject

Deprecated since version 1.28.0.

Use cropbox instead.

property cropbox

A *RectangleObject*, expressed in default user space units, defining the visible region of default user space. When the page is displayed or printed, its contents are to be clipped (cropped) to this rectangle and then imposed on the output medium in some implementation-defined manner. Default value: same as *mediabox*.

extractText($Tj_sep: str = ", TJ_sep: str = ") \rightarrow str$

Deprecated since version 1.28.0: Use *extract_text()* instead.

extract_text(*args: Any, Tj_sep: str = None, TJ_sep: str = None, orientations: Union[int, Tuple[int, ...]] = (0, 90, 180, 270), space_width: float = 200.0, visitor_operand_before: Optional[Callable[[Any, Any, Any, Any], None]] = None, visitor_operand_after: Optional[Callable[[Any, Any, Any, Any], None]] = None, visitor_text: Optional[Callable[[Any, Any, Any, Any, Any], None]] = None) → str

Locate all text drawing commands, in the order they are provided in the content stream, and extract the text.

This works well for some PDF files, but poorly for others, depending on the generator used. This will be refined in the future.

Do not rely on the order of text coming out of this function, as it will change if this function is made more sophisticated.

Arabic, Hebrew,... are extracted in the good order. If required an custom RTL range of characters can be defined; see function set_custom_rtl

Additionally you can provide visitor-methods to get informed on all operands and all text-objects. For example in some PDF files this can be useful to parse tables.

Parameters

- Tj_sep Deprecated. Kept for compatibility until PyPDF2 4.0.0
- TJ_sep Deprecated. Kept for compatibility until PyPDF2 4.0.0
- **orientations** list of orientations text_extraction will look for default = (0, 90, 180, 270) note: currently only 0(Up),90(turned Left), 180(upside Down), 270 (turned Right)
- space_width force default space width if not extracted from font (default: 200)
- visitor_operand_before function to be called before processing an operand. It has four arguments: operand, operand-arguments, current transformation matrix and text matrix.
- **visitor_operand_after** function to be called after processing an operand. It has four arguments: operand, operand-arguments, current transformation matrix and text matrix.
- **visitor_text** function to be called when extracting some text at some position. It has five arguments: text, current transformation matrix, text matrix, font-dictionary and font-size. The font-dictionary may be None in case of unknown fonts. If not None it may e.g. contain key "/BaseFont" with value "/Arial,Bold".

Returns

The extracted text

```
\begin{aligned} \texttt{extract\_xform\_text}(x form: EncodedStreamObject, orientations: Tuple[int, ...] = (0, 90, 270, 360), \\ space\_width: float = 200.0, visitor\_operand\_before: Optional[Callable[[Any, Any, Any, Any], None]] = None, visitor\_operand\_after: Optional[Callable[[Any, Any, Any, Any], None]] = None, visitor\_text: Optional[Callable[[Any, Any, Any, Any], None]] = None) \rightarrow \\ \texttt{str} \end{aligned}
```

Extract text from an XObject.

Parameters

space_width – force default space width (if not extracted from font (default 200)

Returns

The extracted text

$getContents() \rightarrow Optional[ContentStream]$

Deprecated since version 1.28.0: Use get_contents() instead.

$get_contents() \rightarrow Optional[ContentStream]$

Access the page contents.

Returns

the /Contents object, or None if it doesn't exist. /Contents is optional, as described in PDF Reference 7.7.3.3

 $hash_value_data() \rightarrow bytes$

property images: List[File]

Get a list of all images of the page.

This requires pillow. You can install it via 'pip install PyPDF2[image]'.

For the moment, this does NOT include inline images. They will be added in future.

property indirect_ref: Optional[IndirectObject]

property mediaBox: RectangleObject

Deprecated since version 1.28.0.

Use mediabox instead.

property mediabox

A *RectangleObject*, expressed in default user space units, defining the boundaries of the physical medium on which the page is intended to be displayed or printed.

mergePage(*page2:* PageObject) \rightarrow None

Deprecated since version 1.28.0: Use merge_page() instead.

mergeRotatedPage(*page2:* PageObject, *rotation: float, expand: bool* = *False*) \rightarrow None

mergeRotatedPage is similar to merge_page, but the stream to be merged is rotated by applying a transformation matrix.

Parameters

- **page2** (PageObject) the page to be merged into this one. Should be an instance of *PageObject*.
- rotation (float) The angle of the rotation, in degrees
- **expand** (*bool*) Whether the page should be expanded to fit the dimensions of the page to be merged.

Deprecated since version 1.28.0: Use add_transformation() and merge_page() instead.

mergeRotatedScaledPage(*page2*: PageObject, *rotation: float, scale: float, expand: bool = False*) \rightarrow None mergeRotatedScaledPage is similar to merge_page, but the stream to be merged is rotated and scaled by applying a transformation matrix.

Parameters

- **page2** (PageObject) the page to be merged into this one. Should be an instance of *PageObject*.
- rotation (float) The angle of the rotation, in degrees
- **scale** (*float*) The scaling factor
- **expand** (*bool*) Whether the page should be expanded to fit the dimensions of the page to be merged.

Deprecated since version 1.28.0: Use add_transformation() and merge_page() instead.

mergeRotatedScaledTranslatedPage(*page2:* PageObject, *rotation: float*, *scale: float*, *tx: float*, *ty: float*, *expand: bool* = *False*) \rightarrow None

mergeRotatedScaledTranslatedPage is similar to merge_page, but the stream to be merged is translated, rotated and scaled by applying a transformation matrix.

Parameters

• **page2** (PageObject) – the page to be merged into this one. Should be an instance of *PageObject*.

- **tx** (*float*) The translation on X axis
- ty (float) The translation on Y axis
- **rotation** (*float*) The angle of the rotation, in degrees
- **scale** (*float*) The scaling factor
- **expand** (*bool*) Whether the page should be expanded to fit the dimensions of the page to be merged.

Deprecated since version 1.28.0: Use add_transformation() and merge_page() instead.

mergeRotatedTranslatedPage(*page2:* PageObject, *rotation: float, tx: float, ty: float, expand: bool* = False) \rightarrow None

mergeRotatedTranslatedPage is similar to merge_page, but the stream to be merged is rotated and translated by applying a transformation matrix.

Parameters

- **page2** (PageObject) the page to be merged into this one. Should be an instance of *PageObject*.
- tx (float) The translation on X axis
- ty (float) The translation on Y axis
- rotation (float) The angle of the rotation, in degrees
- **expand** (*bool*) Whether the page should be expanded to fit the dimensions of the page to be merged.

Deprecated since version 1.28.0: Use add_transformation() and merge_page() instead.

mergeScaledPage(*page2:* PageObject, *scale: float, expand: bool* = *False*) \rightarrow None

mergeScaledPage is similar to merge_page, but the stream to be merged is scaled by applying a transformation matrix.

Parameters

- **page2** (PageObject) The page to be merged into this one. Should be an instance of *PageObject*.
- **scale** (*float*) The scaling factor
- **expand** (*bool*) Whether the page should be expanded to fit the dimensions of the page to be merged.

Deprecated since version 1.28.0: Use add_transformation() and merge_page() instead.

mergeScaledTranslatedPage(*page2:* PageObject, *scale: float, tx: float, ty: float, expand: bool* = *False*) \rightarrow None

mergeScaledTranslatedPage is similar to merge_page, but the stream to be merged is translated and scaled by applying a transformation matrix.

Parameters

- **page2** (PageObject) the page to be merged into this one. Should be an instance of *PageObject*.
- scale (float) The scaling factor
- **tx** (*float*) The translation on X axis
- **ty** (*float*) The translation on Y axis

• **expand** (*bool*) – Whether the page should be expanded to fit the dimensions of the page to be merged.

Deprecated since version 1.28.0: Use *add_transformation()* and *merge_page()* instead.

mergeTransformedPage(*page2:* PageObject, *ctm:* Union[Tuple[float, float, float, float, float], Transformation], *expand:* $bool = False) \rightarrow None$

mergeTransformedPage is similar to merge_page, but a transformation matrix is applied to the merged stream.

Parameters

- **page2** (PageObject) The page to be merged into this one. Should be an instance of *PageObject*.
- **ctm** (*tuple*) a 6-element tuple containing the operands of the transformation matrix
- **expand** (*bool*) Whether the page should be expanded to fit the dimensions of the page to be merged.

Deprecated since version 1.28.0: Use *add_transformation()* and *merge_page()* instead.

mergeTranslatedPage(*page2:* PageObject, *tx: float, ty: float, expand: bool* = *False*) \rightarrow None

mergeTranslatedPage is similar to merge_page, but the stream to be merged is translated by applying a transformation matrix.

Parameters

- **page2** (PageObject) the page to be merged into this one. Should be an instance of *PageObject*.
- tx (float) The translation on X axis
- ty (float) The translation on Y axis
- **expand** (*bool*) Whether the page should be expanded to fit the dimensions of the page to be merged.

Deprecated since version 1.28.0: Use add_transformation() and merge_page() instead.

merge_page(*page2:* PageObject, *expand: bool* = *False*) \rightarrow None

Merge the content streams of two pages into one.

Resource references (i.e. fonts) are maintained from both pages. The mediabox/cropbox/etc of this page are not altered. The parameter page's content stream will be added to the end of this page's content stream, meaning that it will be drawn after, or "on top" of this page.

Parameters

- page2 The page to be merged into this one. Should be an instance of PageObject.
- **expand** If true, the current page dimensions will be expanded to accommodate the dimensions of the page to be merged.

original_page: PageObject

rotate(*angle: int*) \rightarrow *PageObject*

Rotate a page clockwise by increments of 90 degrees.

Parameters

angle – Angle to rotate the page. Must be an increment of 90 deg.

$rotateClockwise(angle: int) \rightarrow PageObject$

Deprecated since version 1.28.0: Use rotate_clockwise() instead.

$rotateCounterClockwise(angle: int) \rightarrow PageObject$

Deprecated since version 1.28.0: Use *rotate_clockwise()* with a negative argument instead.

rotate_clockwise(*angle: int*) → *PageObject*

property rotation: int

The VISUAL rotation of the page.

This number has to be a multiple of 90 degrees: 0,90,180,270 This property does not affect "/Contents"

$scale(sx: float, sy: float) \rightarrow None$

Scale a page by the given factors by applying a transformation matrix to its content and updating the page size.

This updates the mediabox, the cropbox, and the contents of the page.

Parameters

- **sx** The scaling factor on horizontal axis.
- sy The scaling factor on vertical axis.

scaleBy(*factor: float*) \rightarrow None

Deprecated since version 1.28.0: Use *scale_by()* instead.

scaleTo(*width: float, height: float*) \rightarrow None

Deprecated since version 1.28.0: Use *scale_to()* instead.

scale_by(*factor: float*) \rightarrow None

Scale a page by the given factor by applying a transformation matrix to its content and updating the page size.

Parameters

factor – The scaling factor (for both X and Y axis).

$scale_to(width: float, height: float) \rightarrow None$

Scale a page to the specified dimensions by applying a transformation matrix to its content and updating the page size.

Parameters

- width The new width.
- height The new height.

$\texttt{transfer_rotation_to_content()} \rightarrow \textit{None}$

Apply the rotation of the page to the content and the media/crop/... boxes.

It's recommended to apply this function before page merging.

property trimBox: RectangleObject

Deprecated since version 1.28.0.

Use trimbox instead.

property trimbox

A *RectangleObject*, expressed in default user space units, defining the intended dimensions of the finished page after trimming.

property user_unit: float

A read-only positive number giving the size of user space units.

It is in multiples of 1/72 inch. Hence a value of 1 means a user space unit is 1/72 inch, and a value of 3 means that a user space unit is 3/72 inch.

Note: This page is about PyPDF2. PyPDF2 is deprecated, please use pypdf

CHAPTER

TWENTYFOUR

THE TRANSFORMATION CLASS

class PyPDF2.**Transformation**(*ctm: Tuple[float, float, float, float, float, float, float]* = (1, 0, 0, 1, 0, 0))

Bases: object

Represent a 2D transformation.

The transformation between two coordinate systems is represented by a 3-by-3 transformation matrix matrix with the following form:

a b 0 c d 0 e f 1

Because a transformation matrix has only six elements that can be changed, it is usually specified in PDF as the six-element array [a b c d e f].

Coordinate transformations are expressed as matrix multiplications:

a b 0 [xy1] = [xy1] × cd0 ef1

Example

```
>>> from PyPDF2 import Transformation
>>> op = Transformation().scale(sx=2, sy=3).translate(tx=10, ty=20)
>>> page.add_transformation(op)
```

apply_on(*pt: Union*[Tuple[Decimal, Decimal], Tuple[float, float], List[float]]) \rightarrow Union[Tuple[float, float], List[float]]

Apply the transformation matrix on the given point.

Parameters

pt - A tuple or list representing the point in the form (x, y)

Returns

A tuple or list representing the transformed point in the form (x', y')

static compress(*matrix: Tuple*[*float, float, float*], *Tuple*[*float, float*], *Tuple*[*float, float, float*])) \rightarrow Tuple[float, float, float, float, float, float, float]

Compresses the transformation matrix into a tuple of (a, b, c, d, e, f).

Parameters

matrix – The transformation matrix as a tuple of tuples.

Returns

A tuple representing the transformation matrix as (a, b, c, d, e, f)

property matrix: Tuple[Tuple[float, float, float], Tuple[float, float, float], Tuple[float, float, float]]

Return the transformation matrix as a tuple of tuples in the form: ((a, b, 0), (c, d, 0), (e, f, 1))

 $rotate(rotation: float) \rightarrow Transformation$

Rotate the contents of a page.

Parameters

rotation – The angle of rotation in degrees.

Returns

A new Transformation instance with the rotated matrix.

 $scale(sx: Optional[float] = None, sy: Optional[float] = None) \rightarrow Transformation$

Scale the contents of a page towards the origin of the coordinate system.

Typically, that is the lower-left corner of the page. That can be changed by translating the contents / the page boxes.

Parameters

- **sx** The scale factor along the x-axis.
- **sy** The scale factor along the y-axis.

Returns

A new Transformation instance with the scaled matrix.

translate(*tx: float* = 0, *ty: float* = 0) \rightarrow *Transformation*

Translate the contents of a page.

Parameters

- **tx** The translation along the x-axis.
- **ty** The translation along the y-axis.

Returns

A new Transformation instance

Note: This page is about PyPDF2. PyPDF2 is deprecated, please use pypdf

CHAPTER

TWENTYFIVE

THE DOCUMENTINFORMATION CLASS

class PyPDF2.DocumentInformation

Bases: DictionaryObject

A class representing the basic document metadata provided in a PDF File. This class is accessible through *PdfReader.metadata*.

All text properties of the document metadata have *two* properties, eg. author and author_raw. The non-raw property will always return a TextStringObject, making it ideal for a case where the metadata is being displayed. The raw property can sometimes return a ByteStringObject, if PyPDF2 was unable to decode the string's text encoding; this requires additional safety in the caller and therefore is not as commonly accessed.

property author: Optional[str]

Read-only property accessing the document's author.

Returns a unicode string (TextStringObject) or None if the author is not specified.

property author_raw: Optional[str]

The "raw" version of author; can return a ByteStringObject.

property creation_date: Optional[datetime]

Read-only property accessing the document's **creation date**.

property creation_date_raw: Optional[str]

The "raw" version of creation date; can return a ByteStringObject.

Typically in the format D:YYYYMMDDhhmmss[+-]hh'mm where the suffix is the offset from UTC.

property creator: Optional[str]

Read-only property accessing the document's creator.

If the document was converted to PDF from another format, this is the name of the application (e.g. OpenOffice) that created the original document from which it was converted. Returns a unicode string (TextStringObject) or None if the creator is not specified.

property creator_raw: Optional[str]

The "raw" version of creator; can return a ByteStringObject.

getText(*key: str*) \rightarrow Optional[str]

The text value of the specified key or None.

Deprecated since version 1.28.0: Use the attributes (e.g. title / author).

property modification_date: Optional[datetime]

Read-only property accessing the document's **modification date**.

The date and time the document was most recently modified.

property modification_date_raw: Optional[str]

The "raw" version of modification date; can return a ByteStringObject.

Typically in the format D:YYYYMMDDhhmmss[+-]hh'mm where the suffix is the offset from UTC.

property producer: Optional[str]

Read-only property accessing the document's producer.

If the document was converted to PDF from another format, this is the name of the application (for example, OSX Quartz) that converted it to PDF. Returns a unicode string (TextStringObject) or None if the producer is not specified.

property producer_raw: Optional[str]

The "raw" version of producer; can return a ByteStringObject.

property subject: Optional[str]

Read-only property accessing the document's subject.

Returns a unicode string (TextStringObject) or None if the subject is not specified.

property subject_raw: Optional[str]

The "raw" version of subject; can return a ByteStringObject.

property title: Optional[str]

Read-only property accessing the document's title.

Returns a unicode string (TextStringObject) or None if the title is not specified.

property title_raw: Optional[str]

The "raw" version of title; can return a ByteStringObject.

Note: This page is about PyPDF2. PyPDF2 is deprecated, please use pypdf

CHAPTER

TWENTYSIX

THE XMPINFORMATION CLASS

class PyPDF2.xmp.XmpInformation(stream: ContentStream)

Bases: PdfObject

An object that represents Adobe XMP metadata. Usually accessed by xmp_metadata()

Raises

PdfReadError – if XML is invalid

property custom_properties: Dict[Any, Any]

Retrieve custom metadata properties defined in the undocumented pdfx metadata schema.

Returns

a dictionary of key/value items for custom metadata properties.

property dc_contributor: Optional[List[str]]

Contributors to the resource (other than the authors). An unsorted array of names.

property dc_coverage: Optional[Any]

Text describing the extent or scope of the resource.

property dc_creator: Optional[List[Any]]

A sorted array of names of the authors of the resource, listed in order of precedence.

property dc_date: Optional[List[Any]]

A sorted array of dates (datetime.datetime instances) of significance to the resource. The dates and times are in UTC.

property dc_description: Optional[Dict[Any, Any]]

A language-keyed dictionary of textual descriptions of the content of the resource.

property dc_format: Optional[Any]

The mime-type of the resource.

property dc_identifier: Optional[Any]

Unique identifier of the resource.

property dc_language: Optional[List[str]]

An unordered array specifying the languages used in the resource.

property dc_publisher: Optional[List[str]]

An unordered array of publisher names.

property dc_relation: Optional[List[str]]

An unordered array of text descriptions of relationships to other documents.

property dc_rights: Optional[Dict[Any, Any]]

A language-keyed dictionary of textual descriptions of the rights the user has to this resource.

property dc_source: Optional[Any]

Unique identifier of the work from which this resource was derived.

property dc_subject: Optional[List[str]]

An unordered array of descriptive phrases or keywrods that specify the topic of the content of the resource.

property dc_title: Optional[Dict[Any, Any]]

A language-keyed dictionary of the title of the resource.

property dc_type: Optional[List[str]]

An unordered array of textual descriptions of the document type.

- **getElement**(*aboutUri: str, namespace: str, name: str*) \rightarrow Iterator[Any] Deprecated since version 1.28.0: Use *get_element()* instead.
- getNodesInNamespace(*aboutUri: str, namespace: str*) \rightarrow Iterator[Any] Deprecated since version 1.28.0: Use get_nodes_in_namespace() instead.
- get_element(*about_uri: str, namespace: str, name: str*) \rightarrow Iterator[Any]

get_nodes_in_namespace(*about_uri: str, namespace: str*) → Iterator[Any]

property pdf_keywords: Optional[Any]

An unformatted text string representing document keywords.

property pdf_pdfversion: Optional[Any]

The PDF file version, for example 1.0, 1.3.

property pdf_producer: Optional[Any]

The name of the tool that created the PDF document.

property rdfRoot: Element

- writeToStream(stream: IO, encryption_key: Union[None, str, bytes]) \rightarrow None Deprecated since version 1.28.0: Use write_to_stream() instead.
- write_to_stream(stream: IO, encryption_key: Union[None, str, bytes]) \rightarrow None

property xmp_createDate: datetime

property xmp_create_date: Optional[Any]

The date and time the resource was originally created. The date and time are returned as a UTC datetime.datetime object.

property xmp_creatorTool: str

property xmp_creator_tool: Optional[Any]

The name of the first known tool used to create the resource.

property xmp_metadataDate: datetime

property xmp_metadata_date: Optional[Any]

The date and time that any metadata for this resource was last changed.

The date and time are returned as a UTC datetime.datetime object.

property xmp_modifyDate: datetime

property xmp_modify_date: Optional[Any]

The date and time the resource was last modified. The date and time are returned as a UTC datetime.datetime object.

property xmpmm_documentId: str

property xmpmm_document_id: Optional[Any]

The common identifier for all versions and renditions of this resource.

property xmpmm_instanceId: str

property xmpmm_instance_id: Optional[Any]

An identifier for a specific incarnation of a document, updated each time a file is saved.

Note: This page is about PyPDF2. PyPDF2 is deprecated, please use pypdf
TWENTYSEVEN

THE DESTINATION CLASS

class PyPDF2.generic.Destination(title: str, page: Union[NumberObject, IndirectObject, NullObject, DictionaryObject], fit: Fit)

Bases: TreeObject

A class representing a destination within a PDF file. See section 8.2.1 of the PDF 1.6 reference.

Parameters

- **title** (*str*) Title of this destination.
- **page** (*IndirectObject*) Reference to the page of this destination. Should be an instance of IndirectObject.
- **fit** (Fit) How the destination is displayed.

Raises

PdfReadError – If destination type is invalid.

property bottom: Optional[FloatObject]

Read-only property accessing the bottom vertical coordinate.

```
childs: List[Any] = []
```

property color: Optional[ArrayObject]

Read-only property accessing the color in (R, G, B) with values 0.0-1.0

property dest_array: ArrayObject

property font_format: Optional[OutlineFontFlag]

Read-only property accessing the font type. 1=italic, 2=bold, 3=both

getDestArray() \rightarrow ArrayObject

Deprecated since version 1.28.3: Use *dest_array* instead.

property left: Optional[FloatObject]

Read-only property accessing the left horizontal coordinate.

node: Optional[DictionaryObject] = None

property outline_count: Optional[int]

Read-only property accessing the outline count. positive = expanded negative = collapsed absolute value = number of visible descendents at all levels

property page: Optional[int]

Read-only property accessing the destination page number.

property right: Optional[FloatObject]

Read-only property accessing the right horizontal coordinate.

property title: Optional[str]

Read-only property accessing the destination title.

property top: Optional[FloatObject]

Read-only property accessing the top vertical coordinate.

property typ: Optional[str]

Read-only property accessing the destination type.

write_to_stream(*stream*: IO, *encryption_key*: Union[None, *str*, bytes]) \rightarrow None

property zoom: Optional[int]

Read-only property accessing the zoom factor.

Note: This page is about PyPDF2. PyPDF2 is deprecated, please use pypdf

TWENTYEIGHT

THE RECTANGLEOBJECT CLASS

class PyPDF2.generic.RectangleObject(arr: Union[RectangleObject, Tuple[float, float, float, float]])
Bases: ArrayObject

This class is used to represent page boxes in PyPDF2. These boxes include:

- artbox
- bleedbox
- cropbox
- mediabox
- trimbox

property bottom: FloatObject

ensureIsNumber(*value: Any*) → Union[FloatObject, NumberObject]

 $getHeight() \rightarrow Decimal$

 $getLowerLeft() \rightarrow Tuple[Decimal, Decimal]$

 $\texttt{getLowerLeft}_x() \rightarrow FloatObject$

getLowerLeft_y() \rightarrow FloatObject

 $getLowerRight() \rightarrow Tuple[Decimal, Decimal]$

 $\texttt{getLowerRight}_x() \rightarrow FloatObject$

 $\texttt{getLowerRight}_y() \rightarrow FloatObject$

getUpperLeft() \rightarrow Tuple[Decimal, Decimal]

 $getUpperLeft_x() \rightarrow FloatObject$

 $\texttt{getUpperLeft_y}() \rightarrow FloatObject$

 $getUpperRight() \rightarrow Tuple[Decimal, Decimal]$

 $\texttt{getUpperRight}_x() \rightarrow FloatObject$

 $\texttt{getUpperRight}_y() \rightarrow FloatObject$

 $\texttt{getWidth}() \rightarrow \text{Decimal}$

property height: Decimal

property left: FloatObject property lowerLeft: Tuple[Decimal, Decimal] property lowerRight: Tuple[Decimal, Decimal] property lower_left: Tuple[Decimal, Decimal] Property to read and modify the lower left coordinate of this box in (x,y) form. property lower_right: Tuple[Decimal, Decimal] Property to read and modify the lower right coordinate of this box in (x,y) form. property right: FloatObject $scale(sx: float, sy: float) \rightarrow RectangleObject$ **setLowerLeft**(*value: Tuple*[*float, float*]) \rightarrow None **setLowerRight**(*value: Tuple*[float, float]) \rightarrow None $\texttt{setUpperLeft}(\textit{value: Tuple[float, float]}) \rightarrow \texttt{None}$ **setUpperRight**(*value: Tuple[float, float]*) → None property top: FloatObject property upperLeft: Tuple[Decimal, Decimal] property upperRight: Tuple[Decimal, Decimal] property upper_left: Tuple[Decimal, Decimal] Property to read and modify the upper left coordinate of this box in (x,y) form. property upper_right: Tuple[Decimal, Decimal] Property to read and modify the upper right coordinate of this box in (x,y) form. property width: Decimal

Note: This page is about PyPDF2. PyPDF2 is deprecated, please use pypdf

TWENTYNINE

THE FIELD CLASS

class PyPDF2.generic.Field(data: Dict[str, Any])

Bases: TreeObject

A class representing a field dictionary.

This class is accessed through get_fields()

property additionalActions: Optional[DictionaryObject]

Deprecated since version 1.28.3.

Use additional_actions instead.

property additional_actions: Optional[DictionaryObject]

Read-only property accessing the additional actions dictionary. This dictionary defines the field's behavior in response to trigger events. See Section 8.5.2 of the PDF 1.7 reference.

property altName: Optional[str]

Deprecated since version 1.28.3.

Use alternate_name instead.

property alternate_name: Optional[str]

Read-only property accessing the alternate name of this field.

property defaultValue: Optional[Any]

Deprecated since version 1.28.3.

Use default_value instead.

property default_value: Optional[Any]

Read-only property accessing the default value of this field.

property fieldType: Optional[NameObject]

Deprecated since version 1.28.3.

Use *field_type* instead.

property field_type: Optional[NameObject]

Read-only property accessing the type of this field.

property flags: Optional[int]

Read-only property accessing the field flags, specifying various characteristics of the field (see Table 8.70 of the PDF 1.7 reference).

property kids: Optional[ArrayObject]

Read-only property accessing the kids of this field.

property mappingName: Optional[str]

Deprecated since version 1.28.3.

Use mapping_name instead.

property mapping_name: Optional[str]

Read-only property accessing the mapping name of this field. This name is used by PyPDF2 as a key in the dictionary returned by *get_fields()*

property name: Optional[str]

Read-only property accessing the name of this field.

property parent: Optional[DictionaryObject]

Read-only property accessing the parent of this field.

property value: Optional[Any]

Read-only property accessing the value of this field. Format varies based on field type.

Note: This page is about PyPDF2. PyPDF2 is deprecated, please use pypdf

THIRTY

THE PAGERANGE CLASS

class PyPDF2.PageRange(arg: Union[slice, PageRange, str])

Bases: object

A slice-like representation of a range of page indices.

For example, page numbers, only starting at zero.

The syntax is like what you would put between brackets []. The slice is one of the few Python types that can't be subclassed, but this class converts to and from slices, and allows similar use.

- PageRange(str) parses a string representing a page range.
- PageRange(slice) directly "imports" a slice.
- to_slice() gives the equivalent slice.
- str() and repr() allow printing.
- indices(n) is like slice.indices(n).

```
indices(n: int) \rightarrow Tuple[int, int, int]
```

n is the length of the list of pages to choose from.

Returns arguments for range(). See help(slice.indices).

```
\textbf{to\_slice()} \rightarrow slice
```

Return the slice equivalent of this page range.

static valid(*input:* Any) \rightarrow bool

True if input is a valid initializer for a PageRange.

Note: This page is about PyPDF2. PyPDF2 is deprecated, please use pypdf

THIRTYONE

THE ANNOTATIONBUILDER CLASS

class PyPDF2.generic.AnnotationBuilder

Bases: object

The AnnotationBuilder creates dictionaries representing PDF annotations.

Those dictionaries can be modified before they are added to a PdfWriter instance via writer.add_annotation.

See adding PDF annotations for it's usage combined with PdfWriter.

static free_text(*text: str, rect: Union*[RectangleObject, *Tuple*[*float, float, float*]], *font: str* = '*Helvetica', bold: bool* = *False, italic: bool* = *False, font_size: str* = '14pt', *font_color: str* = '000000', *border_color: str* = '000000', *background_color: str* = 'ffffff') \rightarrow DictionaryObject

Add text in a rectangle to a page.

Parameters

- text (str) Text to be added
- **rect** (RectangleObject) or array of four integers specifying the clickable rectangular area [xLL, yLL, xUR, yUR]
- **font** (*str*) Name of the Font, e.g. 'Helvetica'
- **bold** (*bool*) Print the text in bold
- italic (bool) Print the text in italic
- **font_size** (*str*) How big the text will be, e.g. '14pt'
- font_color (str) Hex-string for the color
- **border_color** (*str*) Hex-string for the border color
- **background_color** (*str*) Hex-string for the background of the annotation

static line(p1: Tuple[float, float], p2: Tuple[float, float], rect: Union[RectangleObject, Tuple[float, float, float, float]], text: str = ", title_bar: str = ") → DictionaryObject

Draw a line on the PDF.

Parameters

- p1 (Tuple[float, float]) First point
- p2 (Tuple[float, float]) Second point
- **rect** (RectangleObject) or array of four integers specifying the clickable rectangular area [xLL, yLL, xUR, yUR]
- text (str) Text to be displayed as the line annotation

- **title_bar** (*str*) Text to be displayed in the title bar of the annotation; by convention this is the name of the author
- static link(rect: ~typing.Union[~PyPDF2.generic._rectangle.RectangleObject, ~typing.Tuple[float, float, float, float]], border: ~typing.Optional[~PyPDF2.generic._data_structures.ArrayObject] = None, url: ~typing.Optional[str] = None, target_page_index: ~typing.Optional[int] = None, fit: ~PyPDF2.generic. fit.Fit = <PyPDF2.generic. fit.Fit object>) → DictionaryObject

Add a link to the document.

The link can either be an external link or an internal link.

An external link requires the URL parameter. An internal link requires the target_page_index, fit, and fit args.

Parameters

- **rect** (RectangleObject) or array of four integers specifying the clickable rectangular area [xLL, yLL, xUR, yUR]
- **border** if provided, an array describing border-drawing properties. See the PDF spec for details. No border will be drawn if this argument is omitted. horizontal corner radius, vertical corner radius, and border width Optionally: Dash
- **url** (*str*) Link to a website (if you want to make an external link)
- **target_page_index** (*int*) index of the page to which the link should go (if you want to make an internal link)
- **fit** (Fit) Page fit or 'zoom' option.
- **static rectangle**(*rect: Union*[RectangleObject, *Tuple*[*float, float, float, float*]], *interiour_color:* $Optional[str] = None) \rightarrow DictionaryObject$

Draw a rectangle on the PDF.

Parameters

rect (RectangleObject) – or array of four integers specifying the clickable rectangular area [xLL, yLL, xUR, yUR]

static text(*rect: Union*[RectangleObject, *Tuple*[*float, float, float, float*]], *text: str, open: bool* = *False, flags: int* = 0) \rightarrow DictionaryObject

Add text annotation.

Parameters

- **rect** (*Tuple[int, int, int, int]*) or array of four integers specifying the clickable rectangular area [xLL, yLL, xUR, yUR]
- open (bool) -
- flags (int) -

Note: This page is about PyPDF2. PyPDF2 is deprecated, please use pypdf

THIRTYTWO

THE FIT CLASS

class PyPDF2.generic.**Fit**(*fit_type: str, fit_args: Tuple[Union[None, float, Any], ...]* = ())

Bases: object

classmethod fit() \rightarrow *Fit*

Display the page designated by page, with its contents magnified just enough to fit the entire page within the window both horizontally and vertically. If the required horizontal and vertical magnification factors are different, use the smaller of the two, centering the page within the window in the other dimension.

classmethod fit_box() \rightarrow *Fit*

Display the page designated by page, with its contents magnified just enough to fit its bounding box entirely within the window both horizontally and vertically. If the required horizontal and vertical magnification factors are different, use the smaller of the two, centering the bounding box within the window in the other dimension.

Display the page designated by page , with the vertical coordinate top positioned at the top edge of the window and the contents of the page magnified just enough to fit the entire width of its bounding box within the window.

A null value for top specifies that the current value of that parameter is to be retained unchanged.

classmethod fit_box_vertically(*left: Optional*[*float*] = *None*) \rightarrow *Fit*

Display the page designated by page, with the horizontal coordinate left positioned at the left edge of the window and the contents of the page magnified just enough to fit the entire height of its bounding box within the window.

A null value for left specifies that the current value of that parameter is to be retained unchanged.

Display the page designated by page, with the vertical coordinate top positioned at the top edge of the window and the contents of the page magnified just enough to fit the entire width of the page within the window.

A null value for top specifies that the current value of that parameter is to be retained unchanged.

classmethod fit_rectangle(*left: Optional[float]* = *None, bottom: Optional[float]* = *None, right: Optional[float]* = *None, top: Optional[float]* = *None*) \rightarrow *Fit*

Display the page designated by page, with its contents magnified just enough to fit the rectangle specified by the coordinates left, bottom, right, and top entirely within the window both horizontally and vertically.

If the required horizontal and vertical magnification factors are different, use the smaller of the two, centering the rectangle within the window in the other dimension.

A null value for any of the parameters may result in unpredictable behavior.

classmethod fit_vertically(*left: Optional*[*float*] = *None*) \rightarrow *Fit*

classmethod xyz(*left: Optional[float*] = *None, top: Optional[float*] = *None, zoom: Optional[float*] = *None*) \rightarrow *Fit*

Display the page designated by page, with the coordinates (left, top) positioned at the upper-left corner of the window and the contents of the page magnified by the factor zoom.

A null value for any of the parameters left, top, or zoom specifies that the current value of that parameter is to be retained unchanged.

A zoom value of 0 has the same meaning as a null value.

Note: This page is about PyPDF2. PyPDF2 is deprecated, please use pypdf

THIRTYTHREE

THE PAPERSIZE CLASS

class PyPDF2.PaperSize

Bases: object

(width, height) of the paper in portrait mode in pixels at 72 ppi.

A0 = Dimensions(width=2384, height=3370)

- A1 = Dimensions(width=1684, height=2384)
- A2 = Dimensions(width=1191, height=1684)
- A3 = Dimensions(width=842, height=1191)
- A4 = Dimensions(width=595, height=842)
- A5 = Dimensions(width=420, height=595)
- A6 = Dimensions(width=298, height=420)
- A7 = Dimensions(width=210, height=298)
- A8 = Dimensions(width=147, height=210)
- C4 = Dimensions(width=649, height=918)

CHAPTER THIRTYFOUR

DEVELOPER INTRO

PyPDF2 is a library and hence its users are developers. This document is not for the users, but for people who want to work on PyPDF2 itself.

34.1 Installing Requirements

pip install -r requirements/dev.txt

34.2 Running Tests

See testing PyPDF2 with pytest

34.3 The sample-files git submodule

The reason for having the submodule sample-files is that we want to keep the size of the PyPDF2 repository small while we also want to have an extensive test suite. Those two goals contradict each other.

The resources folder should contain a select set of core examples that cover most cases we typically want to test for. The sample-files might cover a lot more edge cases, the behavior we get when file sizes get bigger, different PDF producers.

In order to get the sample-files folder, you need to execute:

git submodule update --init

34.4 Tools: git and pre-commit

Git is a command line application for version control. If you don't know it, you can play ohmygit to learn it.

GitHub is the service where the PyPDF2 project is hosted. While git is free and open source, GitHub is a paid service by Microsoft - but for free in lot of cases.

pre-commit is a command line application that uses git hooks to automatically execute code. This allows you to avoid style issues and other code quality issues. After you entered pre-commit install once in your local copy of PyPDF2, it will automatically be executed when you git commit.

34.5 Commit Messages

Having a clean commit message helps people to quickly understand what the commit was about, without actually looking at the changes. The first line of the commit message is used to auto-generate the CHANGELOG. For this reason, the format should be:

PREFIX: DESCRIPTION

BODY

The PREFIX can be:

- BUG: A bug was fixed. Likely there is one or multiple issues. Then write in the BODY: Closes #123 where 123 is the issue number on GitHub. It would be absolutely amazing if you could write a regression test in those cases. That is a test that would fail without the fix.
- ENH: A new feature! Describe in the body what it can be used for.
- DEP: A deprecation either marking something as "this is going to be removed" or actually removing it.
- PI: A performance improvement. This could also be a reduction in the file size of PDF files generated by PyPDF2.
- ROB: A robustness change. Dealing better with broken PDF files.
- DOC: A documentation change.
- TST: Adding / adjusting tests.
- DEV: Developer experience improvements e.g. pre-commit or setting up CI
- MAINT: Quite a lot of different stuff. Performance improvements are for sure the most interesting changes in here. Refactorings as well.
- STY: A style change. Something that makes PyPDF2 code more consistent. Typically a small change.

34.6 Benchmarks

We need to keep an eye on performance and thus we have a few benchmarks.

See py-pdf.github.io/PyPDF2/dev/bench

THIRTYFIVE

THE PDF FORMAT

It's recommended to look in the PDF specification for details and clarifications. This is only intended to give a very rough overview of the format.

35.1 Overall Structure

A PDF consists of:

- 1. Header: Contains the version of the PDF, e.g. %PDF-1.7
- 2. Body: Contains a sequence of indirect objects
- 3. Cross-reference table (xref): Contains a list of the indirect objects in the body
- 4. Trailer

35.2 The xref table

A cross-reference table (xref) is a table of the indirect objects in the body. It allows quick access to those objects by pointing to their location in the file.

It looks like this:

xref 42 5 0000001000 65535 f 0000001234 00000 n 0000001987 00000 n 0000011987 00000 n

Let's go through it step-by-step:

- xref is just a keyword that specifies the start of the xref table.
- 42 is the numerical ID of the first object in this xref section; 5 is the number of entries in the xref table.
- Now every object has 3 entries nnnnnnnn ggggg n: The 10-digit byte offset, a 5-digit generation number, and a literal keyword which is either n or f.
 - nnnnnnnn is the byte offset of the object. It tells the reader where the object is in the file.
 - ggggg is the generation number. It tells the reader how old the object is.
 - n means that the object is a normal in-use object, f means that the object is a free object.

- * The first free object always has a generation number of 65535. It forms the head of a linked-list of all free objects.
- * The generation number of a normal object is always 0. The generation number allows the PDF format to contain multiple versions of the same object. This is a version history mechanism.

35.3 The body

The body is a sequence of indirect objects:

counter generationnumber << the_object >> endobj

- counter (integer) is a unique identifier for the object.
- generationnumber (integer) is the generation number of the object.
- the_object is the object itself. It can be empty. Starts with /Keyword to specify which kind of object it is.
- endobj marks the end of the object.

A concrete example can be found in test_reader.py::test_get_images_raw:

```
1 0 obj << /Count 1 /Kids [4 0 R] /Type /Pages >> endobj
2 0 obj << >> endobj
3 0 obj << >> endobj
4 0 obj << /Contents 3 0 R /CropBox [0.0 0.0 2550.0 3508.0]
/MediaBox [0.0 0.0 2550.0 3508.0] /Parent 1 0 R
/Resources << /Font << >> >>
/Rotate 0 /Type /Page >> endobj
5 0 obj << /Pages 1 0 R /Type /Catalog >> endobj
```

35.4 The trailer

The trailer looks like this:

```
trailer << /Root 5 0 R
            /Size 6
            >>
startxref 1234
%%EOF
```

Let's go through it:

- trailer << indicates that the *trailer dictionary* starts. It ends with >>.
- startxref is a keyword followed by the byte-location of the xref keyword. As the trailer is always at the bottom of the file, this allows readers to quickly find the xref table.
- %%EOF is the end-of-file marker.

The trailer dictionary is a key-value list. The keys are specified in Table 3.13 of the PDF Reference 1.7, e.g. /Root and /Size (both are required).

- /Root (dictionary) contains the document catalog.
 - The 5 is the object number of the catalog dictionary

- 0 is the generation number of the catalog dictionary
- R is the keyword that indicates that the object is a reference to the catalog dictionary.
- /Size (integer) contains the total number of entries in the files xref table.

35.5 Reading PDF files

Most PDF files are compressed. If you want to read them, first uncompress them:

pdftk crazyones.pdf output crazyones-uncomp.pdf uncompress

Then rename crazyones-uncomp.pdf to crazyones-uncomp.txt and open it in our favorite IDE / text editor.

THIRTYSIX

CMAPS

Looking at the cmap of "crazyones":

pdftk crazyones.pdf output crazyones-uncomp.pdf uncompress

You can see this:

begincmap /CMapName /T1Encoding-UTF16 def /CMapType 2 def /CIDSystemInfo <<</pre> /Registry (Adobe) /Ordering (UCS) /Supplement 0 >> def 1 begincodespacerange <00> <FF> endcodespacerange 1 beginbfchar <1B> <FB00> endbfchar endcmap CMapName currentdict /CMap defineresource pop

36.1 codespacerange

A codespacerange maps a complete sequence of bytes to a range of unicode glyphs. It defines a starting point:

1 beginbfchar <1B> <FB00>

That means that 1B (Hex for 27) maps to the unicode character FB00 - the ligature ff (two lowercase f's).

The two numbers in begincodespacerange mean that it starts with an offset of 0 (hence from 1B FB00) upt to an offset of FF (dec: 255), hence 1B+FF = 282 FBFF.

Within the text stream, there is

(The)-342(mis\034ts.)

034 is octal for 28 decimal.

THIRTYSEVEN

THE DEPRECATION PROCESS

PyPDF2 strives to be an excellent library for its current users and for new ones. We are careful with introducing potentially breaking changes, but we will do them if they provide value for the community on the long run.

We hope and think that deprecations will not happen soon again. If they do, users can rely on the following procedure.

37.1 Semantic Versioning

PyPDF2 uses semantic versioning. If you want to avoid breaking changes, please use dependency pinning (also known as version pinning). In Python, this is done by specifying the exact version you want to use in a requirements.txt file. A tool that can support you is pip-compile from pip-tools.

If you are using Poetry it is done with the poetry.lock file.

37.2 How PyPDF2 deprecates features

Assume the current version of PyPDF2 is x.y.z. After a discussion (e.g. via GitHub issues) we decided to remove a class / function / method. This is how we do it:

- 1. x.y.(z+1): Add a DeprecationWarning. If there is a replacement, the replacement is also introduced and the warning informs about the change and when it will happen. The docs let users know about the deprecation and when it will happen and the new function. The CHANGELOG informs about it.
- 2. (x+1).0.0: Remove / change the code in the breaking way by replacing DeprecationWarnings by Deprecation-Errors. We do this to help people who didn't look at the warnings before. The CHANGELOG informs about it.
- 3. (x+2).0.0: The DeprecationErrors are removed.

This means the users have 3 warnings in the CHANGELOG, a DeprecationWarning until the next major release and a DeprecationError until the major release after that.

Please note that adding warnings can be a breaking change for some users; most likely just in the CI. This means it needs to be properly documented.

THIRTYEIGHT

TESTING

PyPDF2 uses pytest for testing.

38.1 De-selecting groups of tests

PyPDF2 makes use of the following pytest markers:

- slow: Tests that require more than 5 seconds
- samples: Tests that require the the sample-files git submodule to be initialized. As of October 2022, this is about 25 MB.
- external: Tests that download PDF documents. They are stored locally and thus only need to be downloaded once. As of October 2022, this is about 200 MB.

You can disable them by pytest -m "not external" or pytest -m "not samples". You can even disable all of them: pytest -m "not external" -m "not samples" -m "not slow".

Please note that this reduces test coverage. The CI will always test all files.

38.2 Creating a Coverage Report

If you want to get a coverage report that considers the Python version specific code, you can run tox.

As a prerequisite, we recommend using pyenv so that you can install the different Python versions:

```
pyenv install pypy3.8-7.3.7
pyenv install 3.6.15
pyenv install 3.7.12
pyenv install 3.8.12
pyenv install 3.9.10
pyenv install 3.10.2
```

Then you can execute tox which will create a coverage report in HTML form in the end. The execution takes about 30 minutes.

THIRTYNINE

CHANGELOG

39.1 Version 3.0.0, 2022-12-22

39.1.1 BREAKING CHANGES

- Deprecate features with PyPDF2==3.0.0 (#1489)
- Refactor Fit / Zoom parameters (#1437)

39.1.2 New Features (ENH)

- Add Cloning (#1371)
- Allow int for indirect_reference in PdfWriter.get_object (#1490)

39.1.3 Documentation (DOC)

- How to read PDFs from S3 (#1509)
- Make MyST parse all links as simple hyperlinks (#1506)
- Changed 'latest' for 'stable' generated docs (#1495)
- Adjust deprecation procedure (#1487)

39.1.4 Maintenance (MAINT)

• Use typing.IO for file streams (#1498)

Full Changelog

39.2 Version 2.12.1, 2022-12-10

39.2.1 Documentation (DOC)

- Deduplicate extract_text docstring (#1485)
- How to cite PyPDF2 (#1476)

39.2.2 Maintenance (MAINT)

Consistency changes:

- indirect_ref/ido indirect_reference, dest page_destination (#1467)
- owner_pwd/user_pwd owner_password/user_password (#1483)
- position page_number in Merger.merge (#1482)
- indirect_ref indirect_reference (#1484)

Full Changelog

39.3 Version 2.12.0, 2022-12-10

39.3.1 New Features (ENH)

- Add support to extract gray scale images (#1460)
- Add 'threads' property to PdfWriter (#1458)
- Add 'open_destination' property to PdfWriter (#1431)
- Make PdfReader.get_object accept integer arguments (#1459)

39.3.2 Bug Fixes (BUG)

• Scale PDF annotations (#1479)

39.3.3 Robustness (ROB)

- Padding issue with AES encryption (#1469)
- Accept empty object as null objects (#1477)

39.3.4 Documentation (DOC)

• Add module documentation the PaperSize class (#1447)

39.3.5 Maintenance (MAINT)

- Use 'page_number' instead of 'pagenum' (#1365)
- Add List of pages to PageRangeSpec (#1456)

39.3.6 Testing (TST)

- Cleanup temporary files (#1454)
- Mark test_tounicode_is_identity as external (#1449)
- Use Ubuntu 20.04 for running CI test suite (#1452)

Full Changelog

39.4 Version 2.11.2, 2022-11-20

39.4.1 New Features (ENH)

- Add remove_from_tree (#1432)
- Add AnnotationBuilder.rectangle (#1388)

39.4.2 Bug Fixes (BUG)

- JavaScript executed twice (#1439)
- ToUnicode stores /Identity-H instead of stream (#1433)
- Declare Pillow as optional dependency (#1392)

39.4.3 Developer Experience (DEV)

- Link 'Full Changelog' automatically
- Modify read_string_from_stream to a benchmark (#1415)
- Improve error reporting of read_object (#1412)
- Test Python 3.11 (#1404)
- Extend Flake8 ignore list (#1410)
- Use correct pytest markers (#1407)
- Move project configuration to pyproject.toml (#1382)

Full Changelog

39.5 Version 2.11.1, 2022-10-09

39.5.1 Bug Fixes (BUG)

- td matrix (#1373)
- Cope with cmap from #1322 (#1372)

39.5.2 Robustness (ROB)

• Cope with str returned from get_data in cmap (#1380)

Full Changelog

39.6 Version 2.11.0, 2022-09-25

39.6.1 New Features (ENH)

- Addition of optional visitor-functions in extract_text() (#1252)
- Add metadata.creation_date and modification_date (#1364)
- Add PageObject.images attribute (#1330)

39.6.2 Bug Fixes (BUG)

- Lookup index in _xobj_to_image can be ByteStringObject (#1366)
- 'IndexError: index out of range' when using extract_text (#1361)
- Errors in transfer_rotation_to_content() (#1356)

39.6.3 Robustness (ROB)

• Ensure update_page_form_field_values does not fail if no fields (#1346)

Full Changelog

39.7 Version 2.10.9, 2022-09-18

39.7.1 New Features (ENH)

• Add rotation property and transfer_rotate_to_content (#1348)

39.7.2 Performance Improvements (PI)

• Avoid string concatenation with large embedded base64-encoded images (#1350)

39.7.3 Bug Fixes (BUG)

• Format floats using their intrinsic decimal precision (#1267)

39.7.4 Robustness (ROB)

• Fix merge_page for pages without resources (#1349)

Full Changelog

39.8 Version 2.10.8, 2022-09-14

39.8.1 New Features (ENH)

• Add PageObject.user_unit property (#1336)

39.8.2 Robustness (ROB)

• Improve NameObject reading/writing (#1345)

Full Changelog

39.9 Version 2.10.7, 2022-09-11

39.9.1 Bug Fixes (BUG)

- Fix Error in transformations (#1341)
- Decode #23 in NameObject (#1342)

39.9.2 Testing (TST)

• Use pytest.warns() for warnings, and .raises() for exceptions (#1325)

Full Changelog

39.10 Version 2.10.6, 2022-09-09

39.10.1 Robustness (ROB)

- Fix infinite loop due to Invalid object (#1331)
- Fix image extraction issue with superfluous whitespaces (#1327)

Full Changelog

39.11 Version 2.10.5, 2022-09-04

39.11.1 New Features (ENH)

- Process XRefStm (#1297)
- Auto-detect RTL for text extraction (#1309)

39.11.2 Bug Fixes (BUG)

• Avoid scaling cropbox twice (#1314)

39.11.3 Robustness (ROB)

- Fix offset correction in revised PDF (#1318)
- Crop data of /U and /O in encryption dictionary to 48 bytes (#1317)
- MultiLine bfrange in cmap (#1299)
- Cope with 2 digit codes in bfchar (#1310)
- Accept '/annn' charset as ASCII code (#1316)
- Log errors during Float / NumberObject initialization (#1315)
- Cope with corrupted entries in xref table (#1300)

39.11.4 Documentation (DOC)

- Migration guide (PyPDF2 1.x 2.x) (#1324)
- Creating a coverage report (#1319)
- Fix AnnotationBuilder.free_text example (#1311)
- Fix usage of page.scale by replacing it with page.scale_by (#1313)

39.11.5 Maintenance (MAINT)

- PdfReaderProtocol (#1303)
- Throw PdfReadError if Trailer can't be read (#1298)
- Remove catching OverflowException (#1302)

Full Changelog

39.12 Version 2.10.4, 2022-08-28

39.12.1 Robustness (ROB)

- Fix errors/warnings on no /Resources within extract_text (#1276)
- Add required line separators in ContentStream ArrayObjects (#1281)

39.12.2 Maintenance (MAINT)

• Use NameObject idempotency (#1290)

39.12.3 Testing (TST)

- Rectangle deletion (#1289)
- Add workflow tests (#1287)
- Remove files after tests ran (#1286)

39.12.4 Packaging (PKG)

• Add minimum version for typing_extensions requirement (#1277)

Full Changelog

39.13 Version 2.10.3, 2022-08-21

39.13.1 Robustness (ROB)

• Decrypt returns empty bytestring (#1258)

39.13.2 Developer Experience (DEV)

• Modify CI to better verify built package contents (#1244)

39.13.3 Maintenance (MAINT)

- Remove 'mine' as PdfMerger always creates the stream (#1261)
- Let PdfMerger._create_stream raise NotImplemented (#1251)
- password param of _security._alg32(...) is only a string, not bytes (#1259)
- Remove unreachable code in read_block_backwards (#1250) and sign function in _extract_text (#1262)

39.13.4 Testing (TST)

- Delete annotations (#1263)
- Close PdfMerger in tests (#1260)
- PdfReader.xmp_metadata workflow (#1257)
- Various PdfWriter (Layout, Bookmark deprecation) (#1249)

Full Changelog

39.14 Version 2.10.2, 2022-08-15

BUG: Add PyPDF2.generic to PyPI distribution

39.15 Version 2.10.1, 2022-08-15

39.15.1 Bug Fixes (BUG)

- TreeObject.remove_child had a non-PdfObject assignment for Count (#1233, #1234)
- Fix stream truncated prematurely (#1223)

39.15.2 Documentation (DOC)

• Fix docstring formatting (#1228)

39.15.3 Maintenance (MAINT)

• Split generic.py (#1229)

39.15.4 Testing (TST)

- Decrypt AlgV4 with owner password (#1239)
- AlgV5.generate_values (#1238)
- TreeObject.remove_child / empty_tree (#1235, #1236)
- create_string_object (#1232)
- Free-Text annotations (#1231)
- generic._base (#1230)
- Strict get fonts (#1226)
- Increase PdfReader coverage (#1219, #1225)
- Increase PdfWriter coverage (#1237)
- 100% coverage for utils.py (#1217)
- PdfWriter exception non-binary stream (#1218)
- Don't check coverage for deprecated code (#1216)

Full Changelog

39.16 Version 2.10.0, 2022-08-07

39.16.1 New Features (ENH)

- "with" support for PdfMerger and PdfWriter (#1193)
- Add AnnotationBuilder.text(...) to build text annotations (#1202)

39.16.2 Bug Fixes (BUG)

• Allow IndirectObjects as stream filters (#1211)

39.16.3 Documentation (DOC)

- Font scrambling
- Page vs Content scaling (#1208)
- Example for orientation parameter of extract_text (#1206)
- Fix AnnotationBuilder parameter formatting (#1204)

39.16.4 Developer Experience (DEV)

• Add flake8-print (#1203)

39.16.5 Maintenance (MAINT)

• Introduce WrongPasswordError / FileNotDecryptedError / EmptyFileError (#1201)

Full Changelog

39.17 Version 2.9.0, 2022-07-31

39.17.1 New Features (ENH)

- Add ability to add hex encoded colors to outline items (#1186)
- Add support for pathlib.Path in PdfMerger.merge (#1190)
- Add link annotation (#1189)
- Add capability to filter text extraction by orientation (#1175)

39.17.2 Bug Fixes (BUG)

- Named Dest in PDF1.1 (#1174)
- Incomplete Graphic State save/restore (#1172)

39.17.3 Documentation (DOC)

- Update changelog url in package metadata (#1180)
- Mantion camelot for table extraction (#1179)
- Mention pyHanko for signing PDF documents (#1178)
- Weow have CMAP support since a while (#1177)

39.17.4 Maintenance (MAINT)

- Consistant usage of warnings / log messages (#1164)
- Consistent terminology for outline items (#1156)

Full Changelog
39.18 Version 2.8.1, 2022-07-25

39.18.1 Bug Fixes (BUG)

• u_hash in AlgV4.compute_key (#1170)

39.18.2 Robustness (ROB)

- Fix loading of file from #134 (#1167)
- Cope with empty DecodeParams (#1165)

39.18.3 Documentation (DOC)

• Typo in merger deprecation warning message (#1166)

39.18.4 Maintenance (MAINT)

• Package updates; solve mypy strict remarks (#1163)

39.18.5 Testing (TST)

• Add test from #325 (#1169)

Full Changelog

39.19 Version 2.8.0, 2022-07-24

39.19.1 New Features (ENH)

• Add writer.add_annotation, page.annotations, and generic.AnnotationBuilder (#1120)

39.19.2 Bug Fixes (BUG)

- Set /AS for /Btn form fields in writer (#1161)
- Ignore if /Perms verify failed (#1157)

39.19.3 Robustness (ROB)

- Cope with utf16 character for space calculation (#1155)
- Cope with null params for FitH / FitV destination (#1152)
- Handle outlines without valid destination (#1076)

39.19.4 Developer Experience (DEV)

• Introduce _utils.logger_warning (#1148)

39.19.5 Maintenance (MAINT)

- Break up parse_to_unicode (#1162)
- Add diagnostic output to exception in read_from_stream (#1159)
- Reduce PdfReader.read complexity (#1151)

39.19.6 Testing (TST)

- Add workflow tests found by arc testing (#1154)
- Decrypt file which is not encrypted (#1149)
- Test CryptRC4 encryption class; test image extraction filters (#1147)

Full Changelog

39.20 Version 2.7.0, 2022-07-21

39.20.1 New Features (ENH)

• Add outline_count property (#1129)

39.20.2 Bug Fixes (BUG)

- Make reader.get_fields also return dropdowns with options (#1114)
- Add deprecated EncodedStreamObject functions back until PyPDF2==3.0.0 (#1139)

39.20.3 Robustness (ROB)

- Cope with missing /W entry (#1136)
- Cope with invalid parent xref (#1133)

39.20.4 Documentation (DOC)

- Contributors file (#1132)
- Fix type in signature of PdfWriter.add_uri (#1131)

39.20.5 Developer Experience (DEV)

• Add .git-blame-ignore-revs (#1141)

39.20.6 Code Style (STY)

- Fixing typos (#1137)
- Re-use code via get_outlines_property in tests (#1130)

Full Changelog

39.21 Version 2.6.0, 2022-07-17

39.21.1 New Features (ENH)

- Add color and font_format to PdfReader.outlines[i] (#1104)
- Extract Text Enhancement (whitespaces) (#1084)

39.21.2 Bug Fixes (BUG)

- Use build_destination for named destination outlines (#1128)
- Avoid a crash when a ToUnicode CMap has an empty dstString in beginbfchar (#1118)
- Prevent deduplication of PageObject (#1105)
- None-check in DictionaryObject.read_from_stream (#1113)
- Avoid IndexError in _cmap.parse_to_unicode (#1110)

39.21.3 Documentation (DOC)

- Explanation for git submodule
- Watermark and stamp (#1095)

39.21.4 Maintenance (MAINT)

- Text extraction improvements (#1126)
- Destination.color returns ArrayObject instead of tuple as fallback (#1119)
- Use add_bookmark_destination in add_bookmark (#1100)
- Use add_bookmark_destination in add_bookmark_dict (#1099)

39.21.5 Testing (TST)

- Add test for arab text (#1127)
- Add xfail for decryption fail (#1125)
- Add xfail test for IndexError when extracting text (#1124)
- Add MCVE showing outline title issue (#1123)

39.21.6 Code Style (STY)

- Use IntFlag for permissions_flag / update_page_form_field_values (#1094)
- Simplify code (#1101)

Full Changelog

39.22 Version 2.5.0, 2022-07-10

39.22.1 New Features (ENH)

- Add support for indexed color spaces / BitsPerComponent for decoding PNGs (#1067)
- Add PageObject._get_fonts (#1083)

39.22.2 Performance Improvements (PI)

• Use iterative DFS in PdfWriter._sweep_indirect_references (#1072)

39.22.3 Bug Fixes (BUG)

- Let Page.scale also scale the crop-/trim-/bleed-/artbox (#1066)
- Column default for CCITTFaxDecode (#1079)

39.22.4 Robustness (ROB)

• Guard against None-value in _get_outlines (#1060)

39.22.5 Documentation (DOC)

- Stamps and watermarks (#1082)
- OCR vs PDF text extraction (#1081)
- Python Version support
- Formatting of CHANGELOG

39.22.6 Developer Experience (DEV)

- Cache downloaded files (#1070)
- Speed-up for CI (#1069)

39.22.7 Maintenance (MAINT)

- Set page.rotate(angle: int) (#1092)
- Issue #416 was fixed by #1015 (#1078)

39.22.8 Testing (TST)

- Image extraction (#1080)
- Image extraction (#1077)

39.22.9 Code Style (STY)

- Apply black
- Typo in Changelog

Full Changelog

39.23 Version 2.4.2, 2022-07-05

39.23.1 New Features (ENH)

• Add PdfReader.xfa attribute (#1026)

39.23.2 Bug Fixes (BUG)

- Wrong page inserted when PdfMerger.merge is done (#1063)
- Resolve IndirectObject when it refers to a free entry (#1054)

39.23.3 Developer Experience (DEV)

• Added {posargs} to tox.ini (#1055)

39.23.4 Maintenance (MAINT)

• Remove PyPDF2._utils.bytes_type (#1053)

39.23.5 Testing (TST)

- Scale page (indirect rect object) (#1057)
- Simplify pathlib PdfReader test (#1056)
- IndexError of VirtualList (#1052)
- Invalid XML in xmp information (#1051)
- No pycryptodome (#1050)
- Increase test coverage (#1045)

39.23.6 Code Style (STY)

- DOC of compress_content_streams (#1061)
- Minimize diff for #879 (#1049)

Full Changelog

39.24 Version 2.4.1, 2022-06-30

39.24.1 New Features (ENH)

• Add writer.pdf_header property (getter and setter) (#1038)

39.24.2 Performance Improvements (PI)

- Remove b_ call in FloatObject.write_to_stream (#1044)
- Check duplicate objects in writer._sweep_indirect_references (#207)

39.24.3 Documentation (DOC)

- How to surppress exceptions/warnings/log messages (#1037)
- Remove hyphen from lossless (#1041)
- Compression of content streams (#1040)
- Fix inconsistent variable names in add-watermark.md (#1039)
- File size reduction
- Add CHANGELOG to the rendered docs (#1023)

39.24.4 Maintenance (MAINT)

- Handle XML error when reading XmpInformation (#1030)
- Deduplicate Code / add mutmut config (#1022)

39.24.5 Code Style (STY)

- Use unnecessary one-line function / class attribute (#1043)
- Docstring formatting (#1033)

Full Changelog

39.25 Version 2.4.0, 2022-06-26

39.25.1 New Features (ENH):

- Support R6 decrypting (#1015)
- Add PdfReader.pdf_header (#1013)

39.25.2 Performance Improvements (PI):

• Remove ord_ calls (#1014)

39.25.3 Bug Fixes (BUG):

• Fix missing page for bookmark (#1016)

39.25.4 Robustness (ROB):

• Deal with invalid Destinations (#1028)

39.25.5 Documentation (DOC):

- get_form_text_fields does not extract dropdown data (#1029)
- Adjust PdfWriter.add_uri docstring
- Mention crypto extra_requires for installation (#1017)

39.25.6 Developer Experience (DEV):

- Use /n line endings everywhere (#1027)
- Adjust string formatting to be able to use mutmut (#1020)
- Update Bug report template

Full Changelog

39.26 Version 2.3.1, 2022-06-19

BUG: Forgot to add the interal _codecs subpackage.

Full Changelog

39.27 Version 2.3.0, 2022-06-19

The highlight of this release is improved support for file encryption (AES-128 and AES-256, R5 only). See #749 for the amazing work of @exiledkingcc Thank you

39.27.1 Deprecations (DEP)

- Rename names to be PEP8-compliant (#967)
- PdfWriter.get_page: the pageNumber parameter is renamed to page_number
- PyPDF2.filters:
 - For all classes, a parameter rename: decodeParms decode_parms
 - decodeStreamData decode_stream_data
- PyPDF2.xmp:
 - XmpInformation.rdfRoot XmpInformation.rdf_root
 - XmpInformation.xmp_createDate XmpInformation.xmp_create_date
 - XmpInformation.xmp_creatorTool XmpInformation.xmp_creator_tool
 - XmpInformation.xmp_metadataDate XmpInformation.xmp_metadata_date
 - XmpInformation.xmp_modifyDate XmpInformation.xmp_modify_date

- XmpInformation.xmpMetadata XmpInformation.xmp_metadata
- XmpInformation.xmpmm_documentId XmpInformation.xmpmm_document_id
- XmpInformation.xmpmm_instanceId XmpInformation.xmpmm_instance_id
- PyPDF2.generic:
 - readHexStringFromStream read_hex_string_from_stream
 - initializeFromDictionary initialize_from_dictionary
 - createStringObject create_string_object
 - TreeObject.hasChildren TreeObject.has_children
 - TreeObject.emptyTree TreeObject.empty_tree

39.27.2 New Features (ENH)

• Add decrypt support for V5 and AES-128, AES-256 (R5 only) (#749)

39.27.3 Robustness (ROB)

• Fix corrupted (wrongly) linear PDF (#1008)

39.27.4 Maintenance (MAINT)

- · Move PDF_Samples folder into ressources
- Fix typos (#1007)

39.27.5 Testing (TST)

- Improve encryption/decryption test (#1009)
- Add merger test cases with real PDFs (#1006)
- Add mutmut config

39.27.6 Code Style (STY)

- Put pure data mappings in separate files (#1005)
- Make encryption module private, apply pre-commit (#1010)

Full Changelog

39.28 Version 2.2.1, 2022-06-17

39.28.1 Performance Improvements (PI)

- Remove b_ calls (#992, #986)
- Apply improvements to _utils suggested by perflint (#993)

39.28.2 Robustness (ROB)

• utf-16-be codec can't decode (...) (#995)

39.28.3 Documentation (DOC)

• Remove reference to Scripts (#987)

39.28.4 Developer Experience (DEV)

• Fix type annotations for add_bookmarks (#1000)

39.28.5 Testing (TST)

- Add test for PdfMerger (#1001)
- Add tests for XMP information (#996)
- reader.get_fields / zlib issue / LZW decode issue (#1004)
- reader.get_fields with report generation (#1002)
- Improve test coverage by extracting texts (#998)

39.28.6 Code Style (STY)

• Apply fixes suggested by pylint (#999)

Full Changelog

39.29 Version 2.2.0, 2022-06-13

The 2.2.0 release improves text extraction again via (#969):

- Improvements around /Encoding / /ToUnicode
- Extraction of CMaps improved
- Fallback for font def missing
- Support for /Identity-H and /Identity-V: utf-16-be
- Support for /GB-EUC-H / /GB-EUC-V / GBp/c-EUC-H / /GBpc-EUC-V (beta release for evaluation)
- Arabic (for evaluation)

• Whitespace extraction improvements

Those changes should mainly improve the text extraction for non-ASCII alphabets, e.g. Russian / Chinese / Japanese / Korean / Arabic.

Full Changelog

39.30 Version 2.1.1, 2022-06-12

39.30.1 New Features (ENH)

• Add support for pathlib as input for PdfReader (#979)

39.30.2 Performance Improvements (PI)

• Optimize read_next_end_line (#646)

39.30.3 Bug Fixes (BUG)

• Adobe Acrobat 'Would you like to save this file?' (#970)

39.30.4 Documentation (DOC)

- Notes on annotations (#982)
- Who uses PyPDF2
- intendet \xe2\x9e\x94 in robustness page (#958)

39.30.5 Maintenance (MAINT)

- pre-commit / requirements.txt updates (#977)
- Mark read_next_end_line as deprecated (#965)
- Export PageObject in PyPDF2 root (#960)

39.30.6 Testing (TST)

- Add MCVE of issue #416 (#980)
- FlateDecode.decode decodeParms (#964)
- Xmp module (#962)
- utils.paeth_predictor (#959)

39.30.7 Code Style (STY)

• Use more tuples and list/dict comprehensions (#976)

Full Changelog

39.31 Version 2.1.0, 2022-06-06

The highlight of the 2.1.0 release is the most massive improvement to the text extraction capabilities of PyPDF2 since 2016 A very big thank you goes to pubpub-zz who took a lot of time and knowledge about the PDF format to finally get those improvements into PyPDF2. Thank you

In case the new function causes any issues, you can use _extract_text_old for the old functionality. Please also open a bug ticket in that case.

There were several people who have attempted to bring similar improvements to PyPDF2. All of those were valuable. The main reason why they didn't get merged is the big amount of open PRs / issues. pubpub-zz was the most comprehensive PR which also incorporated the latest changes of PyPDF2 2.0.0.

Thank you to VictorCarlquist for #858 and asabramo for #464

39.31.1 New Features (ENH)

- Massive text extraction improvement (#924). Closed many open issues:
 - Exceptions / missing spaces in extract_text() method (#17)
 - * Whitespace issues in extract_text() (#42)
 - * pypdf2 reads the hifenated words in a new line (#246)
 - PyPDF2 failing to read unicode character (#37)
 - * Unable to read bullets (#230)
 - ExtractText yields nothing for apparently good PDF (#168)
 - Encoding issue in extract_text() (#235)
 - extractText() doesn't work on Chinese PDF (#252)
 - encoding error (#260)
 - Trouble with apostophes in names in text "O'Doul" (#384)
 - extract_text works for some PDF files, but not the others (#437)
 - Euro sign not being recognized by extractText (#443)
 - Failed extracting text from French texts (#524)
 - extract_text doesn't extract ligatures correctly (#598)
 - reading spanish text mark convert issue (#635)
 - Read PDF changed from text to random symbols (#654)
 - .extractText() reads / as 1. (#789)
- Update glyphlist (#947) inspired by #464
- Allow adding PageRange objects (#948)

39.31.2 Bug Fixes (BUG)

- Delete .python-version file (#944)
- Compare StreamObject.decoded_self with None (#931)

39.31.3 Robustness (ROB)

• Fix some conversion errors on non conform PDF (#932)

39.31.4 Documentation (DOC)

- Elaborate on PDF text extraction difficulties (#939)
- Add logo (#942)
- rotate vs Transformation().rotate (#937)
- Example how to use PyPDF2 with AWS S3 (#938)
- How to deprecate (#930)
- Fix typos on robustness page (#935)
- Remove scripts (pdfcat) from docs (#934)

39.31.5 Developer Experience (DEV)

- Ignore .python-version file
- Mark deprecated code with no-cover (#943)
- Automatically create Github releases from tags (#870)

39.31.6 Testing (TST)

- Text extraction for non-latin alphabets (#954)
- Ignore PdfReadWarning in benchmark (#949)
- writer.remove_text (#946)
- Add test for Tree and _security (#945)

39.31.7 Code Style (STY)

• black, isort, Flake8, splitting buildCharMap (#950)

Full Changelog

39.32 Version 2.0.0, 2022-06-01

The 2.0.0 release of PyPDF2 includes three core changes:

- 1. Dropping support for Python 3.5 and older.
- 2. Introducing type annotations.
- 3. Interface changes, mostly to have PEP8-compliant names

We introduced a deprecation process that hopefully helps users to avoid unexpected breaking changes.

39.32.1 Breaking Changes (DEP)

- PyPDF2 2.0 requires Python 3.6+. Python 2.7 and 3.5 support were dropped.
- PdfFileReader: The "warndest" parameter was removed
- PdfFileReader and PdfFileMerger no longer have the overwriteWarnings parameter. The new behavior is overwriteWarnings=False.
- merger: OutlinesObject was removed without replacement.
- merger.py _merger.py: You must import PdfFileMerger from PyPDF2 directly.
- utils:
 - ConvertFunctionsToVirtualList was removed
 - formatWarning was removed
 - isInt(obj): Use instance(obj, int) instead
 - u_(s): Use s directly
 - chr_(c): Use chr(c) instead
 - barray(b): Use bytearray(b) instead
 - isBytes(b): Use instance(b, type(bytes())) instead
 - xrange_fn: Use range instead
 - string_type: Use str instead
 - isString(s): Use instance(s, str) instead
 - _basestring: Use str instead
 - All Exceptions are now in PyPDF2.errors:
 - * PageSizeNotDefinedError
 - * PdfReadError
 - * PdfReadWarning
 - * PyPdfError
- PyPDF2.pdf (the pdf module) no longer exists. The contents were moved with the library. You should most likely import directly from PyPDF2 instead. The RectangleObject is in PyPDF2.generic.
- The Resources, Scripts, and Tests will no longer be part of the distribution files on PyPI. This should have little to no impact on most people. The Tests are renamed to tests, the Resources are renamed to resources. Both are still in the git repository. The Scripts are now in cpdf. Sample_Code was moved to the docs.

For a full list of deprecated functions, please see the changelog of version 1.28.0.

39.32.2 New Features (ENH)

- Improve space setting for text extraction (#922)
- Allow setting the decryption password in PdfReader.__init__ (#920)
- Add Page.add_transformation (#883)

39.32.3 Bug Fixes (BUG)

• Fix error adding transformation to page without /Contents (#908)

39.32.4 Robustness (ROB)

• Cope with invalid length in streams (#861)

39.32.5 Documentation (DOC)

- Fix style of 1.25 and 1.27 patch notes (#927)
- Transformation (#907)

39.32.6 Developer Experience (DEV)

- Create flake8 config file (#916)
- Use relative imports (#875)

39.32.7 Maintenance (MAINT)

- Use Python 3.6 language features (#849)
- Add wrapper function for PendingDeprecationWarnings (#928)
- Use new PEP8 compliant names (#884)
- Explicitly represent transformation matrix (#878)
- Inline PAGE_RANGE_HELP string (#874)
- Remove unnecessary generics imports (#873)
- Remove star imports (#865)
- merger.py _merger.py (#864)
- Type annotations for all functions/methods (#854)
- Add initial type support with mypy (#853)

39.32.8 Testing (TST)

- Regression test for xmp_metadata converter (#923)
- Checkout submodule sample-files for benchmark
- Add text extracting performance benchmark
- Use new PyPDF2 API in benchmark (#902)
- Make test suite fail for uncaught warnings (#892)
- Remove -OO testrun from CI (#901)
- Improve tests for convert_to_int (#899)

Full Changelog

39.33 PyPDF2 1.X

See CHANGELOG PyPDF2 1.X

CHAPTER

FORTY

CHANGELOG OF PYPDF2 1.X

40.1 Version 1.28.4, 2022-05-29

Bug Fixes (BUG):

• XmpInformation._converter_date was unusable (#921)

Full Changelog

40.2 Version 1.28.3, 2022-05-28

40.2.1 Deprecations (DEP)

• PEP8 renaming (#905)

40.2.2 Bug Fixes (BUG)

- XmpInformation missing method _getText (#917)
- Fix PendingDeprecationWarning on _merge_page (#904)

Full Changelog

40.3 Version 1.28.2, 2022-05-23

40.3.1 Bug Fixes (BUG)

- PendingDeprecationWarning for getContents (#893)
- PendingDeprecationWarning on using PdfMerger (#891)

Full Changelog

40.4 Version 1.28.1, 2022-05-22

40.4.1 Bug Fixes (BUG)

• Incorrectly show deprecation warnings on internal usage (#887)

40.4.2 Maintenance (MAINT)

- Add stacklevel=2 to deprecation warnings (#889)
- Remove duplicate warnings imports (#888)

Full Changelog

40.5 Version 1.28.0, 2022-05-22

This release adds a lot of deprecation warnings in preparation of the PyPDF2 2.0.0 release. The changes are mostly using snake_case function-, method-, and variable-names as well as using properties instead of getter-methods.

Maintenance (MAINT):

• Remove IronPython Fallback for zlib (#868)

Full Changelog

40.5.1 Deprecations (DEP)

- Make the PyPDF2.utils module private
- Rename of core classes:
 - PdfFileReader PdfReader
 - PdfFileWriter PdfWriter
 - PdfFileMerger PdfMerger
- Use PEP8 conventions for function names and parameters
- If a property and a getter-method are both present, use the property

Details

In many places:

- getObject get_object
- writeToStream write_to_stream
- readFromStream read_from_stream

PyPDF2.generic

- readObject read_object
- convertToInt convert_to_int

• DocumentInformation.getText DocumentInformation._get_text : This method should typically not be used; please let me know if you need it.

PdfReader class:

- reader.getPage(pageNumber) reader.pages[page_number]
- reader.getNumPages() / reader.numPages len(reader.pages)
- getDocumentInfo metadata
- flattenedPages attribute flattened_pages
- · resolvedObjects attribute resolved_objects
- xrefIndex attribute xref_index
- getNamedDestinations / namedDestinations attribute named_destinations
- getPageLayout / pageLayout page_layout attribute
- getPageMode / pageMode page_mode attribute
- getIsEncrypted / isEncrypted is_encrypted attribute
- getOutlines get_outlines
- readObjectHeader read_object_header
- cacheGetIndirectObject cache_get_indirect_object
- cacheIndirectObject cache_indirect_object
- getDestinationPageNumber get_destination_page_number
- readNextEndLine read_next_end_line
- _zeroXref _zero_xref
- _authenticateUserPassword _authenticate_user_password
- _pageId2Num attribute _page_id2num
- _buildDestination _build_destination
- _buildOutline _build_outline
- _getPageNumberByIndirect(indirectRef) _get_page_number_by_indirect(indirect_ref)
- _getObjectFromStream _get_object_from_stream
- _decryptObject _decrypt_object
- _flatten(..., indirectRef) _flatten(..., indirect_ref)
- _buildField _build_field
- _checkKids _check_kids
- _writeField _write_field
- _write_field(..., fieldAttributes) _write_field(..., field_attributes)
- _read_xref_subsections(..., getEntry, ...) _read_xref_subsections(..., get_entry, ...)

PdfWriter class:

- writer.getPage(pageNumber) writer.pages[page_number]
- writer.getNumPages() len(writer.pages)

- addMetadata add_metadata
- addPage add_page
- addBlankPage add_blank_page
- addAttachment(fname, fdata) add_attachment(filename, data)
- insertPage insert_page
- insertBlankPage insert_blank_page
- appendPagesFromReader append_pages_from_reader
- updatePageFormFieldValues update_page_form_field_values
- cloneReaderDocumentRoot clone_reader_document_root
- cloneDocumentFromReader clone_document_from_reader
- getReference get_reference
- getOutlineRoot get_outline_root
- getNamedDestRoot get_named_dest_root
- addBookmarkDestination add_bookmark_destination
- addBookmarkDict add_bookmark_dict
- addBookmark add_bookmark
- addNamedDestinationObject add_named_destination_object
- addNamedDestination add_named_destination
- removeLinks remove_links
- removeImages(ignoreByteStringObject) remove_images(ignore_byte_string_object)
- removeText(ignoreByteStringObject) remove_text(ignore_byte_string_object)
- addURI add_uri
- addLink add_link
- getPage(pageNumber) get_page(page_number)
- getPageLayout / setPageLayout / pageLayout page_layout attribute
- getPageMode / setPageMode / pageMode page_mode attribute
- _addObject _add_object
- _addPage _add_page
- _sweepIndirectReferences _sweep_indirect_references

PdfMerger class

- __init__ parameter: strict=True strict=False (the PdfFileMerger still has the old default)
- addMetadata add_metadata
- addNamedDestination add_named_destination
- setPageLayout set_page_layout
- setPageMode set_page_mode

Page class:

- artBox / bleedBox/ cropBox/ mediaBox / trimBox artbox / bleedbox/ cropbox/ mediabox / trimbox
 - getWidth, getHeight width / height
 - getLowerLeft_x / getUpperLeft_x left
 - getUpperRight_x / getLowerRight_x right
 - getLowerLeft_y / getLowerRight_y bottom
 - getUpperRight_y / getUpperLeft_y top
 - getLowerLeft / setLowerLeft lower_left property
 - upperRight upper_right
- mergePage merge_page
- rotateClockwise / rotateCounterClockwise rotate_clockwise
- _mergeResources _merge_resources
- _contentStreamRename _content_stream_rename
- _pushPopGS _push_pop_gs
- _addTransformationMatrix _add_transformation_matrix
- _mergePage _merge_page

XmpInformation class:

- getElement(..., aboutUri, ...) get_element(..., about_uri, ...)
- getNodesInNamespace(..., aboutUri, ...) get_nodes_in_namespace(..., aboutUri, ...)
- _getText _get_text

utils.py:

- matrixMultiply matrix_multiply
- RC4_encrypt is moved to the security module

40.6 Version 1.27.12, 2022-05-02

40.6.1 Bug Fixes (BUG)

• _rebuild_xref_table expects trailer to be a dict (#857)

40.6.2 Documentation (DOC)

• Security Policy

```
Full Changelog
```

40.7 Version 1.27.11, 2022-05-02

40.7.1 Bug Fixes (BUG)

• Incorrectly issued xref warning/exception (#855)

Full Changelog

40.8 Version 1.27.10, 2022-05-01

40.8.1 Robustness (ROB)

- Handle missing destinations in reader (#840)
- warn-only in readStringFromStream (#837)
- Fix corruption in startxref or xref table (#788 and #830)

40.8.2 Documentation (DOC)

- Project Governance (#799)
- History of PyPDF2
- PDF feature/version support (#816)
- More details on text parsing issues (#815)

40.8.3 Developer Experience (DEV)

- Add benchmark command to Makefile
- Ignore IronPython parts for code coverage (#826)

40.8.4 Maintenance (MAINT)

- Split pdf module (#836)
- Separated CCITTFax param parsing/decoding (#841)
- Update requirements files

40.8.5 Testing (TST)

- Use external repository for larger/more PDFs for testing (#820)
- Swap incorrect test names (#838)
- Add test for PdfFileReader and page properties (#835)
- Add tests for PyPDF2.generic (#831)
- Add tests for utils, form fields, PageRange (#827)
- Add test for ASCII85Decode (#825)

- Add test for FlateDecode (#823)
- Add test for filters.ASCIIHexDecode (#822)

40.8.6 Code Style (STY)

- Apply pre-commit (black, isort) + use snake_case variables (#832)
- Remove debug code (#828)
- Documentation, Variable names (#839)

Full Changelog

40.9 Version 1.27.9, 2022-04-24

A change I would like to highlight is the performance improvement for large PDF files (#808)

40.9.1 New Features (ENH)

- Add papersizes (#800)
- Allow setting permission flags when encrypting (#803)
- Allow setting form field flags (#802)

40.9.2 Bug Fixes (BUG)

- TypeError in xmp._converter_date (#813)
- Improve spacing for text extraction (#806)
- Fix PDFDocEncoding Character Set (#809)

40.9.3 Robustness (ROB)

- Use null ID when encrypted but no ID given (#812)
- Handle recursion error (#804)

40.9.4 Documentation (DOC)

- CMaps (#811)
- The PDF Format + commit prefixes (#810)
- Add compression example (#792)

40.9.5 Developer Experience (DEV)

• Add Benchmark for Performance Testing (#781)

40.9.6 Maintenance (MAINT)

- Validate PDF magic byte in strict mode (#814)
- Make PdfFileMerger.addBookmark() behave life PdfFileWriters' (#339)
- Quadratic runtime while parsing reduced to linear (#808)

40.9.7 Testing (TST)

• Newlines in text extraction (#807)

Full Changelog

40.10 Version 1.27.8, 2022-04-21

40.10.1 Bug Fixes (BUG)

- Use 1MB as offset for readNextEndLine (#321)
- 'PdfFileWriter' object has no attribute 'stream' (#787)

40.10.2 Robustness (ROB)

• Invalid float object; use 0 as fallback (#782)

40.10.3 Documentation (DOC)

• Robustness (#785)

Full Changelog

40.11 Version 1.27.7, 2022-04-19

40.11.1 Bug Fixes (BUG)

• Import exceptions from PyPDF2.errors in PyPDF2.utils (#780)

40.11.2 Code Style (STY)

• Naming in 'make_changelog.py'

40.12 Version 1.27.6, 2022-04-18

40.12.1 Deprecations (DEP)

• Remove support for Python 2.6 and older (#776)

40.12.2 New Features (ENH)

• Extract document permissions (#320)

40.12.3 Bug Fixes (BUG)

- Clip by trimBox when merging pages, which would otherwise be ignored (#240)
- Add overwriteWarnings parameter PdfFileMerger (#243)
- IndexError for getPage() of decryped file (#359)
- Handle cases where decodeParms is an ArrayObject (#405)
- Updated PDF fields don't show up when page is written (#412)
- Set Linked Form Value (#414)
- Fix zlib -5 error for corrupt files (#603)
- Fix reading more than last1K for EOF (#642)
- Acciental import

40.12.4 Robustness (ROB)

• Allow extra whitespace before "obj" in readObjectHeader (#567)

40.12.5 Documentation (DOC)

- Link to pdftoc in Sample_Code (#628)
- Working with annotations (#764)
- Structure history

40.12.6 Developer Experience (DEV)

- Add issue templates (#765)
- Add tool to generate changelog

40.12.7 Maintenance (MAINT)

- Use grouped constants instead of string literals (#745)
- Add error module (#768)
- Use decorators for @staticmethod (#775)
- Split long functions (#777)

40.12.8 Testing (TST)

- Run tests in CI once with -OO Flags (#770)
- Filling out forms (#771)
- Add tests for Writer (#772)
- Error cases (#773)
- Check Error messages (#769)
- Regression test for issue #88
- Regression test for issue #327

40.12.9 Code Style (STY)

• Make variable naming more consistent in tests

Full changelog

40.13 Version 1.27.5, 2022-04-15

40.13.1 Security (SEC)

• ContentStream_readInlineImage had potential infinite loop (#740)

40.13.2 Bug fixes (BUG)

- Fix merging encrypted files (#757)
- CCITTFaxDecode decodeParms can be an ArrayObject (#756)

40.13.3 Robustness improvements (ROBUST)

• title sometimes None (#744)

40.13.4 Documentation (DOC)

• Adjust short description of the package

40.13.5 Tests and Test setup (TST)

- Rewrite JS tests from unittest to pytest (#746)
- Increase Test coverage, mainly with filters (#756)
- Add test for inline images (#758)

40.13.6 Developer Experience Improvements (DEV)

- Remove unused Travis-CI configuration (#747)
- Show code coverage (#754, #755)
- Add mutmut (#760)

40.13.7 Miscellaneous

• STY: Closing file handles, explicit exports, ... (#743)

Full Changelog

40.14 Version 1.27.4, 2022-04-12

40.14.1 Bug fixes (BUG)

• Guard formatting of __init__.__doc__ string (#738)

40.14.2 Packaging (PKG)

• Add more precise license field to setup (#733)

40.14.3 Testing (TST)

• Add test for issue #297

40.14.4 Miscellaneous

- DOC: Miscallenious Miscellaneous (Typo)
- TST: Fix CI triggering (master main) (#739)
- STY: Fix various style issues (#742)

Full Changelog

40.15 Version 1.27.3, 2022-04-10

- PKG: Make Tests not a subpackage (#728)
- BUG: Fix ASCII85Decode.decode assertion (#729)
- BUG: Error in Chinese character encoding (#463)
- BUG: Code duplication in Scripts/2-up.py
- ROBUST: Guard 'obj.writeToStream' with 'if obj is not None'
- ROBUST: Ignore a /Prev entry with the value 0 in the trailer
- MAINT: Remove Sample_Code (#726)
- TST: Close file handle in test_writer (#722)
- TST: Fix test_get_images (#730)
- DEV: Make tox use pytest and add more Python versions (#721)
- DOC: Many (#720, #723-725, #469)

Full Changelog

40.16 Version 1.27.2, 2022-04-09

• Add Scripts (including pdfcat), Resources, Tests, and Sample_Code back to PyPDF2. It was removed by accident in 1.27.0, but might get removed with 2.0.0 See discussions/718.

Full Changelog

40.17 Version 1.27.1, 2022-04-08

- Fixed project links on PyPI page after migration from mstamy2 to MartinThoma to the py-pdf organization on GitHub
- Documentation is now at pypdf2.readthedocs.io

Full Changelog

40.18 Version 1.27.0, 2022-04-07

Features:

• Add alpha channel support for png files in Script (#614)

40.18.1 Bug fixes (BUG)

- Fix formatWarning for filename without slash (#612)
- Add whitespace between words for extractText() (#569, #334)
- "invalid escape sequence" SyntaxError (#522)
- Avoid error when printing warning in pythonw (#486)
- Stream operations can be List or Dict (#665)

40.18.2 Documentation (DOC)

- Added Scripts/pdf-image-extractor.py
- Documentation improvements (#550, #538, #324, #426, #394)

40.18.3 Tests and Test setup (TST)

- Add Github Action which automatically run unit tests via pytest and static code analysis with Flake8 (#660)
- Add several unit tests (#661, #663)
- Add .coveragerc to create coverage reports

40.18.4 Developer Experience Improvements (DEV)

• Pre commit: Developers can now pre-commit install to avoid tiny issues like trailing whitespaces

40.18.5 Miscellaneous

- Add the LICENSE file to the distributed packages (#288)
- Use setuptools instead of distutils (#599)
- Improvements for the PyPI page (#644)
- Python 3 changes (#504, #366)

Full Changelog

40.19 Version 1.26.0, 2016-05-18

- NOTE: Active maintenance on PyPDF2 is resuming after a hiatus
- Fixed a bug where image resources where incorrectly overwritten when merging pages
- Added dictionary for JavaScript actions to the root (louib)
- Added unit tests for the JS functionality (louib)
- Add more Python 3 compatibility when reading inline images (im2703 and (VyacheslavHashov)
- Return NullObject instead of raising error when failing to resolve object (ctate)
- Don't output warning for non-zeroed xref table when strict=False (BenRussert)
- Remove extraneous zeroes from output formatting (speedplane)
- Fix bug where reading an inline image would cut off prematurely in certain cases (speedplane)

40.20 Version 1.25.1, 2015-07-20

- Fix bug when parsing inline images. Occurred when merging certain pages with inline images
- Fixed type error when creating outlines by utilizing the isString() test

40.21 Version 1.25, 2015-07-07

BUGFIXES:

- Added Python 3 algorithm for ASCII85Decode. Fixes issue when reading reportlab-generated files with Py 3 (jerickbixly)
- Recognize more escape sequence which would otherwise throw an exception (manuelzs, robertsoakes)
- Fixed overflow error in generic.py. Occurred when reading a too-large int in Python 2 (by Raja Jamwal)
- Allow access to files which were encrypted with an empty password. Previously threw a "File has not been decrypted" exception (Elena Williams)
- Do not attempt to decode an empty data stream. Previously would cause an error in decode algorithms (vladir)
- Fixed some type issues specific to Py 2 or Py 3
- Fix issue when stream data begins with whitespace (soloma83)
- Recognize abbreviated filter names (AlmightyOatmeal and Matthew Weiss)

- Copy decryption key from PdfFileReader to PdfFileMerger. Allows usage of PdfFileMerger with encrypted files (twolfson)
- Fixed bug which occurred when a NameObject is present at end of a file stream. Threw a "Stream has ended unexpectedly" exception (speedplane)

FEATURES:

- Initial work on a test suite; to be expanded in future. Tests and Resources directory added, README updated (robertsoakes)
- Added document cloning methods to PdfFileWriter: appendPagesFromReader, cloneReaderDocumentRoot, and cloneDocumentFromReader. See official documentation (robertsoakes)
- Added method for writing to form fields: updatePageFormFieldValues. This will be enhanced in the future. See official documentation (robertsoakes)
- New addAttachment method. See documentation. Support for adding and extracting embedded files to be enhanced in the future (moshekaplan)
- Added methods to get page number of given PageObject or Destination: getPageNumber and getDestinationPageNumber. See documentation (mozbugbox)

OTHER ENHANCEMENTS:

- Enhanced type handling (Brent Amrhein)
- Enhanced exception handling in NameObject (sbywater)
- Enhanced extractText method output (peircej)
- Better exception handling
- Enhanced regex usage in NameObject class (speedplane)

40.22 Version 1.24, 2014-12-31

- Bugfixes for reading files in Python 3 (by Anthony Tuininga and pqqp)
- Appropriate errors are now raised instead of infinite loops (by naure and Cyrus Vafadari)
- Bugfix for parsing number tokens with leading spaces (by Maxim Kamenkov)
- Don't crash on bad /Outlines reference (by eshellman)
- Conform tabs/spaces and blank lines to PEP 8 standards
- Utilize the readUntilRegex method when reading Number Objects (by Brendan Jurd)
- · More bugfixes for Python 3 and clearer exception handling
- Fixed encoding issue in merger (with eshellman)
- Created separate folder for scripts

40.23 Version 1.23, 2014-08-11

- Documentation now available at pythonhosted.org
- Bugfix in pagerange.py for when __init__.__doc__ has no value (by Vladir Cruz)
- Fix typos in OutlinesObject().add() (by shilluc)
- · Re-added a missing return statement in a utils.py method
- · Corrected viewing mode names (by Jason Scheirer)
- New PdfFileWriter method: addJS() (by vfigueiro)
- New bookmark features: color, boldness, italics, and page fit (by Joshua Arnott)
- New PdfFileReader method: getFields(). Used to extract field information from PDFs with interactive forms. See documentation for details
- Converted README file to markdown format (by Stephen Bussard)
- Several improvements to overall performance and efficiency (by mozbugbox)
- · Fixed a bug where geospatial information was not scaling along with its page
- Fixed a type issue and a Python 3 issue in the decryption algorithms (with Francisco Vieira and koba-ninkigumi)
- Fixed a bug causing an infinite loop in the ASCII 85 decoding algorithm (by madmaardigan)
- · Annotations (links, comment windows, etc.) are now preserved when pages are merged together
- Used the Destination class in addLink() and addBookmark() so that the page fit option could be properly customized

40.24 Version 1.22, 2014-05-29

- Added .DS_Store to .gitignore (for Mac users) (by Steve Witham)
- Removed __init__() implementation in NameObject (by Steve Witham)
- Fixed bug (inf. loop) when merging pages in Python 3 (by commx)
- Corrected error when calculating height in scaleTo()
- Removed unnecessary code from DictionaryObject (by Georges Dubus)
- Fixed bug where an exception was thrown upon reading a NULL string (by speedplane)
- Allow string literals (non-unicode strings in Python 2) to be passed to PdfFileReader
- Allow ConvertFunctionsToVirtualList to be indexed with slices and longs (in Python 2) (by Matt Gilson)
- Major improvements and bugfixes to addLink() method (see documentation in source code) (by Henry Keiter)
- General code clean-up and improvements (with Steve Witham and Henry Keiter)
- · Fixed bug that caused crash when comments are present at end of dictionary

40.25 Version 1.21, 2014-04-21

- Fix for when /Type isn't present in the Pages dictionary (by Rob1080)
- More tolerance for extra whitespace in Indirect Objects
- Improved Exception handling
- Fixed error in getHeight() method (by Simon Kaempflein)
- implement use of utils.string_type to resolve Py2-3 compatibility issues
- Prevent exception for multiple definitions in a dictionary (with carlosfunk) (only when strict = False)
- Fixed errors when parsing a slice using pdfcat on command line (by Steve Witham)
- Tolerance for EOF markers within 1024 bytes of the actual end of the file (with David Wolever)
- Added overwriteWarnings parameter to PdfFileReader constructor, if False PyPDF2 will NOT overwrite methods from Python's warnings.py module with a custom implementation.
- Fix NumberObject and NameObject constructors for compatibility with PyPy (Rüdiger Jungbeck, Xavier Dupré, shezadkhan137, Steven Witham)
- Utilize utils.Str in pdf.py and pagerange.py to resolve type issues (by egbutter)
- Improvements in implementing StringIO for Python 2 and BytesIO for Python 3 (by Xavier Dupré)
- Added /x00 to Whitespaces, defined utils.WHITESPACES to clarify code (by Maxim Kamenkov)
- Bugfix for merging 3 or more resources with the same name (by lucky-user)
- Improvements to Xref parsing algorithm (by speedplane)

40.26 Version 1.20, 2014-01-27

- Official Python 3+ support (with contributions from TWAC and cgammans) Support for Python versions 2.6 and 2.7 will be maintained
- Command line concatenation (see pdfcat in sample code) (by Steve Witham)
- New FAQ; link included in README
- Allow more (although unnecessary) escape sequences
- · Prevent exception when reading a null object in decoding parameters
- Corrected error in reading destination types (added a slash since they are name objects)
- Corrected TypeError in scaleTo() method
- addBookmark() method in PdfFileMerger now returns bookmark (so nested bookmarks can be created)
- · Additions to Sample Code and Sample PDFs
- changes to allow 2up script to work (see sample code) (by Dylan McNamee)
- changes to metadata encoding (by Chris Hiestand)
- New methods for links: addLink() (by Enrico Lambertini) and removeLinks()
- Bugfix to handle nested bookmarks correctly (by Jamie Lentin)
- New methods removeImages() and removeText() available for PdfFileWriter (by Tien Haï)
- · Exception handling for illegal characters in Name Objects

40.27 Version 1.19, 2013-10-08

BUGFIXES:

- Removed pop in sweepIndirectReferences to prevent infinite loop (provided by ian-su-sirca)
- Fixed bug caused by whitespace when parsing PDFs generated by AutoCad
- Fixed a bug caused by reading a 'null' ASCII value in a dictionary object (primarily in PDFs generated by AutoCad).

FEATURES:

- Added new folders for PyPDF2 sample code and example PDFs; see README for each folder
- Added a method for debugging purposes to show current location while parsing
- Ability to create custom metadata (by jamma313)
- Ability to access and customize document layout and view mode (by Joshua Arnott)

OTHER:

- Added and corrected some documentation
- · Added some more warnings and exception messages
- Removed old test/debugging code

UPCOMING:

- More bugfixes (We have received many problematic PDFs via email, we will work with them)
- Documentation It's time for PyPDF2 to get its own documentation since it has grown much since the original pyPdf
- A FAQ to answer common questions

40.28 Version 1.18, 2013-08-19

- Fixed a bug where older verions of objects were incorrectly added to the cache, resulting in outdated or missing pages, images, and other objects (from speedplane)
- Fixed a bug in parsing the xref table where new xref values were overwritten; also cleaned up code (from speed-plane)
- New method mergeRotatedAroundPointPage which merges a page while rotating it around a point (from speed-plane)
- Updated Destination syntax to respect PDF 1.6 specifications (from jamma313)
- Prevented infinite loop when a PdfFileReader object was instantiated with an empty file (from Jerome Nexedi)

Other Changes:

- Downloads now available via PyPI
- Installation through pip library is fixed

40.29 Version 1.17, 2013-07-25

- Removed one (from pdf.py) of the two Destination classes. Both classes had the same name, but were slightly different in content, causing some errors. (from Janne Vanhala)
- Corrected and Expanded README file to demonstrate PdfFileMerger
- Added filter for LZW encoded streams (from Michal Horejsek)
- PyPDF2 issue tracker enabled on Github to allow community discussion and collaboration

40.30 Versions -1.16, -2013-06-30

- Note: This ChangeLog has not been kept up-to-date for a while. Hopefully we can keep better track of it from now on. Some of the changes listed here come from previous versions 1.14 and 1.15; they were only vaguely defined. With the new _version.py file we should have more structured and better documented versioning from now on.
- Defined PyPDF2.__version__
- Fixed encrypt() method (from Martijn The)
- Improved error handling on PDFs with truncated streams (from cecilkorik)
- Python 3 support (from kushal-kumaran)
- Fixed example code in README (from Jeremy Bethmont)
- Fixed an bug caused by DecimalError Exception (from Adam Morris)
- Many other bug fixes and features by:

jeansch Anton Vlasenko Joseph Walton Jan Oliver Oelerich Fabian Henze And any others I missed. Thanks for contributing!

40.31 Version 1.13, 2010-12-04

- Fixed a typo in code for reading a "\b" escape character in strings.
- Improved __repr__ in FloatObject.
- Fixed a bug in reading octal escape sequences in strings.
- Added getWidth and getHeight methods to the RectangleObject class.
- Fixed compatibility warnings with Python 2.4 and 2.5.
- Added addBlankPage and insertBlankPage methods on PdfFileWriter class.
- Fixed a bug with circular references in page's object trees (typically annotations) that prevented correctly writing out a copy of those pages.
- New merge page functions allow application of a transformation matrix.
- To all patch contributors: I did a poor job of keeping this ChangeLog up-to-date for this release, so I am missing attributions here for any changes you submitted. Sorry! I'll do better in the future.

40.32 Version 1.12, 2008-09-02

- Added support for XMP metadata.
- Fix reading files with xref streams with multiple /Index values.
- Fix extracting content streams that use graphics operators longer than 2 characters. Affects merging PDF files.

40.33 Version 1.11, 2008-05-09

- Patch from Hartmut Goebel to permit RectangleObjects to accept NumberObject or FloatObject values.
- PDF compatibility fixes.
- Fix to read object xref stream in correct order.
- Fix for comments inside content streams.

40.34 Version 1.10, 2007-10-04

- Text strings from PDF files are returned as Unicode string objects when pyPdf determines that they can be decoded (as UTF-16 strings, or as PDFDocEncoding strings). Unicode objects are also written out when necessary. This means that string objects in pyPdf can be either generic.ByteStringObject instances, or generic.TextStringObject instances.
- The extractText method now returns a unicode string object.
- All document information properties now return unicode string objects. In the event that a document provides docinfo properties that are not decoded by pyPdf, the raw byte strings can be accessed with an "_raw" property (ie. title_raw rather than title)
- generic.DictionaryObject instances have been enhanced to be easier to use. Values coming out of dictionary objects will automatically be de-referenced (.getObject will be called on them), unless accessed by the new "raw_get" method. DictionaryObjects can now only contain PdfObject instances (as keys and values), making it easier to debug where non-PdfObject values (which cannot be written out) are entering dictionaries.
- Support for reading named destinations and outlines in PDF files. Original patch by Ashish Kulkarni.
- Stream compatibility reading enhancements for malformed PDF files.
- Cross reference table reading enhancements for malformed PDF files.
- Encryption documentation.
- Replace some "assert" statements with error raising.
- Minor optimizations to FlateDecode algorithm increase speed when using PNG predictors.
40.35 Version 1.9, 2006-12-15

- Fix several serious bugs introduced in version 1.8, caused by a failure to run through our PDF test suite before releasing that version.
- Fix bug in NullObject reading and writing.

40.36 Version 1.8, 2006-12-14

- Add support for decryption with the standard PDF security handler. This allows for decrypting PDF files given the proper user or owner password.
- Add support for encryption with the standard PDF security handler.
- Add new pythondoc documentation.
- Fix bug in ASCII85 decode that occurs when whitespace exists inside the two terminating characters of the stream.

40.37 Version 1.7, 2006-12-10

- Fix a bug when using a single page object in two PdfFileWriter objects.
- Adjust PyPDF to be tolerant of whitespace characters that don't belong during a stream object.
- Add documentInfo property to PdfFileReader.
- Add numPages property to PdfFileReader.
- Add pages property to PdfFileReader.
- Add extractText function to PdfFileReader.

40.38 Version 1.6, 2006-06-06

- Add basic support for comments in PDF files. This allows us to read some ReportLab PDFs that could not be read before.
- Add "auto-repair" for finding xref table at slightly bad locations.
- New StreamObject backend, cleaner and more powerful. Allows the use of stream filters more easily, including compressed streams.
- Add a graphics state push/pop around page merges. Improves quality of page merges when one page's content stream leaves the graphics in an abnormal state.
- Add PageObject.compressContentStreams function, which filters all content streams and compresses them. This will reduce the size of PDF pages, especially after they could have been decompressed in a mergePage operation.
- Support inline images in PDF content streams.
- Add support for using .NET framework compression when zlib is not available. This does not make pyPdf compatible with IronPython, but it is a first step.
- Add support for reading the document information dictionary, and extracting title, author, subject, producer and creator tags.

• Add patch to support NullObject and multiple xref streams, from Bradley Lawrence.

40.39 Version 1.5, 2006-01-28

- Fix a bug where merging pages did not work in "no-rename" cases when the second page has an array of content streams.
- Remove some debugging output that should not have been present.

40.40 Version 1.4, 2006-01-27

- Add capability to merge pages from multiple PDF files into a single page using the PageObject.mergePage function. See example code (README or web site) for more information.
- Add ability to modify a page's MediaBox, CropBox, BleedBox, TrimBox, and ArtBox properties through PageObject. See example code (README or web site) for more information.
- Refactor pdf.py into multiple files: generic.py (contains objects like NameObject, DictionaryObject), filters.py (contains filter code), utils.py (various). This does not affect importing PdfFileReader or PdfFileWriter.
- Add new decoding functions for standard PDF filters ASCIIHexDecode and ASCII85Decode.
- Change url and download_url to refer to new pybrary.net web site.

40.41 Version 1.3, 2006-01-23

- Fix new bug introduced in 1.2 where PDF files with \r line endings did not work properly anymore. A new test suite developed with various PDF files should prevent regression bugs from now on.
- Fix a bug where inheriting attributes from page nodes did not work.

40.42 Version 1.2, 2006-01-23

- Improved support for files with CRLF-based line endings, fixing a common reported problem stating "assertion error: assert line == "%%EOF"".
- Software author/maintainer is now officially a proud married person, which is sure to result in better software... somehow.

40.43 Version 1.1, 2006-01-18

- Add capability to rotate pages.
- Improved PDF reading support to properly manage inherited attributes from /Type=/Pages nodes. This means that page groups that are rotated or have different media boxes or whatever will now work properly.
- Added PDF 1.5 support. Namely cross-reference streams and object streams. This release can mangle Adobe's PDFReference16.pdf successfully.

40.44 Version 1.0, 2006-01-17

- First distutils-capable true public release. Supports a wide variety of PDF files that I found sitting around on my system.
- Does not support some PDF 1.5 features, such as object streams, cross-reference streams.

CHAPTER FORTYONE

PROJECT GOVERNANCE

This document describes how the PyPDF2 project is managed. It describes the different actors, their roles, and the responsibilities they have.

41.1 Terminology

- The **project** is PyPDF2 a free and open-source pure-python PDF library capable of splitting, merging, cropping, and transforming the pages of PDF files. It includes the code, issues, and discussions on GitHub, and the documentation on ReadTheDocs, the package on PyPI, and the website on GitHub.
- A **maintainer** is a person who has technical permissions to change one or more part of the projects. It is a person who is driven to keep the project running and improving.
- A **contributor** is a person who contributes to the project. That could be through writing code in the best case through forking and creating a pull request, but that is up to the maintainer. Other contributors describe issues, help to ask questions on existing issues to make them easier to answer, participate in discussions, and help to improve the documentation. Contributors are similar to maintainers, but without technial permissions.
- A **user** is a person who imports PyPDF2 into their code. All PyPDF2 users are developers, but not developers who know the internals of PyPDF2. They only use the public interface of PyPDF2. They will likely have less knowledge about PDF than contributors.
- The community is all of that the users, the contributors, and the maintainers.

41.2 Governance, Leadership, and Steering PyPDF2 forward

PyPDF2 is a free and open source project with over 100 contributors and likely (way) more than 1000 users.

As PyPDF2 does not have any formal relationship with any company and no funding, all the work done by the community are voluntary contributions. People don't get paid, but choose to spend their free time to create software of which many more are profiting. This has to be honored and respected.

Despite such a big community, the project was dormant from 2016 to 2022. There were still questions asked, issues reported, and pull requests created. But the maintainer didn't have the time to move PyPDF2 forward. During that time, nobody else stepped up to become the new maintainer.

For this reason, PyPDF2 has the **Benevolent Dictator** governance model. The benevolent dictator is a maintainer with all technical permissions - most importantly the permission to push new PyPDF2 versions on PyPI.

Being benevolent, the benevolent dictator listens for decisions to the community and tries their best to make decisions from which the overall community profits - the current one and the potential future one. Being a dictator, the benevolent dictator always has the power and the right to make decisions on their own - also against some members of the community.

As PyPDF2 is free software, parts of the community can split off (fork the code) and create a new community. This should limit the harm a bad benevolent dictator can do.

41.3 Project Language

The project language is (american) English. All documentation and issues must be written in English to ensure that the community can understand it.

We appreciate the fact that large parts of the community don't have English as their mother tongue. We try our best to understand others - automatic translators might help.

41.4 Expectations

The community can expect the following:

- The **benevolent dictator** tries their best to make decisions from which the overall community profits. The benevolent dictator is aware that his/her decisions can shape the overall community. Once the benevolent dictator notices that she/he doesn't have the time to advance PyPDF2, he/she looks for a new benevolent dictator. As it is expected that the benevolent dictator will step down at some point of their choice (hopefully before their death), it is NOT a benevolent dictator for life (BDFL).
- Every maintainer (including the benevolent dictator) is aware of their permissions and the harm they could do. They value security and ensure that the project is not harmed. They give their technical permissions back if they don't need them any longer. Any long-time contributor can become a maintainer. Maintainers can - and should!
 step down from their role when they realize that they can no longer commit that time. Their contribution will be honored in the *History of PyPDF2*.
- Every **contributor** is aware that the time of maintainers and the benevolent dictator is limited. Short pull requests that briefly describe the solved issue and have a unit test have a higher chance to get merged soon simply because it's easier for maintainers to see that the contribution will not harm the overall project. Their contributions are documented in the git history and in the public issues. Let us know if you would appriciate something else!
- Every **community member** uses a respectful language. We are all human, we get upset about things we care and other things than what's visible on the internet go on in our live. PyPDF2 does not pay its contributors keep all of that in mind when you interact with others. We are here because we want to help others.

41.4.1 Issues and Discussions

An issue is any technical description that aims at bringing PyPDF2 forward:

- Bugs tickets: Something went wrong because PyPDF2 developers made a mistake.
- Feature requests: PyPDF2 does not support all features of the PDF specifications. There are certainly also convenience methods that would help users a lot.
- Robustness requests: There are many broken PDFs around. In some cases, we can deal with that. It's kind of a mixture between a bug ticket and a feature request.
- Performance tickets: PyPDF2 could be faster let us know about your specific scenario.

Any comment that is in those technial descriptions which is not helping the discussion can be deleted. This is especially true for "me too" comments on bugs or "bump" comments for desired features. People can express this with / reactions.

Discussions are open. No comments will be deleted there - except if they are clearly unrelated spam or only try to insult people (luckily, the community was very respectful so far)

41.4.2 Releases

The maintainers follow semantic versioning. Most importantly, that means that breaking changes will have a major version bump.

Be aware that unintentional breaking changes might still happen. The PyPDF2 maintainers do their best to fix that in a timely manner - please report such issues!

41.5 People

- Martin Thoma is benevolent dictator since April 2022.
- Maintainers:
 - Matthew Stamy (mstamy2) was the benevolent dictator for a long time. He still is around on GitHub once in a while and has permissions on PyPI and GitHub.
 - Matthew Peveler (MasterOdin) is a maintainer on GitHub.

CHAPTER

FORTYTWO

HISTORY OF PYPDF2

42.1 The Origins: pyPdf (2005-2010)

In 2005, Mathieu Fenniak launched pyPdf "as a PDF toolkit..." focused on

- document manipulation: by-page splitting, concatenation, and merging;
- document introspection;
- page cropping; and
- · document encryption and decryption.

The last release of PyPI was pyPdf 1.13 in 2010.

42.2 PyPDF2 is born (2011-2016)

At the end of 2011, after consultation with Mathieu and others, Phaseit sponsored PyPDF2 as a fork of pyPdf on GitHub. The initial impetus was to handle a wider range of input PDF instances; Phaseit's commercial work often encounters PDF instances "in the wild" that it needs to manage (mostly concatenate and paginate), but that deviate so much from PDF standards that pyPdf can't read them. PyPDF2 reads a considerably wider range of real-world PDF instances.

Neither pyPdf nor PyPDF2 aims to be universal, that is, to provide all possible PDF-related functionality. Note that the similar-appearing pyfpdf of Mariano Reingart is most comparable to ReportLab, in that both ReportLab and pyfpdf emphasize document generation. Interestingly enough, pyfpdf builds in a basic HTML \rightarrow PDF converter while PyPDF2 has no knowledge of HTML.

So what is PyPDF2 truly about? Think about popular pdftk for a moment. PyPDF2 does what pdftk does, and it does so within your current Python process, and it handles a wider range of variant PDF formats [explain]. PyPDF2 has its own FAQ to answer other questions that have arisen.

The Reddit /r/python crowd chatted obliquely and briefly about PyPDF2 in March 2012.

42.3 PyPDF3 and PyPDF4 (2018 - 2022)

Two approaches were made to get PyPDF2 active again: PyPDF3 and PyPDF4.

PyPDF3 had it's first release in 2018 and its last one in February 2022. It never got the user base from PyPDF2. PyPDF4 only had one release in 2018.

42.4 PyPDF2: Reborn (2022-Today)

Martin Thoma took over maintenance of PyPDF2 in April 2022.

CHAPTER FORTYTHREE

CONTRIBUTORS

PyPDF2 had a lot of contributors since it started with pyPdf in 2005. We are a free software project without any company affiliation. We cannot pay contributors, but we do value their contributions. A lot of time, effort, and expertise went into this project. With this list, we recognize those awesome people

The list is definitely not complete. You can find more contributors via the git history and GitHubs 'Contributors' feature.

43.1 Contributors to the pyPdf / PyPDF2 project

- DL6ER
- ediamondscience
- Górny, Michał
- Hale, Joseph
- JianzhengLuo
- Karvonen, Harry
- KourFrost
- Lightup1
- Mérino, Antoine
- Perrensen, Olsen
- Pinheiro, Arthur
- programmarchy
- pubpub-zz: involved in community development
- Rogmann, Sascha
- sietzeberends
- Stüber, Timo
- Thoma, Martin: Maintainer of PyPDF2 since April 2022. I hope to build a great community with many awesome contributors. LinkedIn | StackOverflow | Blog
- WevertonGomes
- ztravis

43.2 Adding a new contributor

Contributors are:

- Anybody who has an commit in main no matter how big/small or how many. Also if it's via co-authored-by.
- People who opened helpful issues: (1) Bugs: with complete MCVE (2) Well-described feature requests (3) Potentially some more. The maintainers of PyPDF2 have the last call on that one.
- Community work: This is exceptional. If the maintainers of PyPDF2 see people being super helpful in answering issues / discussions or being very active on Stackoverflow, we also consider them being contributors to PyPDF2.

Contributors can add themselves or ask via an Github Issue to be added.

Please use the following format:

```
* Last name, First name: 140-characters of text; links to linkedin / github / other.

→profiles and personal pages are ok
```

OR

```
* GitHub Username: 140-characters of text; links to linkedin / github / other profiles_
→and personal pages are ok
```

and add the entry in the alphabetical order. People who . The 140 characters are everything visible after the Name:. Please don't use images.

CHAPTER

FORTYFOUR

PYPDF2 VS X

PyPDF2 is a free and open source pure-python PDF library capable of splitting, merging, cropping, and transforming the pages of PDF files. It can also add custom data, viewing options, and passwords to PDF files. PyPDF2 can retrieve text and metadata from PDFs as well.

44.1 PyMuPDF and PikePDF

PyMuPDF is a Python binding to MuPDF and PikePDF is the Python binding to QPDF.

While both are excellent libraries for various use-cases, using them is not always possible even when they support the use-case. Both of them are powered by C libraries which makes installation harder and might cause security concerns. For MuPDF you might also need to buy a commercial license.

A core feature of PyPDF2 is that it's pure Python. That means there is no C dependency. It has been used for over 10 years and for this reason a lot of support via StackOverflow and examples on the internet.

44.2 pyPDF

PyPDF2 was forked from pyPDF. pyPDF has been unmaintained for a long time.

44.3 PyPDF3 and PyPDF4

Developing and maintaining open source software is extremely time-intensive and in the case of PyPDF2 not paid at all. Having a continuous support is hard.

PyPDF2 was initially released in 2012 on PyPI and received releases until 2016. From 2016 to 2022 there was no update - but people were still using it.

As PyPDF2 is free software, there were attempts to fork it and continue the development. PyPDF3 was first released in 2018 and still receives updates. PyPDF4 has only one release from 2018.

I, Martin Thoma, the current maintainer of PyPDF2, hope that we can bring the community back to one path of development. Let's see.

44.4 pdfrw and pdfminer

I don't have experience with either of those libraries. Please add a comparison if you know PyPDF2 and pdfrw or pdfminer.six!

Please be aware that there is also pdfminer which is not maintained. Then there is pdfrw2 which doesn't have a large community behind it.

And there are more:

pdfplumber

44.5 Document Generation

There are (Python) tools to generate PDF documents. PyPDF2 is not one of them.

CHAPTER

FORTYFIVE

FREQUENTLY-ASKED QUESTIONS

45.1 How is PyPDF2 related to pyPdf?

PyPDF2 is a fork from the no-longer-maintained pyPdf approved by the latter's founder.

45.2 Which Python versions are supported?

PyPDF2 2.0+ supports Python 3.6 and later. PyPDF2 1.27.10 supported Python 2.7 to 3.10.

45.3 Who uses PyPDF2?

pyPdf is vendored into several projects. That means the code of pyPdf was copied into that project.

Projects that depend on PyPDF2:

- · Camelot: A Python library to extract tabular data from PDFs
- edi: Electronic Data Interchange modules
- amazon-textract-textractor: Analyze documents with Amazon Textract and generate output in multiple formats.
- maigret: Collect a dossier on a person by username from thousands of sites
- deda: tracking Dots Extraction, Decoding and Anonymisation toolkit
- opencanary
- Document Conversions
 - rst2pdf
 - xhtml2pdf
 - doc2text
- pdfalyzer: A PDF analysis tool for visualizing the inner tree-like data structure of a PDF in spectacularly large and colorful diagrams as well as scanning the binary streams embedded in the PDF for hidden potentially malicious content.

45.4 How do I cite PyPDF2?

In BibTeX format:

@misc{pypdf	E2,
title	<pre>= {The {PyPDF2} library},</pre>
author	= {Mathieu Fenniak and
	Matthew Stamy and
	pubpub-zz and
	Martin Thoma and
	Matthew Peveler and
	<pre>exiledkingcc and {PyPDF2 Contributors}},</pre>
year	= {2022},
url	<pre>= {https://pypi.org/project/PyPDF2/}</pre>
note	<pre>= {See https://pypdf2.readthedocs.io/en/latest/meta/CONTRIBUTORS.html for_</pre>
⊶all contr	ributors}
}	

CHAPTER

FORTYSIX

INDICES AND TABLES

- genindex
- modindex
- search

Note: This page is about PyPDF2. PyPDF2 is deprecated, please use pypdf

INDEX

А

A0 (PyPDF2.PaperSize attribute), 117 A1 (PyPDF2.PaperSize attribute), 117 A2 (PyPDF2.PaperSize attribute), 117 A3 (PyPDF2.PaperSize attribute), 117 A4 (PyPDF2.PaperSize attribute), 117 A5 (PyPDF2.PaperSize attribute), 117 A6 (PyPDF2.PaperSize attribute), 117 A7 (PyPDF2.PaperSize attribute), 117 A8 (PyPDF2.PaperSize attribute), 117 add_annotation() (PyPDF2.PdfWriter method), 74 add_attachment() (PyPDF2.PdfWriter method), 74 add_blank_page() (PyPDF2.PdfWriter method), 74 add_bookmark() (PyPDF2.PdfMerger method), 85 add_bookmark() (PyPDF2.PdfWriter method), 74 add_bookmark_destination() (PyPDF2.PdfWriter method), 74 add_bookmark_dict() (PyPDF2.PdfWriter method), 74 add_filtered_articles() (PyPDF2.PdfWriter method), 74 add_js() (PyPDF2.PdfWriter method), 74 add_link() (PyPDF2.PdfWriter method), 74 add_metadata() (PyPDF2.PdfMerger method), 85 add_metadata() (PyPDF2.PdfWriter method), 75 add_named_destination() (PyPDF2.PdfMerger method), 85 add_named_destination() (PyPDF2.PdfWriter method), 75 add_named_destination_array() (PyPDF2.PdfWriter method), 75 add_named_destination_object() (PyPDF2.PdfWriter method), 75 add_outline() (PyPDF2.PdfWriter method), 75 add_outline_item() (PyPDF2.PdfMerger method), 86 add_outline_item() (PyPDF2.PdfWriter method), 75 add_outline_item_destination() (PyPDF2.PdfWriter method), 75 add_outline_item_dict() (PyPDF2.PdfWriter method), 75 add_page() (PyPDF2.PdfWriter method), 76 add_transformation() (PyPDF2._page.PageObject

method), 89 add_uri() (PyPDF2.PdfWriter method), 76 addAttachment() (PyPDF2.PdfWriter method), 73 addBlankPage() (PyPDF2.PdfWriter method), 73 addBookmark() (PyPDF2.PdfMerger method), 85 addBookmark() (PyPDF2.PdfWriter method), 73 addBookmarkDestination() (PyPDF2.PdfWriter method), 73 addBookmarkDict() (PyPDF2.PdfWriter method), 73 additional_actions (PyPDF2.generic.Field property), 109 additionalActions (PyPDF2.generic.Field property), 109 addJS() (PyPDF2.PdfWriter method), 73 addLink() (PyPDF2.PdfWriter method), 73 addMetadata() (PyPDF2.PdfMerger method), 85 addMetadata() (PyPDF2.PdfWriter method), 73 addNamedDestination() (PyPDF2.PdfMerger method), 85 addNamedDestination() (*PyPDF2.PdfWriter method*), 73 addNamedDestinationObject() (PyPDF2.PdfWriter method), 73 addPage() (PyPDF2.PdfWriter method), 73 addTransformation() (PyPDF2._page.PageObject method), 89 addURI() (PyPDF2.PdfWriter method), 73 alternate_name (PyPDF2.generic.Field property), 109 altName (PyPDF2.generic.Field property), 109 AnnotationBuilder (class in PyPDF2.generic), 113 annotations (PyPDF2._page.PageObject property), 89 append() (*PyPDF2.PdfMerger method*), 86 append() (*PyPDF2.PdfWriter method*), 76 append_pages_from_reader() (PyPDF2.PdfWriter method), 76 appendPagesFromReader() (PyPDF2.PdfWriter method), 76 apply_on() (PyPDF2.Transformation method), 97 artBox (*PyPDF2*._*page*.*PageObject property*), 89 artbox (PyPDF2._page.PageObject property), 89 author (PyPDF2.DocumentInformation property), 99 author_raw (*PyPDF2.DocumentInformation property*),

99

В

bleedBox (PyPDF2._page.PageObject property), 89 bleedbox (PyPDF2._page.PageObject property), 89 bottom (PyPDF2.generic.Destination property), 105 bottom (PyPDF2.generic.RectangleObject property), 107

С

C4 (PvPDF2.PaperSize attribute), 1	17
cache get indirect object()	(PvPDF2 PdfReader
method) 67	
cache indirect object()	(PvPDF? PdfReader
method) 67	(i yi bi 2.1 ajiteaae)
cacheGetIndirectObject()	(PvPDF? PdfReader
method) 67	(1 yr Di 2.1 ujreduer
cacheIndirectObject()	(PvPDF? PdfReader
method) 67	(1 yr DI 2.1 ujredder
childs (PyPDF2 generic Destinati	on attributa) 105
closp page() (PyPDE2 PdfWrite)	r method) 77
clean_page() (1 yr Dr2.1 ur writer	(DyDDE? DdfWritan
mathod) 77	(1 yi Dr 2.1 uj writer
along noodon document noot()	(D.D.D.F? D.d.W.witan
crone_reader_document_root()) (FyFDF2.Fajwriier
meinoa), //	
cloneDocumentFromkeader()	(PyPDF2.Pafwriter
metnoa), //	
clonekeaderDocumentRoot()	(PyPDF2.Pafwriter
method), //	
close() (PyPDF2.PdfMerger meth	<i>bod</i>), 86
close() (PyPDF2.PdfWriter metho	od), 77
color (PyPDF2.generic.Destination	n property), 105
<pre>compress() (PyPDF2.Transformat</pre>	ion static method), 97
<pre>compress_content_streams()</pre>	
(PyPDF2page.PageObje	ect method), 90
compressContentStreams()	
(PyPDF2page.PageObje	ect method), 90
<pre>create_blank_page() (PyPD</pre>	F2page.PageObject
static method), 90	
<pre>createBlankPage() (PyPDF2p</pre>	age.PageObject static
method), 90	
creation_date (PyPDF2.Docum	entInformation prop-
<i>erty</i>), 99	
creation_date_raw (PyPDF2.1	DocumentInformation
property), 99	
creator (PyPDF2.DocumentInform	nation property), 99
creator_raw (PyPDF2.Docume	ntInformation prop-
<i>erty</i>), 99	
cropBox (PyPDF2page.PageObje	ect property), 90
cropbox (PyPDF2page.PageObje	ect property), 90
custom_properties (PyPDF2.	xmp.XmpInformation
property), 101	- * *

D

dc_contributor (PyPDF2.xmp.XmpInformation prop-	
<i>erty</i>), 101	
dc couorago (P)PDF2 rmp VmpInformation property)	

- dc_coverage (*PyPDF2.xmp.XmpInformation property*), 101
- dc_date (*PyPDF2.xmp.XmpInformation property*), 101
- dc_description (*PyPDF2.xmp.XmpInformation property*), 101
- dc_format (PyPDF2.xmp.XmpInformation property),
 101
- dc_identifier (PyPDF2.xmp.XmpInformation property), 101
- dc_language (*PyPDF2.xmp.XmpInformation property*), 101
- dc_publisher (PyPDF2.xmp.XmpInformation property), 101
- dc_rights (PyPDF2.xmp.XmpInformation property),
 101
- dc_source (*PyPDF2.xmp.XmpInformation property*), 102
- dc_subject (PyPDF2.xmp.XmpInformation property),
 102
- dc_title (*PyPDF2.xmp.XmpInformation property*), 102

dc_type (*PyPDF2.xmp.XmpInformation property*), 102 decode_permissions() (*PyPDF2.PdfReader method*), 67

- decrypt() (PyPDF2.PdfReader method), 67
- default_value (*PyPDF2.generic.Field property*), 109
- defaultValue (*PyPDF2.generic.Field property*), 109

dest_array (PyPDF2.generic.Destination property), 105

Destination (*class in PyPDF2.generic*), 105 documentInfo (*PyPDF2.PdfReader property*), 67 DocumentInformation (*class in PyPDF2*), 99

Е

- encrypt() (PyPDF2.PdfWriter method), 77

F

- Field (class in PyPDF2.generic), 109
- field_type (PyPDF2.generic.Field property), 109
 fieldType (PyPDF2.generic.Field property), 109

- find_bookmark() (PyPDF2.PdfMerger method), 86
- find_bookmark() (PyPDF2.PdfWriter method), 78

- Fit (class in PyPDF2.generic), 115
- fit() (PyPDF2.generic.Fit class method), 115
- fit_box() (PyPDF2.generic.Fit class method), 115

- flags (PyPDF2.generic.Field property), 109

G

- get_contents() (PyPDF2._page.PageObject method), 91 get_destination_page_number() (PyPDF2.PdfReader method), 68 (PyPDF2.xmp.XmpInformation get_element() method), 102 get_fields() (PyPDF2.PdfReader method), 68 get_form_text_fields() (PyPDF2.PdfReader method), 69 get_named_dest_root() (PyPDF2.PdfWriter method), 78 get_nodes_in_namespace() (PyPDF2.xmp.XmpInformation *method*). 102 get_object() (PyPDF2.PdfReader method), 69 get_object() (PyPDF2.PdfWriter method), 78 get_outline_root() (PyPDF2.PdfWriter method), 78 get_page() (PyPDF2.PdfWriter method), 78 get_page_number() (*PvPDF2.PdfReader method*), 69 get_reference() (PyPDF2.PdfWriter method), 78
- getDestArray() (PyPDF2.generic.Destination method), 105
- getDocumentInfo() (PyPDF2.PdfReader method), 68

- getFields() (PyPDF2.PdfReader method), 68
- getHeight() (PyPDF2.generic.RectangleObject method), 107
- getIsEncrypted() (PyPDF2.PdfReader method), 68

getNamedDestRoot() (PyPDF2.PdfWriter method), 78
getNodesInNamespace()

- (*PyPDF2.xmp.XmpInformation* method), 102
- getNumPages() (PyPDF2.PdfReader method), 68 getNumPages() (PyPDF2.PdfWriter method), 78 getObject() (PyPDF2.PdfReader method), 68 getObject() (PyPDF2.PdfWriter method), 78 getOutlineRoot() (PyPDF2.PdfWriter method), 78 getOutlines() (PyPDF2.PdfReader method), 68 getPage() (PyPDF2.PdfReader method), 68 getPage() (PyPDF2.PdfWriter method), 78 getPageLayout() (PvPDF2.PdfReader method), 68 getPageLayout() (*PyPDF2.PdfWriter method*), 78 getPageMode() (PyPDF2.PdfReader method), 68 getPageMode() (PyPDF2.PdfWriter method), 78 getPageNumber() (PyPDF2.PdfReader method), 68 getReference() (PyPDF2.PdfWriter method), 78 getText() (PyPDF2.DocumentInformation method), 99 getUpperLeft() (PyPDF2.generic.RectangleObject method), 107 getUpperLeft_x() (PyPDF2.generic.RectangleObject method), 107 getUpperLeft_y() (PyPDF2.generic.RectangleObject method), 107 getUpperRight() (PyPDF2.generic.RectangleObject method), 107 getUpperRight_x() (PyPDF2.generic.RectangleObject method), 107 getUpperRight_y() (PyPDF2.generic.RectangleObject method), 107
- getWidth() (PyPDF2.generic.RectangleObject

method), 107
getXmpMetadata() (PyPDF2.PdfReader method), 68

Η

hash_value_data()		(PyPDF2page.	PageObject
height	method), 91 (PvPDF2.generic	RectangleObject	property).
5	107		I I

I

- images (PyPDF2._page.PageObject property), 91
- indices() (PyPDF2.PageRange method), 111
- insert_blank_page() (PyPDF2.PdfWriter method),
 79
- insert_page() (PyPDF2.PdfWriter method), 79
 insertBlankPage() (PyPDF2.PdfWriter method), 79
 insertPage() (PyPDF2.PdfWriter method), 79
 is_encrypted (PyPDF2.PdfReader property), 69
- isEncrypted (*PyPDF2.PdfReader property*), 69

Κ

kids (PyPDF2.generic.Field property), 109

L

left (*PyPDF2.generic.Destination property*), 105

- left (*PyPDF2.generic.RectangleObject property*), 107
- line() (PyPDF2.generic.AnnotationBuilder static method), 113
- link() (PyPDF2.generic.AnnotationBuilder static method), 114
- lower_left (PyPDF2.generic.RectangleObject property), 108
- lower_right (PyPDF2.generic.RectangleObject property), 108
- lowerRight (PyPDF2.generic.RectangleObject property), 108

Μ

mapping_name (PyPDF2.generic.Field property), 110
mappingName (PyPDF2.generic.Field property), 109
matrix (PyPDF2.Transformation property), 98
mediaBox (PyPDF2.page.PageObject property), 92
mediabox (PyPDF2.page.PageObject property), 92
merge() (PyPDF2.PdfMerger method), 86
merge() (PyPDF2.PdfWriter method), 79
mergePage() (PyPDF2.page.PageObject method), 94
mergePage() (PyPDF2.page.PageObject method), 92
mergeRotatedPage() (PyPDF2.page.PageObject method), 92

mergeRotatedScaledPage() (PyPDF2._page.PageObject method), 92 mergeRotatedScaledTranslatedPage() (PyPDF2._page.PageObject method), 92 mergeRotatedTranslatedPage() (PvPDF2. page.PageObject method), 93 mergeScaledPage() (PyPDF2. page.PageObject method), 93 mergeScaledTranslatedPage() (PyPDF2._page.PageObject method), 93 mergeTransformedPage() (PyPDF2._page.PageObject method), 94 mergeTranslatedPage() (PyPDF2._page.PageObject method), 94 metadata (PyPDF2.PdfReader property), 69 modification_date (PyPDF2.DocumentInformation property), 99 modification_date_raw (PyPDF2.DocumentInformation property), 99

Ν

0

open_destination (PyPDF2.PdfWriter property), 80
original_page (PyPDF2._page.PageObject attribute),
 94
outline (PyPDF2.PdfReader property), 69
outline_count (PyPDF2.generic.Destination prop erty), 105
outlines (PyPDF2.PdfReader property), 70

Ρ

page (*PyPDF2.generic.Destination property*), 105 page_layout (*PyPDF2.PdfReader property*), 70 page_layout (*PyPDF2.PdfReader property*), 80 page_mode (*PyPDF2.PdfReader property*), 70 page_mode (*PyPDF2.PdfWriter property*), 80 pageLayout (*PyPDF2.PdfReader property*), 70 pageLayout (*PyPDF2.PdfReader property*), 70 pageMode (*PyPDF2.PdfReader property*), 80 pageMode (*PyPDF2.PdfReader property*), 80 PageObject (*class in PyPDF2.page*), 89 PageRange (*class in PyPDF2*), 111 pages (*PyPDF2.PdfReader property*), 70 pages (*PyPDF2.PdfReader property*), 81 PaperSize (*class in PyPDF2*), 117 parent (*PyPDF2.generic.Field property*), 110

- pdf_header (PyPDF2.PdfReader property), 71
- pdf_header (*PyPDF2.PdfWriter property*), 81
- pdf_keywords (PyPDF2.xmp.XmpInformation property), 102
- pdf_pdfversion (PyPDF2.xmp.XmpInformation property), 102
- pdf_producer (*PyPDF2.xmp.XmpInformation property*), 102
- PdfMerger (class in PyPDF2), 85
- PdfReader (class in PyPDF2), 67
- PdfWriter (*class in PyPDF2*), 73
- producer (*PyPDF2.DocumentInformation property*), 100
- producer_raw (*PyPDF2.DocumentInformation property*), 100

R

- rdfRoot (*PyPDF2.xmp.XmpInformation property*), 102 read() (*PyPDF2.PdfReader method*), 71
- read_next_end_line() (PyPDF2.PdfReader method),
 71
- read_object_header() (PyPDF2.PdfReader method),
 71
- readNextEndLine() (PyPDF2.PdfReader method), 71
- readObjectHeader() (PyPDF2.PdfReader method), 71
- **rectangle()** (*PyPDF2.generic.AnnotationBuilder static method*), 114
- RectangleObject (*class in PyPDF2.generic*), 107
- remove_images() (PyPDF2.PdfWriter method), 81
- remove_links() (*PyPDF2.PdfWriter method*), 81
- remove_text() (PyPDF2.PdfWriter method), 81
- removeImages() (PyPDF2.PdfWriter method), 81
- removeLinks() (*PyPDF2.PdfWriter method*), 81
- removeText() (PyPDF2.PdfWriter method), 81
- reset_translation() (*PyPDF2.PdfWriter method*), 81
- right (PyPDF2.generic.Destination property), 105
- right (PyPDF2.generic.RectangleObject property), 108
- rotate() (PyPDF2. page.PageObject method), 94
- rotate() (PyPDF2.Transformation method), 98
- rotate_clockwise() (PyPDF2._page.PageObject method), 95
- rotateClockwise() (PyPDF2._page.PageObject method), 94
- rotateCounterClockwise()
- (*PyPDF2._page.PageObject method*), 95 rotation (*PyPDF2._page.PageObject property*), 95

S

- scale() (PyPDF2._page.PageObject method), 95
 scale() (PyPDF2.generic.RectangleObject method),
 108
 scale() (PyPDF2.Transformation method), 98
- scale_by() (PyPDF2._page.PageObject method), 95

- scale_to() (PyPDF2._page.PageObject method), 95
- scaleBy() (PyPDF2._page.PageObject method), 95
- scaleTo() (PyPDF2._page.PageObject method), 95
- set_page_layout() (*PyPDF2.PdfMerger method*), 87
- set_page_tayout() (PyPDF2.PajMerger method), 87
- set_page_layout() (PyPDF2.PdfWriter method), 81
- set_page_mode() (PyPDF2.PdfMerger method), 87
- set_page_mode() (PyPDF2.PdfWriter method), 82
- setLowerLeft() (PyPDF2.generic.RectangleObject
 method), 108
- setLowerRight() (PyPDF2.generic.RectangleObject
 method), 108
- setPageLayout() (PyPDF2.PdfMerger method), 87
- setPageLayout() (PyPDF2.PdfWriter method), 81
- setPageMode() (PyPDF2.PdfMerger method), 87
- setPageMode() (PyPDF2.PdfWriter method), 81
- setUpperLeft() (PyPDF2.generic.RectangleObject method), 108
- setUpperRight() (PyPDF2.generic.RectangleObject method), 108
- subject (PyPDF2.DocumentInformation property), 100
 subject_raw (PyPDF2.DocumentInformation property), 100

Т

- text() (PyPDF2.generic.AnnotationBuilder static method), 114 threads (PyPDF2.PdfReader property), 71
- threads (*PyPDF2.PdfWriter property*), 82
- title (*PyPDF2.DocumentInformation property*), 100
- title (*PyPDF2.generic.Destination property*), 10
- title_raw (*PyPDF2.DocumentInformation property*), 100
- to_slice() (PyPDF2.PageRange method), 111
- top (PyPDF2.generic.Destination property), 106
- top (PyPDF2.generic.RectangleObject property), 108
- transfer_rotation_to_content()

erty), 108

(PyPDF2._page.PageObject method), 95 Transformation (class in PyPDF2), 97 translate() (PyPDF2.Transformation method), 98 trimBox (PyPDF2._page.PageObject property), 95 trimbox (PyPDF2._page.PageObject property), 95 typ (PyPDF2.generic.Destination property), 106

U

V

valid() (PyPDF2.PageRange static method), 111
value (PyPDF2.generic.Field property), 110

W

Х

xfa (PyPDF2.PdfReader property), 71 (PyPDF2.xmp.XmpInformation xmp_create_date property), 102 xmp_createDate (PyPDF2.xmp.XmpInformation property), 102 xmp_creator_tool (PyPDF2.xmp.XmpInformation property), 102 xmp_creatorTool (PyPDF2.xmp.XmpInformation property), 102 xmp_metadata (PyPDF2.PdfReader property), 71 xmp_metadata_date (PvPDF2.xmp.XmpInformation property), 102 xmp_metadataDate (PyPDF2.xmp.XmpInformation property), 102 xmp_modify_date (PyPDF2.xmp.XmpInformation property), 103 xmp_modifyDate (PyPDF2.xmp.XmpInformation property), 102 XmpInformation (class in PyPDF2.xmp), 101 xmpMetadata (PyPDF2.PdfReader property), 71 xmpmm_document_id (PyPDF2.xmp.XmpInformation property), 103 xmpmm_documentId (PyPDF2.xmp.XmpInformation property), 103 xmpmm_instance_id (PyPDF2.xmp.XmpInformation property), 103 xmpmm_instanceId (PyPDF2.xmp.XmpInformation property), 103 xyz() (PyPDF2.generic.Fit class method), 116

Ζ

zoom (PyPDF2.generic.Destination property), 106